

Package ‘httk’

March 25, 2022

Version 2.1.0

Date 2022-03-22

Title High-Throughput Toxicokinetics

Description Generic models and chemical-specific data for simulation and statistical analysis of chemical toxicokinetics (“TK”) as described by Pearce et al. (2017) <[doi:10.18637/jss.v079.i04](https://doi.org/10.18637/jss.v079.i04)>. Chemical-specific in vitro data have been obtained from relatively high-throughput experiments. Both physiologically-based (“PBTK”) and empirical (for example, one compartment) “TK” models can be parameterized with the data provided for thousands of chemicals, multiple exposure routes, and various species. The models consist of systems of ordinary differential equations which are solved using compiled (C-based) code for speed. A Monte Carlo sampler is included, which allows for simulating human biological variability (Ring et al., 2017 <[doi:10.1016/j.envint.2017.06.004](https://doi.org/10.1016/j.envint.2017.06.004)>) and propagating parameter uncertainty. Calibrated methods are included for predicting tissue:plasma partition coefficients and volume of distribution (Pearce et al., 2017 <[doi:10.1007/s10928-017-9548-7](https://doi.org/10.1007/s10928-017-9548-7)>). These functions and data provide a set of tools for in vitro-in vivo extrapolation (“IVIVE”) of high-throughput screening data (for example, Tox21, ToxCast) to real-world exposures via reverse dosimetry (also known as “RTK”) (Wetmore et al., 2015 <[doi:10.1093/toxsci/kfv171](https://doi.org/10.1093/toxsci/kfv171)>).

Depends R (>= 2.10)

Imports deSolve, msm, data.table, survey, mvtnorm, truncnorm, stats, graphics, utils, magrittr, purrr, methods, Rdpack

RdMacros Rdpack

Suggests ggplot2,
knitr,
rmarkdown,
R.rsp,
GGally,
gplots,
scales,
EnvStats,
MASS,
RColorBrewer,

TeachingDemos,
 classInt,
 ks,
 stringr,
 reshape,
 reshape2,
 viridis,
 CensRegMod,
 gmodels,
 colorspace,
 cowplot,
 ggrepel,
 dplyr,
 forcats,
 smatr,
 gridExtra,
 testthat

License GPL-3

LazyData true

LazyDataCompression xz

Encoding UTF-8

VignetteBuilder knitr, R.rsp

RoxygenNote 7.1.1

URL <https://www.epa.gov/chemical-research/rapid-chemical-exposure-and-dose-research>

BugReports <https://github.com/USEPA/CompTox-ExpoCast-httpk>

NeedsCompilation yes

Author John Wambaugh [aut, cre] (<<https://orcid.org/0000-0002-4024-534X>>),
 Sarah Davidson [aut] (<<https://orcid.org/0000-0002-2891-9380>>),
 Robert Pearce [aut] (<<https://orcid.org/0000-0003-3168-4049>>),
 Caroline Ring [aut] (<<https://orcid.org/0000-0002-0463-1251>>),
 Greg Honda [aut] (<<https://orcid.org/0000-0001-7713-9850>>),
 Mark Sfeir [aut],
 Matt Linakis [aut] (<<https://orcid.org/0000-0003-0526-2395>>),
 Dustin Kapraun [aut] (<<https://orcid.org/0000-0001-5570-6383>>),
 Miyuki Breen [ctb] (<<https://orcid.org/0000-0001-8511-4653>>),
 Shannon Bell [ctb] (<<https://orcid.org/0000-0002-5754-6085>>),
 Xiaoqing Chang [ctb] (<<https://orcid.org/0000-0003-0752-1848>>),
 Todor Antonijevic [ctb] (<<https://orcid.org/0000-0002-0248-8412>>),
 Jimena Davis [ctb],
 James Sluka [ctb] (<<https://orcid.org/0000-0002-5901-1404>>),
 Nisha Sipes [ctb] (<<https://orcid.org/0000-0003-4203-6426>>),
 Barbara Wetmore [ctb] (<<https://orcid.org/0000-0002-6878-5348>>),
 Woodrow Setzer [ctb] (<<https://orcid.org/0000-0002-6709-9186>>)

Maintainer John Wambaugh <wambaugh.john@epa.gov>

Copyright This package is primarily developed by employees of the U.S. Federal government as part of their official duties and is therefore public domain.

R topics documented:

httk-package	6
add_chemtable	7
age_dist_smooth	9
age_draw_smooth	10
armitage_estimate_sarea	11
armitage_eval	12
armitage_input	16
augment.table	17
available_rblood2plasma	18
aylward2014	19
blood_mass_correct	20
blood_weight	21
bmiage	21
body_surface_area	22
bone_mass_age	23
brain_mass	24
calc_analytic_css	24
calc_analytic_css_1comp	27
calc_analytic_css_3comp	28
calc_analytic_css_3compss	29
calc_analytic_css_pbtck	31
calc_css	32
calc_elimination_rate	34
calc_fetal_phys	36
calc_half_life	41
calc_hepatic_clearance	43
calc_hep_bioavailability	44
calc_hep_clearance	45
calc_hep_fu	47
calc_ionization	48
calc_krbc2pu	50
calc_maternal_bw	51
calc_mc_css	52
calc_mc_oral_equiv	56
calc_mc_tk	58
calc_rblood2plasma	62
calc_stats	63
calc_tkstats	65
calc_total_clearance	67
calc_vdist	68
CAS.checksum	70
chem.invivo.PK.aggregate.data	71
chem.invivo.PK.data	71
chem.invivo.PK.summary.data	74
chem.lists	77
chem.physical_and_invitro.data	78
ckd_epi_eq	81
concentration_data_Linakis2020	82
convert_httkpop_1comp	83
convert_solve_x	83

convert_units	85
create_mc_samples	87
dawson2021	89
EPA.ref	90
estimate_gfr	91
estimate_gfr_ped	91
estimate_hematocrit	92
export_pbt_k_jarnac	93
export_pbt_k_sbml	94
fetalpcs	95
Frank2018invivo	95
gen_age_height_weight	96
gen_height_weight	97
gen_serum_creatinine	98
get_cheminfo	98
get_chem_id	101
get_gfr_category	102
get_invitroPK_param	103
get_lit_cheminfo	103
get_lit_css	104
get_lit_oral_equiv	106
get_physchem_param	107
get_rblood2plasma	108
get_weight_class	109
hematocrit_infants	110
honda.ivive	110
howgate	112
httkpop	112
httkpop_biotophys_default	117
httkpop_direct_resample	117
httkpop_direct_resample_inner	119
httkpop_generate	120
httkpop_mc	122
httkpop_virtual_indiv	123
in.list	125
invitro_mc	126
is.httk	128
is_in_inclusive	130
johnson	130
kapraun2019	131
kidney_mass_children	132
liver_mass_children	132
load_dawson2021	133
load_pradeep2020	134
load_sipes2017	135
lump_tissues	136
lung_mass_children	138
mcnally_dt	138
metabolism_data_Linakis2020	139
monte_carlo	140
nhanes_mec_svy	141
Obach2008	142

onlyp	143
pancreas_mass_children	143
parameterize_1comp	144
parameterize_3comp	146
parameterize_fetal_pbtok	148
parameterize_gas_pbtok	151
parameterize_pbtok	154
parameterize_schmitt	157
parameterize_steadystate	159
pc.data	161
pearce2017regression	162
pharma	162
physiology.data	163
pksim.pcs	164
pradeep2020	164
predict_partitioning_schmitt	165
pregnonpregaucs	167
propagate_invitrouv_1comp	167
propagate_invitrouv_3comp	168
propagate_invitrouv_pbtok	168
reset_httk	169
rfun	170
r_left_censored_norm	170
scale_dosing	171
set_httk_precision	172
sipes2017	172
skeletal_muscle_mass	173
skeletal_muscle_mass_children	174
skin_mass_bosgra	174
solve_1comp	175
solve_3comp	179
solve_fetal_pbtok	183
solve_gas_pbtok	186
solve_model	191
solve_pbtok	194
spleen_mass_children	199
spline_heightweight	200
spline_hematocrit	200
spline_serumcreat	201
supptab1_Linakis2020	202
supptab2_Linakis2020	202
Tables.Rdata.stamp	203
tissue.data	203
tissue_masses_flows	204
tissue_scale	205
wambaugh2019	206
wambaugh2019.nhanes	207
wambaugh2019.raw	208
wambaugh2019.seem3	210
wambaugh2019.tox21	210
wang2018	211
well_param	212

Wetmore.data	213
Wetmore2012	213
wfl	214

Index	216
--------------	------------

httk-package	<i>High-Throughput Toxicokinetics</i>
--------------	---------------------------------------

Description

Generic models and chemical-specific data for simulation and statistical analysis of chemical toxicokinetics ("TK") as described by Pearce et al. (2017) <doi:10.18637/jss.v079.i04>. Chemical-specific in vitro data have been obtained from relatively high-throughput experiments. Both physiologically-based ("PBTK") and empirical (for example, one compartment) "TK" models can be parameterized with the data provided for thousands of chemicals, multiple exposure routes, and various species. The models consist of systems of ordinary differential equations which are solved using compiled (C-based) code for speed. A Monte Carlo sampler is included, which allows for simulating human biological variability (Ring et al., 2017 <doi:10.1016/j.envint.2017.06.004>) and propagating parameter uncertainty. Calibrated methods are included for predicting tissue:plasma partition coefficients and volume of distribution (Pearce et al., 2017 <doi:10.1007/s10928-017-9548-7>). These functions and data provide a set of tools for in vitro-in vivo extrapolation ("IVIVE") of high-throughput screening data (for example, Tox21, ToxCast) to real-world exposures via reverse dosimetry (also known as "RTK") (Wetmore et al., 2015 <doi:10.1093/toxsci/kfv171>).

Author(s)

John Wambaugh, Robert Pearce, Caroline Ring, Gregory Honda, Nisha Sipes, Jimena Davis, Barbara Wetmore, Woodrow Setzer, Mark Sfeir

See Also

PowerPoint Presentation: High-Throughput Toxicokinetics (HTTK) R package

doi: [10.1080/17425255.2021.1935867](https://doi.org/10.1080/17425255.2021.1935867)Breen et al. (2021): High-throughput PBTK models for in vitro to in vivo extrapolation

doi: [10.18637/jss.v079.i04](https://doi.org/10.18637/jss.v079.i04)Pearce et al. (2017): httk: R Package for High-Throughput Toxicokinetics

doi: [10.1021/es501955g](https://doi.org/10.1021/es501955g)Armitage et al. (2014): Application of mass balance models and the chemical activity concept to facilitate the use of in vitro toxicity data for risk assessment

doi: [10.1093/toxsci/kfv171](https://doi.org/10.1093/toxsci/kfv171)Incorporating High-Throughput Exposure Predictions with Dosimetry-Adjusted In Vitro Bioactivity to Inform Chemical Toxicity Testing

doi: [10.1093/toxsci/kfv118](https://doi.org/10.1093/toxsci/kfv118)Wambaugh et al. (2015): Toxicokinetic Triage for Environmental Chemicals

doi: [10.1007/s1092801795487](https://doi.org/10.1007/s1092801795487)Pearce et al. (2017): Evaluation and calibration of high-throughput predictions of chemical distribution to tissues

doi: [10.1016/j.envint.2017.06.004](https://doi.org/10.1016/j.envint.2017.06.004)Ring et al. (2017): Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability

doi: [10.1021/acs.est.7b00650](https://doi.org/10.1021/acs.est.7b00650)Sipes et al. (2017): An Intuitive Approach for Predicting Potential Human Health Risk with the Tox21 10k Library

doi: [10.1093/toxsci/kfy020](https://doi.org/10.1093/toxsci/kfy020) Wambaugh et al. (2018): Evaluating In Vitro-In Vivo Extrapolation of Toxicokinetics

doi: [10.1371/journal.pone.0217564](https://doi.org/10.1371/journal.pone.0217564) Honda et al. (2019): Using the concordance of in vitro and in vivo data to evaluate extrapolation assumptions

doi: [10.1093/toxsci/kfz205](https://doi.org/10.1093/toxsci/kfz205) Wambaugh et al. (2019): Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization

doi: [10.1038/s413700200238](https://doi.org/10.1038/s413700200238) Linakis et al. (2020): Development and evaluation of a high-throughput inhalation model for organic chemicals

The U.S. EPA ExpoCast (Exposure Forecasting) Project

add_chemtable

Add a table of chemical information for use in making htk predictions.

Description

This function adds chemical-specific information to the table `chem.physical_and_invitro.data`. This table is queried by the model parameterization functions when attempting to parameterize a model, so adding sufficient data to this table allows additional chemicals to be modeled.

Usage

```
add_chemtable(
  new.table,
  data.list,
  current.table = NULL,
  reference = NULL,
  species = NULL,
  overwrite = FALSE,
  sig.fig = 4,
  clint.pvalue.overwrite = TRUE,
  allow.na = FALSE
)
```

Arguments

<code>new.table</code>	Object of class <code>data.frame</code> containing one row per chemical, with each chemical minimally described by a CAS number.
<code>data.list</code>	This list identifies which properties are to be read from the table. Each item in the list should point to a column in the table <code>new.table</code> . Valid names in the list are: <code>'Compound'</code> , <code>'CAS'</code> , <code>'DSSTox.GSID'</code> , <code>'SMILES.desalt'</code> , <code>'Reference'</code> , <code>'Species'</code> , <code>'MW'</code> , <code>'logP'</code> , <code>'pKa_Donor'</code> , <code>'pKa_Accept'</code> , <code>'logMA'</code> , <code>'Clint'</code> , <code>'Clint.pValue'</code> , <code>'Funbound.plasma'</code> , <code>'Fgutabs'</code> , <code>'Rblood2plasma'</code> .
<code>current.table</code>	This is the table to which data are being added.
<code>reference</code>	This is the reference for the data in the new table. This may be omitted if a column in <code>data.list</code> gives the reference value for each chemical.
<code>species</code>	This is the species for the data in the new table. This may be omitted if a column in <code>data.list</code> gives the species value for each chemical or if the data are not species-specific (e.g., MW).

overwrite	If overwrite=TRUE then data in current.table will be replaced by any data in new.table that is for the same chemical and property. If overwrite=FALSE (DEFAULT) then new data for the same chemical and property are ignored. Funbound.plasma values of 0 (below limit of detection) are overwritten either way.
sig.fig	Sets the number of significant figures stored (defaults to 4)
clint.pvalue.overwrite	If TRUE then the CL_int p-value is set to NA when the CL_int value is changed unless a new p-value is provided. (defaults to TRUE)
allow.na	If TRUE (default is FALSE) then NA values are written to the table, otherwise they are ignored.

Value

data.frame	A new data.frame containing the data in current.table augmented by new.table
------------	--

Author(s)

John Wambaugh

Examples

```
library(httk)
my.new.data <- as.data.frame(c("A", "B", "C"), stringsAsFactors=FALSE)
my.new.data <- cbind(my.new.data, as.data.frame(c(
  "111-11-2", "222-22-0", "333-33-5"),
  stringsAsFactors=FALSE))
my.new.data <- cbind(my.new.data, as.data.frame(c("DTX1", "DTX2", "DTX3"),
  stringsAsFactors=FALSE))
my.new.data <- cbind(my.new.data, as.data.frame(c(200, 200, 200)))
my.new.data <- cbind(my.new.data, as.data.frame(c(2, 3, 4)))
my.new.data <- cbind(my.new.data, as.data.frame(c(0.01, 0.02, 0.3)))
my.new.data <- cbind(my.new.data, as.data.frame(c(0, 10, 100)))
colnames(my.new.data) <- c("Name", "CASRN", "DTXSID", "MW", "LogP", "Fup", "CLint")

chem.physical_and_invitro.data <- add_chemtable(my.new.data,
  current.table=
    chem.physical_and_invitro.data,
  data.list=list(
    Compound="Name",
    CAS="CASRN",
    DTXSID="DTXSID",
    MW="MW",
    logP="LogP",
    Funbound.plasma="Fup",
    Clint="CLint"),
  species="Human",
  reference="MyPaper 2015")

parameterize_steadystate(chem.name="C")
calc_css(chem.name="B")

# Initialize a column describing proton donors ("acids")
my.new.data$pka.a <- NA
# set chemical C to an acid (pKa_donor = 5):
my.new.data[my.new.data$Name=="C", "pka.a"] <- "5"
```



```
chem.physical_and_invitro.data <- add_chemtable(my.new.data,
  current.table=
    chem.physical_and_invitro.data,
  data.list=list(
    Compound="Name",
    CAS="CASRN",
    DTXSID="DTXSID",
    pKa_Donor="pka.a"),
  species="Human",
  reference="MyPaper 2015")

# Note Rblood2plasma and hepatic bioavailability change (relative to above):
parameterize_steadystate(chem.name="C")

# Initialize a column describing proton acceptors ("bases")
my.new.data$pka.b <- NA
# set chemical B to a base with multiple pka's (pKa_accept = 7 and 8):
my.new.data[my.new.data$Name=="B", "pka.b"] <- "7;8"
chem.physical_and_invitro.data <- add_chemtable(my.new.data,
  current.table=
    chem.physical_and_invitro.data,
  data.list=list(
    Compound="Name",
    CAS="CASRN",
    DTXSID="DTXSID",
    pKa_Accept="pka.b"),
  species="Human",
  reference="MyPaper 2015")

# Note that average and max change (relative to above):
calc_css(chem.name="B")
```

age_dist_smooth

Smoothed age distributions by race and gender.

Description

Distributions of ages in months, computed from NHANES data smoothed using `survey::svsmooth()`, for each combination of race/ethnicity and gender.

Usage

```
age_dist_smooth
```

Format

A `data.table` object with three variables:

`gender` Gender: Male or Female

`reth` Race/ethnicity

`smth` A list of `svsmooth` objects, each encoding a weighted smoothed distribution of ages.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

age_draw_smooth	<i>Draws ages from a smoothed distribution for a given gender/race combination</i>
-----------------	--

Description

Draws ages from a smoothed distribution for a given gender/race combination

Usage

```
age_draw_smooth(g, r, nsamp, agelim_months)
```

Arguments

<code>g</code>	Gender. Either 'Male' or 'Female'.
<code>r</code>	Race/ethnicity. One of 'Mexican American', 'Other Hispanic', 'Non-Hispanic Black', 'Non-Hispanic White', 'Other'.
<code>nsamp</code>	Number of ages to draw.
<code>agelim_months</code>	Two-element numeric vector giving the minimum and maximum ages in months to include.

Value

A named list with members 'ages_months' and 'ages_years', each numeric of length `nsamp`, giving the sampled ages in months and years.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

armitage_estimate_sarea

Estimate well surface area

Description

Estimate geometry surface area of plastic in well plate based on well plate format suggested values from Corning. `option.plastic == TRUE` (default) give nonzero surface area (sarea, m²) `option.bottom == TRUE` (default) includes surface area of the bottom of the well in determining sarea. Optionally include user values for working volume (v_working, m³) and surface area.

Usage

```
armitage_estimate_sarea(
  tcdata = NA,
  this.well_number = 384,
  this.cell_yield = NA,
  this.v_working = NA
)
```

Arguments

tcdata	A data table with well_number corresponding to plate format, optionally include v_working, sarea, option.bottom, and option.plastic
this.well_number	For single value, plate format default is 384, used if <code>is.na(tcdata) == TRUE</code>
this.cell_yield	For single value, optionally supply cell_yield, otherwise estimated based on well number
this.v_working	For single value, optionally supply working volume, otherwise estimated based on well number (m ³)

Value

A data table composed of any input data.table *tcdata* with only the following columns either created or altered by this function:

Column Name	Description	Units
well_number	number of wells on plate	
sarea	surface area	m ²
cell_yield	number of cells	cells
v_working	working (filled) volume of each well	uL
v_total	total volume of each well	uL

Author(s)

Greg Honda

References

Armitage, J. M., Arnot, J. A., Wania, F., & Mackay, D. (2013). Development and evaluation of a mechanistic bioconcentration model for ionogenic organic chemicals in fish. *Environmental toxicology and chemistry*, 32(1), 115-128.

armitage_eval

Evaluate the updated Armitage model

Description

Evaluate the Armitage model for chemical distributon in vitro. Takes input as data table or vectors of values. Outputs a data table. Updates over the model published in Armitage et al. 2014 include binding to plastic walls and lipid and protein compartments in cells.

Usage

```
armitage_eval(
  casrn.vector = NA_character_,
  nomconc.vector = 1,
  this.well_number = 384,
  this.FBSf = NA_real_,
  tcdata = NA,
  this.sarea = NA_real_,
  this.v_total = NA_real_,
  this.v_working = NA_real_,
  this.cell_yield = NA_real_,
  this.Tsys = 37,
  this.Tref = 298.15,
  this.option.kbsa2 = FALSE,
  this.option.swat2 = FALSE,
  this.pseudooct = 0.01,
  this.memblip = 0.04,
  this.nlom = 0.2,
  this.P_nlom = 0.035,
  this.P_dom = 0.05,
  this.P_cells = 1,
  this.csalt = 0.15,
  this.celldensity = 1,
  this.cellmass = 3,
  this.f_oc = 1,
  this.conc_ser_alb = 24,
  this.conc_ser_lip = 1.9,
  this.Vdom = 0
)
```

Arguments

casrn.vector For vector or single value, CAS number
 nomconc.vector For vector or single value, micromolar nominal concentration (e.g. AC50 value)

this.well_number	For single value, plate format default is 384, used if is.na(tcdata)==TRUE
this.FBSf	Fraction fetal bovine serum, must be entered by user.
tcdata	A data.table with casrn, nomconc, MP, gkow, gkaw, gswat, sarea, v_total, v_working. Otherwise supply single values to this.params.
this.sarea	Surface area per well (m ²)
this.v_total	Total volume per well (m ³)
this.v_working	Working volume per well (m ³)
this.cell_yield	Number of cells per well
this.Tsys	System temperature (degrees C)
this.Tref	Reference temperature (degrees K)
this.option.kbsa2	Use alternative bovine-serum-albumin partitioning model
this.option.swat2	Use alternative water solubility correction
this.pseudooct	Pseudo-octanol cell storage lipid content
this.memblip	Membrane lipid content of cells
this.nlom	Structural protein content of cells
this.P_nlom	Proportionality constant to octanol structural protein
this.P_dom	Proportionality constant to dissolve organic material
this.P_cells	Proportionality constant to octanol storage lipid
this.csalt	Ionic strength of buffer, mol/L
this.celldensity	Cell density kg/L, g/mL
this.cellmass	Mass per cell, ng/cell
this.f_oc	1, everything assumed to be like proteins
this.conc_ser_alb	24 g/L, mass concentration of albumin in serum.
this.conc_ser_lip	1.9 g/L, mass concentration of lipids in serum.
this.Vdom	0 ml, the volume of dissolved organic matter (DOM)

Value

Column	Description	units
casrn	Chemical Abstracts Service Registry Number	
nomconc	Nominal Concentration	mol/L
well_number	Number of wells in plate	unitless
sarea	Surface area of well	m ²
v_total	Total volume of well	m ³
v_working	Filled volume of well	m ³
cell_yield	Number of cells	cells
gkow	log10 octanol to water partition coefficient (PC)	log10
logHenry	log10 Henry's law constant	log10 atm-m ³ /mol
gswat	log10 Water solubility	log10 mol/L

MP	Melting Point	degrees Celsius
MW	Molecular Weight	g/mol
gkaw	air-water partition coefficient	(mol/m ³)/(mol/m ³)
dsm		
duow		
duaw		
dumw		
gkmw		
gkcw		
gksa		
gkpl		
ksalt		
Tsys		
Tref		
option.kbsa2		
option.swat2		
FBSf		
pseudooct		
memblip		
nlom		
P_nlom		
P_dom	dissolved organic matter to water PC	Dimensionless
P_cells		
csalt		
celldensity		
cellmass		
f_oc		
cellwat		
Tcor		
Vm	Volume of media	L
Vwell	volume of medium (aqueous phase only)	L
Vair	volume of head space	L
Vcells	volume of cells/tissue	
Valb	volume of serum albumin	
Vslip	volume of serum lipids	
Vdom	volume of dissolved organic matter	
F_ratio		
gs1.GSE		
s1.GSE		
gss.GSE		
ss.GSE		
kmw		
kow	octanol to water PC	
kaw	the air to water PC	dimensionless
swat		
kpl		
kcw	cell/tissue to water PC	dimensionless
kbsa		
swat_L		
oct_L		
scell_L		
cinit	Initial concentration	mol

mtot	Total moles	mol
cwat	Total concentration in water	mol/L
cwat_s	Dissolved concentration in water	mol/L
csat	Is the solution saturated (1/0)	Boolean
activity		
cair		mol/L
calb		mol/L
cslip		mol/L
cdom	concentration of/in dissolved organic matter	mol/L
ccells		mol/L
cplastic		mol/L
mwat_s	Mass dissolved in water	mols
mair	Mass in air	mols
mbsa	Mass bound to bovine serum albumin	mols
mslip	Mass bound to serum lipids	mols
mdom	Mass bound to dissolved organic matter	mols
mcells	Mass in cells	mols
mplastic	Mass bond to plastic	mols
mprecip	Mass precipitated out of solution	
xwat_s	Fraction dissolved in water	fraction
xair	Fraction in the air	fraction
xbsa	Fraction bound to bovine serum albumin	fraction
xslip	Fraction bound to serum lipids	fraction
xdom	Fraction bound to dissolved organic matter	fraction
xcells	Fraction within cells	fraction
xplastic	Fraction bound to plastic	fraction
xprecip	Fraction precipitated out of solution	fraction
eta_free	effective availability ratio	fraction
cfree.invitro	Free concentration in the in vitro media (use for Honda1 and Honda2)	micromolar

Author(s)

Greg Honda

References

Armitage, J. M.; Wania, F.; Arnot, J. A. Environ. Sci. Technol. 2014, 48, 9770-9779. <https://doi.org/10.1021/es501955g>
 Honda et al. PloS one 14.5 (2019): e0217564. <https://doi.org/10.1371/journal.pone.0217564>

Examples

```
library(httk)

# Check to see if we have info on the chemical:
"80-05-7" %in% get_cheminfo()

#We do:
temp <- armitage_eval(casrn.vector = c("80-05-7", "81-81-2"), this.FBSf = 0.1,
  this.well_number = 384, nomconc = 10)
```

```
print(temp$cfree.invitro)

# Check to see if we have info on the chemical:
"793-24-8" %in% get_cheminfo()

# Since we don't have any info, let's look up phys-chem from dashboard:
cheminfo <- data.frame(
  Compound="6-PPD",
  CASRN="793-24-8",
  DTXSID="DTXSID9025114",
  logP=4.27,
  logHenry=log10(7.69e-8),
  logWSol=log10(1.58e-4),
  MP= 99.4,
  MW=268.404
)

# Add the information to HTK's database:
chem.physical_and_invitro.data <- add_chemtable(
  cheminfo,
  current.table=chem.physical_and_invitro.data,
  data.list=list(
    Compound="Compound",
    CAS="CASRN",
    DTXSID="DTXSID",
    MW="MW",
    logP="logP",
    logHenry="logHenry",
    logWSol="logWSol",
    MP="MP"),
  species="Human",
  reference="CompTox Dashboard 31921")

# Run the Armitage et al. (2014) model:
out <- armitage_eval(
  casrn.vector = "793-24-8",
  this.FBSf = 0.1,
  this.well_number = 384,
  nomconc = 10)

print(out)
```

armitage_input*Armitage et al. (2014) Model Inputs from Honda et al. (2019)*

Description

Armitage et al. (2014) Model Inputs from Honda et al. (2019)

Usage

armitage_input

Format

A data frame with 53940 rows and 10 variables:

MP

MW

casrn

compound_name

gkaw

gkow

gswat

Author(s)

Greg Honda

Source

<https://www.diamondse.info/>

References

Armitage, J. M.; Wania, F.; Arnot, J. A. Environ. Sci. Technol. 2014, 48, 9770-9779. dx.doi.org/10.1021/es501955g

Honda, Gregory S., et al. "Using the Concordance of In Vitro and In Vivo Data to Evaluate Extrapolation Assumptions", PloS ONE 14.5 (2019): e0217564.

augment.table

Add a parameter value to the chem.physical_and_invitro.data table

Description

This internal function is used by `add_chemtable` to add a single new parameter to the table of chemical parameters. It should not be typically used from the command line.

Usage

```
augment.table(  
  this.table,  
  this.CAS,  
  compound.name = NULL,  
  this.property,  
  value,  
  species = NULL,  
  reference,  
  overwrite = FALSE,  
  sig.fig = 4,  
  clint.pvalue.overwrite = TRUE,  
  allow.na = FALSE  
)
```

Arguments

<code>this.table</code>	Object of class <code>data.frame</code> containing one row per chemical.
<code>this.CAS</code>	The Chemical Abstracts Service registry number (CAS-RN) corresponding to the parameter value
<code>compound.name</code>	A name associated with the chemical (defaults to <code>NULL</code>)
<code>this.property</code>	The property being added/modified.
<code>value</code>	The value being assigned to <code>this.property</code> .
<code>species</code>	This is the species for the data in the new table. This may be omitted if a column in <code>data.list</code> gives the species value for each chemical or if the data are not species-specific (e.g., MW).
<code>reference</code>	This is the reference for the data in the new table. This may be omitted if a column in <code>data.list</code> gives the reference value for each chemical.
<code>overwrite</code>	If <code>overwrite=TRUE</code> then data in <code>current.table</code> will be replaced by any data in <code>new.table</code> that is for the same chemical and property. If <code>overwrite=FALSE</code> (DEFAULT) then new data for the same chemical and property are ignored. Funbound.plasma values of 0 (below limit of detection) are overwritten either way.
<code>sig.fig</code>	Sets the number of significant figures stored (defaults to 4)
<code>clint.pvalue.overwrite</code>	If <code>TRUE</code> then the <code>Cl_int</code> p-value is set to <code>NA</code> when the <code>Cl_int</code> value is changed unless a new p-value is provided. (defaults to <code>TRUE</code>)
<code>allow.na</code>	If <code>TRUE</code> (default is <code>FALSE</code>) then <code>NA</code> values are written to the table, otherwise they are ignored.

Value

<code>data.frame</code>	A new <code>data.frame</code> containing the data in <code>current.table</code> augmented by <code>new.table</code>
-------------------------	---

Author(s)

John Wambaugh

available_rblood2plasma

Find the best available ratio of the blood to plasma concentration constant.

Description

This function finds the best available constant ratio of the blood concentration to the plasma concentration, using `get_rblood2plasma` and `calc_rblood2plasma`.

Usage

```
available_rblood2plasma(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  species = "Human",
  adjusted.funbound.plasma = TRUE,
  suppress.messages = FALSE
)
```

Arguments

<code>chem.cas</code>	Either the CAS number or the chemical name must be specified.
<code>chem.name</code>	Either the chemical name or the CAS number must be specified.
<code>dtxsid</code>	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXIDs
<code>species</code>	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
<code>adjusted.funbound.plasma</code>	Whether or not to use Funbound.plasma adjustment if calculating Rblood2plasma.
<code>suppress.messages</code>	Whether or not to display relevant warning messages to user.

Details

Either retrieves a measured blood:plasma concentration ratio from the `chem.physical_and_invitro.data` table or calculates it using the red blood cell partition coefficient predicted with Schmitt's method

If available, in vivo data (from `chem.physical_and_invitro.data`) for the given species is returned, substituting the human in vivo value when missing for other species. In the absence of in vivo data, the value is calculated with `calc_rblood2plasma` for the given species. If `Funbound.plasma` is unavailable for the given species, the human `Funbound.plasma` is substituted. If none of these are available, the mean human `Rblood2plasma` from `chem.physical_and_invitro.data` is returned. details than the description above ~~

Value

The blood to plasma chemical concentration ratio – measured if available, calculated if not.

Author(s)

Robert Pearce

Examples

```
available_rblood2plasma(chem.name="Bisphenol A",adjusted.funbound.plasma=FALSE)
available_rblood2plasma(chem.name="Bisphenol A",species="Rat")
```

aylward2014

Aylward et al. 2014

Description

Aylward et al. (2014) compiled measurements of the ratio of maternal to fetal cord blood chemical concentrations at birth for a range of chemicals with environmental routes of exposure, including bromodiphenyl ethers, fluorinated compounds, organochlorine pesticides, polyaromatic hydrocarbons, tobacco smoke components, and vitamins.

Usage

```
aylward2014
```

Format

data.frame

Source

Kapraun et al. 2021 (submitted)

References

Aylward LL, Hays SM, Kirman CR, Marchitti SA, Kenneke JF, English C, Mattison DR, Becker RA (2014). "Relationships of chemical concentrations in maternal and cord blood: a review of available data." *Journal of Toxicology and Environmental Health, Part B*, **17**(3), 175–203. doi: [10.1080/10937404.2014.884956](https://doi.org/10.1080/10937404.2014.884956).

blood_mass_correct	<i>Find average blood masses by age.</i>
--------------------	--

Description

If blood mass from `blood_weight` is negative or very small, then just default to the mean blood mass by age. (Geigy Scientific Tables, 7th ed.)

Usage

```
blood_mass_correct(blood_mass, age_months, age_years, gender, weight)
```

Arguments

<code>blood_mass</code>	A vector of blood masses in kg to be replaced with averages.
<code>age_months</code>	A vector of ages in months.
<code>age_years</code>	A vector of ages in years.
<code>gender</code>	A vector of genders (either 'Male' or 'Female').
<code>weight</code>	A vector of body weights in kg.

Value

A vector of blood masses in kg.

Author(s)

Caroline Ring

References

Geigy Pharmaceuticals, "Scientific Tables", 7th Edition, John Wiley and Sons (1970)

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

blood_weight	<i>Predict blood mass.</i>
--------------	----------------------------

Description

Predict blood mass based on body surface area and gender, using equations from Bosgra et al. 2012

Usage

```
blood_weight(BSA, gender)
```

Arguments

BSA	Body surface area in m ² . May be a vector.
gender	Either 'Male' or 'Female'. May be a vector.

Value

A vector of blood masses in kg the same length as BSA and gender.

Author(s)

Caroline Ring

References

Bosgra, Sieto, et al. "An improved model to predict physiologically based model parameters and their inter-individual variability from anthropometry." *Critical reviews in toxicology* 42.9 (2012): 751-767.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

bmiage	<i>CDC BMI-for-age charts</i>
--------	-------------------------------

Description

Charts giving the BMI-for-age percentiles for boys and girls ages 2-18

Usage

```
bmiage
```

Format

A data.table object with variables

Sex 'Male' or 'Female'

Agemos Age in months

L, M, S LMS parameters; see https://www.cdc.gov/growthcharts/percentile_data_files.htm

P3, P5, P10, P25, P50, P75, P85, P90, P95, and P97 BMI percentiles

Details

For children ages 2 to 18, weight class depends on the BMI-for-age percentile.

Underweight <5th percentile

Normal weight 5th-85th percentile

Overweight 85th-95th percentile

Obese \geq 95th percentile

Author(s)

Caroline Ring

Source

https://www.cdc.gov/growthcharts/percentile_data_files.htm

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

body_surface_area	<i>Predict body surface area.</i>
-------------------	-----------------------------------

Description

Predict body surface area from weight, height, and age, using Mosteller's formula for age >18 and Haycock's formula for age <18

Usage

```
body_surface_area(BW, H, age_years)
```

Arguments

BW	A vector of body weights in kg.
H	A vector of heights in cm.
age_years	A vector of ages in years.

Value

A vector of body surface areas in cm².

Author(s)

Caroline Ring

References

- Mosteller, R. D. "Simplified calculation of body surface area." N Engl J Med 317 (1987): 1098..
- Haycock, George B., George J. Schwartz, and David H. Wisotsky. "Geometric method for measuring body surface area: a height-weight formula validated in infants, children, and adults." The Journal of pediatrics 93.1 (1978): 62-66.
- Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

bone_mass_age	<i>Predict bone mass</i>
---------------	--------------------------

Description

Predict bone mass from age_years, height, weight, gender, using logistic equations fit to data from Baxter-Jones et al. 2011, or for infants < 1 year, using equation from Koo et al. 2000 (See Price et al. 2003)

Usage

```
bone_mass_age(age_years, age_months, height, weight, gender)
```

Arguments

age_years	Vector of ages in years.
age_months	Vector of ages in months.
height	Vector of heights in cm.
weight	Vector of body weights in kg.
gender	Vector of genders, either 'Male' or 'Female'.

Value

Vector of bone masses.

Author(s)

Caroline Ring

References

- Baxter-Jones, Adam DG, et al. "Bone mineral accrual from 8 to 30 years of age: an estimation of peak bone mass." Journal of Bone and Mineral Research 26.8 (2011): 1729-1739.
- Koo, Winston WK, and Elaine M. Hockman. "Physiologic predictors of lumbar spine bone mass in neonates." Pediatric research 48.4 (2000): 485-489.
- Price, Paul S., et al. "Modeling interindividual variation in physiological factors used in PBPK models of humans." Critical reviews in toxicology 33.5 (2003): 469-503.
- Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

brain_mass	<i>Predict brain mass.</i>
------------	----------------------------

Description

Predict brain mass from gender and age.

Usage

```
brain_mass(gender, age_years)
```

Arguments

gender	Vector of genders, either 'Male' or 'Female'
age_years	Vector of ages in years.

Value

A vector of brain masses in kg.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

calc_analytic_css	<i>Calculate the analytic steady state plasma concentration.</i>
-------------------	--

Description

This function calculates the analytic steady state plasma or venous blood concentrations as a result of infusion dosing for the three compartment and multiple compartment PBTK models.

Usage

```
calc_analytic_css(  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL,  
  parameters = NULL,  
  species = "human",  
  daily.dose = 1,  
  route = "oral",  
  exp.conc = 1,  
  period = 24,  
  exp.duration = 24,
```



```

    output.units = "uM",
    model = "pbtk",
    concentration = "plasma",
    suppress.messages = FALSE,
    tissue = NULL,
    restrictive.clearance = TRUE,
    bioactive.free.invivo = FALSE,
    IVIVE = NULL,
    parameterize.args = list(default.to.human = FALSE, adjusted.Funbound.plasma = TRUE,
        regression = TRUE, minimum.Funbound.plasma = 1e-04),
    ...
)

```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_pbtk (for model = 'pbtk'), parameterize_3comp (for model = '3compartment'), parameterize_1comp (for model = '1compartment') or parameterize_steadystate (for model = '3compartmentss'), overrides chem.name and chem.cas.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
daily.dose	Total daily dose, mg/kg BW.
route	Route of exposure (either "oral", "iv", or "inhalation" default "oral").
exp.conc	Specified inhalation exposure concentration for use in assembling 'forcings' data series argument for integrator. Defaults to uM/L
period	For use in assembling forcing function data series 'forcings' argument, specified in hours
exp.duration	For use in assembling forcing function data series 'forcings' argument, specified in hours
output.units	Units for returned concentrations, defaults to uM (specify units = "uM") but can also be mg/L.
model	Model used in calculation, 'gas_pbtk' for the gas pbtk model, 'pbtk' for the multiple compartment model, '3compartment' for the three compartment model, '3compartmentss' for the three compartment steady state model, and '1compartment' for one compartment model.
concentration	Desired concentration type, 'blood', 'tissue', or default 'plasma'.
suppress.messages	Whether or not the output message is suppressed.
tissue	Desired tissue concentration (defaults to whole body concentration.)
restrictive.clearance	If TRUE (default), then only the fraction of chemical not bound to protein is available for metabolism in the liver. If FALSE, then all chemical in the liver is metabolized (faster metabolism due to rapid off-binding).
bioactive.free.invivo	If FALSE (default), then the total concentration is treated as bioactive in vivo. If TRUE, the the unbound (free) plasma concentration is treated as bioactive in vivo. Only works with tissue = NULL in current implementation.

IVIVE Honda et al. (2019) identified four plausible sets of assumptions for *in vitro-in vivo* extrapolation (IVIVE) assumptions. Argument may be set to "Honda1" through "Honda4". If used, this function overwrites the tissue, restrictive.clearance, and bioactive.free.invivo arguments. See Details below for more information.

parameterize.args List of arguments passed to model's associated parameterization function, including default.to.human, adjusted.Funbound.plasma, regression, and minimum.Funbound.plasma. The default.to.human argument substitutes missing animal values with human values if true, adjusted.Funbound.plasma returns adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value, regression indicates whether or not to use the regressions in calculating partition coefficients, and minimum.Funbound.plasma is the value to which Monte Carlo draws less than this value are set (default is 0.0001 – half the lowest measured C_{up} in our dataset).

... Additional parameters passed to parameterize function if parameters is NULL.

Details

Concentrations are calculated for the specified model with constant oral infusion dosing. All tissues other than gut, liver, and lung are the product of the steady state plasma concentration and the tissue to plasma partition coefficient.

	<i>in vivo</i> Conc.	Metabolic Clearance	Bioactive Chemical Conc.	TK Statistic Used*
Honda1	Veinous (Plasma)	Restrictive	Free	Mean Conc.
Honda2	Veinous	Restrictive	Free	Max Conc.
Honda3	Veinous	Non-restrictive	Total	Mean Conc.
Honda4	Veinous	Non-restrictive	Total	Max Conc.
Honda5	Target Tissue	Non-restrictive	Total	Mean Conc.
Honda6	Target Tissue	Non-restrictive	Total	Max Conc.

*Assumption is currently ignored because analytical steady-state solutions are currently used by this function.

Value

Steady state plasma concentration in specified units

Author(s)

Robert Pearce, John Wambaugh, Greg Honda, Miyuki Breen

References

Honda, Gregory S., et al. "Using the Concordance of In Vitro and In Vivo Data to Evaluate Extrapolation Assumptions." 2019. PLoS ONE 14(5): e0217564.

Examples

```
calc_analytic_css(chem.name='Bisphenol-A',output.units='mg/L',
                  model='3compartment',concentration='blood')

calc_analytic_css(chem.name='Bisphenol-A',tissue='liver',species='rabbit',
```

```

parameterize.args = list(
  default.to.human=TRUE,
  adjusted.Funbound.plasma=TRUE,
  regression=TRUE,
  minimum.Funbound.plasma=1e-4),daily.dose=2)

calc_analytic_css(chem.name="bisphenol a",model="1compartment")

calc_analytic_css(chem.cas="80-05-7",model="3compartmentss")

params <- parameterize_pbt(chem.cas="80-05-7")

calc_analytic_css(parameters=params,model="pbt")

```

calc_analytic_css_1comp

Calculate the analytic steady state concentration for the one compartment model.

Description

This function calculates the analytic steady state plasma or venous blood concentrations as a result of infusion dosing.

Usage

```

calc_analytic_css_1comp(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  parameters = NULL,
  hourly.dose = 1/24,
  concentration = "plasma",
  suppress.messages = FALSE,
  recalc.blood2plasma = FALSE,
  tissue = NULL,
  restrictive.clearance = TRUE,
  bioactive.free.invivo = FALSE,
  ...
)

```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_pbt (for model = 'pbt'), parameterize_3comp (for model = '3compartment'), parameterize_1comp (for model = '1compartment') or parameterize_steadystate (for model = '3compartmentss'), overrides chem.name and chem.cas.

hourly.dose	Hourly dose rate mg/kg BW/h.
concentration	Desired concentration type, 'blood' or default 'plasma'.
suppress.messages	Whether or not the output message is suppressed.
recalc.blood2plasma	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters. Use this if you have altered hematocrit, Funbound.plasma, or Krbc2pu.
tissue	Desired tissue concentration (defaults to whole body concentration.)
restrictive.clearance	If TRUE (default), then only the fraction of chemical not bound to protein is available for metabolism in the liver. If FALSE, then all chemical in the liver is metabolized (faster metabolism due to rapid off-binding).
bioactive.free.invivo	If FALSE (default), then the total concentration is treated as bioactive in vivo. If TRUE, the the unbound (free) plasma concentration is treated as bioactive in vivo. Only works with tissue = NULL in current implementation.
...	Additional parameters passed to parameterize function if parameters is NULL.

Value

Steady state plasma concentration in mg/L units

Author(s)

Robert Pearce and John Wambaugh

calc_analytic_css_3comp

Calculate the analytic steady state concentration for model 3comp

Description

This function calculates the analytic steady state plasma or venous blood concentrations as a result of infusion dosing.

Usage

```
calc_analytic_css_3comp(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  parameters = NULL,
  hourly.dose = 1/24,
  concentration = "plasma",
  suppress.messages = FALSE,
  recalc.blood2plasma = FALSE,
  tissue = NULL,
  restrictive.clearance = TRUE,
  bioactive.free.invivo = FALSE,
  ...
)
```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXIDs
parameters	Chemical parameters from parameterize_pbt (for model = 'pbt'), parameterize_3comp (for model = '3compartment'), parameterize_1comp (for model = '1compartment') or parameterize_steadystate (for model = '3compartmentss'), overrides chem.name and chem.cas.
hourly.dose	Hourly dose rate mg/kg BW/h.
concentration	Desired concentration type, 'blood' or default 'plasma'.
suppress.messages	Whether or not the output message is suppressed.
recalc.blood2plasma	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters. Use this if you have 'altered hematocrit, Funbound.plasma, or Krbc2pu.
tissue	Desired tissue concentration (defaults to whole body concentration.)
restrictive.clearance	If TRUE (default), then only the fraction of chemical not bound to protein is available for metabolism in the liver. If FALSE, then all chemical in the liver is metabolized (faster metabolism due to rapid off-binding).
bioactive.free.invivo	If FALSE (default), then the total concentration is treated as bioactive in vivo. If TRUE, the the unbound (free) plasma concentration is treated as bioactive in vivo. Only works with tissue = NULL in current implementation.
...	Additional parameters passed to parameterize function if parameters is NULL.

Value

Steady state plasma concentration in mg/L units

Author(s)

Robert Pearce and John Wambaugh

calc_analytic_css_3compss

Calculate the analytic steady state concentration for the three compartment steady-state model

Description

This function calculates the analytic steady state plasma or venous blood concentrations as a result of infusion dosing.

Usage

```
calc_analytic_css_3compss(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  parameters = NULL,
  hourly.dose = 1/24,
  concentration = "plasma",
  suppress.messages = FALSE,
  recalc.blood2plasma = FALSE,
  tissue = NULL,
  restrictive.clearance = TRUE,
  bioactive.free.invivo = FALSE,
  ...
)
```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_pbt (for model = 'pbt'), parameterize_3comp (for model = '3compartment'), parameterize_1comp (for model = '1compartment') or parameterize_steadystate (for model = '3compartmentss'), overrides chem.name and chem.cas.
hourly.dose	Hourly dose rate mg/kg BW/h.
concentration	Desired concentration type, 'blood' or default 'plasma'.
suppress.messages	Whether or not the output message is suppressed.
recalc.blood2plasma	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters. Use this if you have 'altered hematocrit, Funbound.plasma, or Krbc2pu.
tissue	Desired tissue concentration (defaults to whole body concentration.)
restrictive.clearance	If TRUE (default), then only the fraction of chemical not bound to protein is available for metabolism in the liver. If FALSE, then all chemical in the liver is metabolized (faster metabolism due to rapid off-binding).
bioactive.free.invivo	If FALSE (default), then the total concentration is treated as bioactive in vivo. If TRUE, the the unbound (free) plasma concentration is treated as bioactive in vivo. Only works with tissue = NULL in current implementation.
...	Additional parameters passed to parameterize function if parameters is NULL.

Value

Steady state plasma concentration in mg/L units

Author(s)

Robert Pearce and John Wambaugh

calc_analytic_css_pbt*Calculate the analytic steady state plasma concentration for model pbt.*

Description

This function calculates the analytic steady state plasma or venous blood concentrations as a result of infusion dosing.

Usage

```
calc_analytic_css_pbt(  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL,  
  parameters = NULL,  
  hourly.dose = 1/24,  
  concentration = "plasma",  
  suppress.messages = FALSE,  
  recalc.blood2plasma = FALSE,  
  tissue = NULL,  
  restrictive.clearance = TRUE,  
  bioactive.free.in vivo = FALSE,  
  ...  
)
```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_pbt (for model = 'pbt'), parameterize_3comp (for model = '3compartment'), parameterize_1comp (for model = '1compartment') or parameterize_steadystate (for model = '3compartmentss'), overrides chem.name and chem.cas.
hourly.dose	Hourly dose rate mg/kg BW/h.
concentration	Desired concentration type, 'blood', 'tissue', or default 'plasma'.
suppress.messages	Whether or not the output message is suppressed.
recalc.blood2plasma	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters. Use this if you have 'altered hematocrit, Funbound.plasma, or Krbc2pu.

tissue Desired tissue concentration (defaults to whole body concentration.)

restrictive.clearance If TRUE (default), then only the fraction of chemical not bound to protein is available for metabolism in the liver. If FALSE, then all chemical in the liver is metabolized (faster metabolism due to rapid off-binding).

bioactive.free.in vivo If FALSE (default), then the total concentration is treated as bioactive in vivo. If TRUE, the the unbound (free) plasma concentration is treated as bioactive in vivo. Only works with tissue = NULL in current implementation.

... Additional parameters passed to parameterize function if parameters is NULL.

Value

Steady state plasma concentration in mg/L units

Author(s)

Robert Pearce and John Wambaugh

calc_css

Find the steady state concentration and the day it is reached.

Description

This function finds the day a chemical comes within the specified range of the analytical steady state venous blood or plasma concentration (from calc_analytic_css) for the multiple compartment, three compartment, and one compartment models, the fraction of the true steady state value reached on that day, the maximum concentration, and the average concentration at the end of the simulation.

Usage

```
calc_css(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  parameters = NULL,
  species = "Human",
  f = 0.01,
  daily.dose = 1,
  doses.per.day = 3,
  days = 21,
  output.units = "uM",
  suppress.messages = FALSE,
  tissue = NULL,
  model = "pbtk",
  default.to.human = FALSE,
  f.change = 1e-05,
  adjusted.funbound.plasma = TRUE,
  regression = TRUE,
  well.stirred.correction = TRUE,
  restrictive.clearance = TRUE,
```



```

    dosing = NULL,
    ...
)

```

Arguments

chem.name	Either the chemical name, CAS number, or parameters must be specified.
chem.cas	Either the chemical name, CAS number, or parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXIDs
parameters	Chemical parameters from parameterize_pbt function, overrides chem.name and chem.cas.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
f	Fractional distance from the final steady state concentration that the average concentration must come within to be considered at steady state.
daily.dose	Total daily dose, mg/kg BW.
doses.per.day	Number of doses per day.
days	Initial number of days to run simulation that is multiplied on each iteration.
output.units	Units for returned concentrations, defaults to uM (specify units = "uM") but can also be mg/L.
suppress.messages	Whether or not to suppress messages.
tissue	Desired tissue concentration (default value is NULL, will depend on model – see steady.state.compartment in model.info file for further details.)
model	Model used in calculation, 'pbt' for the multiple compartment model, '3compartment' for the three compartment model, and '1compartment' for the one compartment model.
default.to.human	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
f.change	Fractional change of daily steady state concentration reached to stop calculating.
adjusted.funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
well.stirred.correction	Uses correction in calculation of hepatic clearance for well-stirred model if TRUE for model 1compartment elimination rate. This assumes clearance relative to amount unbound in whole blood instead of plasma, but converted to use with plasma concentration.
restrictive.clearance	Protein binding not taken into account (set to 1) in liver clearance if FALSE.
dosing	The dosing object for more complicated scenarios. Defaults to repeated daily.dose spread out over doses.per.day
...	Additional arguments passed to model solver (default of solve_pbt).

Value

frac	Ratio of the mean concentration on the day steady state is reached (baed on doses.per.day) to the analytical C _{ss} (based on infusion dosing).
max	The maximum concentration of the simulation.
avg	The average concentration on the final day of the simulation.
the.day	The day the average concentration comes within 100 * p percent of the true steady state concentration.

Author(s)

Robert Pearce, John Wambaugh

Examples

```
calc_css(chem.name='Bisphenol-A',doses.per.day=5,f=.001,output.units='mg/L')

parms <- parameterize_3comp(chem.name='Bisphenol-A')
parms$Funbound.plasma <- .07
calc_css(parameters=parms,model='3compartment')

out <- solve_pbtok(chem.name = "Bisphenol A",
  days = 50,
  daily.dose=1,
  doses.per.day = 3)
plot.data <- as.data.frame(out)

css <- calc_analytic_css(chem.name = "Bisphenol A")
library("ggplot2")
c.vs.t <- ggplot(plot.data,aes(time, Cplasma)) + geom_line() +
  geom_hline(yintercept = css) + ylab("Plasma Concentration (uM)") +
  xlab("Day") + theme(axis.text = element_text(size = 16), axis.title =
  element_text(size = 16), plot.title = element_text(size = 17)) +
  ggtitle("Bisphenol A")

print(c.vs.t)
```

calc_elimination_rate *Calculate the elimination rate for a one compartment model.*

Description

This function calculates an elimination rate from the three compartment steady state model where elimination is entirely due to metabolism by the liver and glomerular filtration in the kidneys.

Usage

```
calc_elimination_rate(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
```

```

parameters = NULL,
species = "Human",
suppress.messages = FALSE,
default.to.human = FALSE,
restrictive.clearance = TRUE,
adjusted.funbound.plasma = TRUE,
regression = TRUE,
well.stirred.correction = TRUE,
clint.pvalue.threshold = 0.05,
minimum.funbound.plasma = 1e-04
)

```

Arguments

chem.cas	Either the cas number or the chemical name must be specified.
chem.name	Either the chemical name or the cas number must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_steadystate or 1compartment function, overrides chem.name and chem.cas.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
suppress.messages	Whether or not the output message is suppressed.
default.to.human	Substitutes missing animal values with human values if true.
restrictive.clearance	In calculating elimination rate, protein binding is not taken into account (set to 1) in liver clearance if FALSE.
adjusted.funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
well.stirred.correction	Uses correction in calculation of hepatic clearance for -stirred model if TRUE. This assumes clearance relative to amount unbound in whole blood instead of plasma, but converted to use with plasma concentration.
clint.pvalue.threshold	Hepatic clearance for chemicals where the in vitro clearance assay result has a p-values greater than the threshold are set to zero.
minimum.funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

Details

Elimination rate calculated by dividing the total clearance (using the default -stirred hepatic model) by the volume of distribution. When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

Elimination rate

Units of 1/h.

Author(s)

John Wambaugh

Examples

```
calc_elimination_rate(chem.name="Bisphenol A")
calc_elimination_rate(chem.name="Bisphenol A", species="Rat")
calc_elimination_rate(chem.cas="80-05-7")
```

calc_fetal_phys

*Calculate maternal-fetal physiological parameters***Description**

This function uses the equations from Kapraun (2019) to calculate chemical- independent physiological parameters as a function of gestational age in weeks.

Usage

```
calc_fetal_phys(week = 12, ...)
```

Arguments

week Gestational week

... Additional arguments to parameterize_fetal_pbt

Details

$$BW = pre_{pregnant} BW + BW_{cubic} \theta_1 * tw + BW_{cubic} \theta_2 * tw^2 + BW_{cubic} \theta_3 * tw^3$$

$$W_{adipose} = W_{adipose_{linear}} \theta_0 + W_{adipose_{linear}} \theta_1 * tw;$$

$$W_{fkidney} = 0.001 * W_{fkidney_gompertz} \theta_0 * \exp(W_{fkidney_gompertz} \theta_1 / W_{fkidney_gompertz} \theta_2 * (1 - \exp(-W_{fkidney_gompertz} \theta_3 * tw)))$$

$$W_{fthyroid} = 0.001 * W_{fthyroid_gompertz} \theta_0 * \exp(W_{fthyroid_gompertz} \theta_1 / W_{fthyroid_gompertz} \theta_2 * (1 - \exp(-W_{fthyroid_gompertz} \theta_3 * tw)))$$

$$W_{fliver} = 0.001 * W_{fliver_gompertz} \theta_0 * \exp(W_{fliver_gompertz} \theta_1 / W_{fliver_gompertz} \theta_2 * (1 - \exp(-W_{fliver_gompertz} \theta_3 * tw)))$$

$$W_{fbrain} = 0.001 * W_{fbrain_gompertz} \theta_0 * \exp(W_{fbrain_gompertz} \theta_1 / W_{fbrain_gompertz} \theta_2 * (1 - \exp(-W_{fbrain_gompertz} \theta_3 * tw)))$$

$$Wfgut = 0.001 * Wfgut_gompertz_t\eta_0 * \exp(Wfgut_gompertz_t\eta_1 / Wfgut_gompertz_t\eta_2 * (1 - \exp(-Wfgut_gompertz_t\eta_3 * tw)));$$

$$Wflung = 0.001 * Wflung_gompertz_t\eta_0 * \exp(Wflung_gompertz_t\eta_1 / Wflung_gompertz_t\eta_2 * (1 - \exp(-Wflung_gompertz_t\eta_3 * tw)));$$

$$hematocrit = (hematocrit_qadratic_t\eta_0 + hematocrit_qadratic_t\eta_1 * tw + hematocrit_qadratic_t\eta_2 * pow(tw, 2) + hematocrit_qadratic_t\eta_3 * pow(tw, 3));$$

$$Rblood2plasma = 1 - hematocrit + hematocrit * Krbc2pu * Fraction_u\bound_p\lasma;$$

$$fhematocrit = (fhematocrit_cubic_t\eta_1 * tw + fhematocrit_cubic_t\eta_2 * pow(tw, 2) + fhematocrit_cubic_t\eta_3 * pow(tw, 3));$$

$$Rfblood2plasma = 1 - fhematocrit + fhematocrit * Kfrbc2pu * Fraction_u\bound_p\lasma_fetus;$$

$$fBW = 0.001 * fBW_gompertz_t\eta_0 * \exp(fBW_gompertz_t\eta_1 / fBW_gompertz_t\eta_2 * (1 - \exp(-fBW_gompertz_t\eta_3 * tw)));$$

$$Vplacenta = 0.001 * (Vplacenta_cubic_t\eta_1 * tw + Vplacenta_cubic_t\eta_2 * pow(tw, 2) + Vplacenta_cubic_t\eta_3 * pow(tw, 3));$$

$$Vamn_f = 0.001 * Vamn_flogistic_t\eta_0 / (1 + \exp(-Vamn_flogistic_t\eta_1 * (tw - Vamn_flogistic_t\eta_2)));$$

$$Vplasma = Vplasma_modlogistic_t\eta_0 / (1 + \exp(-Vplasma_modlogistic_t\eta_1 * (tw - Vplasma_modlogistic_t\eta_2)));$$

$$Vrbcs = hematocrit / (1 - hematocrit) * Vplasma;$$

$$Vven = venous_blood_fraction * (Vrbcs + Vplasma);$$

$$Vart = arterial_blood_fraction * (Vrbcs + Vplasma);$$

$$Vadipose = 1 / adipose_density * Wadipose;$$

$$Vffmx = 1 / ffx_density * (BW - Wadipose - (fBW + placenta_density * Vplacenta + amn_density * Vamn_f));$$

$$Vallx = Vart + Vven + Vthyroid + Vkidney + Vgut + Vliver + Vlung;$$

$$Vrest = Vffmx - Vallx;$$

$$Vfart = 0.001 * arterial_blood_fraction * fblood_weight_ratio * fBW;$$

$$Vfven = 0.001 * venous_blood_fraction * fblood_weight_ratio * fBW;$$

$$Vfkidney = 1/kidney_density * Wfkidney;$$

$$Vfthyroid = 1/thyroid_density * Wfthyroid;$$

$$Vfliver = 1/liver_density * Wfliver;$$

$$Vfbrain = 1/brain_density * Vfbrain;$$

$$Vfgut = 1/gut_density * Wfgut;$$

$$Vflung = 1/lung_density * Wflung;$$

$$Vfrest = fBW - (Vfart + Vfven + Vfbrain + Vfkidney + Vfthyroid + Vfliver + Vfgut + Vflung);$$

$$Qcardiac = 24 * (Qcardiac_ubic_t_heta0 + Qcardiac_ubic_t_heta1 * tw + Qcardiac_ubic_t_heta2 * pow(tw, 2) + Qcardiac_ubic_t_heta3 * pow(tw, 3));$$

$$Qgut = 0.01 * (Qgut_percent_i_nitial + (Qgut_percent_t_erminal - Qgut_percent_i_nitial) / term * tw) * Qcardiac;$$

$$Qkidney = 24 * (Qkidney_ubic_t_heta0 + Qkidney_ubic_t_heta1 * tw + Qkidney_ubic_t_heta2 * pow(tw, 2) + Qkidney_ubic_t_heta3 * pow(tw, 3));$$

$$Qliver = 0.01 * (Qliver_percent_i_nitial + (Qliver_percent_t_erminal - Qliver_percent_i_nitial) / term * tw) * Qcardiac;$$

$$Qthyroid = 0.01 * (Qthyroid_percent_i_nitial + (Qthyroid_percent_t_erminal - Qthyroid_percent_i_nitial) / term * tw) * Qcardiac;$$

$$Qplacenta = 24 * Qplacenta_linear_t_heta1 * 1000 * Vplacenta;$$

$$Qadipose = 0.01 * (Qadipose_percent_i_nitial + (Qadipose_percent_t_erminal - Qadipose_percent_i_nitial) / term * tw) * Qcardiac;$$

$$Qrest = Qcardiac - (Qgut + Qkidney + Qliver + Qthyroid + Qplacenta + Qadipose);$$

$$Qgfr = 60*24*0.001*(Qgfr_{quadratic_t}heta0 + Qgfr_{quadratic_t}heta1*tw + Qgfr_{quadratic_t}heta2*pow(tw, 2));$$

$$Qfrvtl = 60*24*0.001*Qfrvtl_{logistic_t}heta0/(1+exp(-Qfrvtl_{logistic_t}heta1*(tw-Qfrvtl_{logistic_t}heta2)));$$

$$Qflvtl = 60*24*0.001*Qflvtl_{logistic_t}heta0/(1+exp(-Qflvtl_{logistic_t}heta1*(tw-Qflvtl_{logistic_t}heta2)));$$

$$Qfda = 60*24*0.001*Qfda_{logistic_t}heta0/(1+exp(-Qfda_{logistic_t}heta1*(tw-Qfda_{logistic_t}heta2)));$$

$$Qfartb = Qflvtl + Qfda;$$

$$Qfcardiac = Qfartb;$$

$$Qflung = Qfrvtl - Qfda;$$

$$Qfplacenta = 60*24*0.001*Qfplacenta_{logistic_t}heta0/(1+exp(-Qfplacenta_{logistic_t}heta1*(tw-Qfplacenta_{logistic_t}heta2)));$$

$$Qfdv = 60*24*0.001*Qfdv_{gompertz_t}heta0*exp(Qfdv_{gompertz_t}heta1/Qfdv_{gompertz_t}heta2*(1-exp(-Qfdv_{gompertz_t}heta3*tw)));$$

$$Qfgut = Qfgut_{percent}/Qfnonplacental_{percent} * (1 - Qfplacenta/Qfartb) * Qfartb;$$

$$Qfkidney = Qfkidney_{percent}/Qfnonplacental_{percent}*(1-Qfplacenta/Qfartb)*Qfartb;$$

$$Qfbrain = Qfbrain_{percent}/Qfnonplacental_{percent} * (1 - Qfplacenta/Qfartb) * Qfartb;$$

$$Qfliver = Qfliver_{percent}/(100-(Qfbrain_{percent}+Qfkidney_{percent}+Qfgut_{percent}))* (1-(Qfbrain_{percent}+Qfkidney_{percent}+Qfgut_{percent}));$$

$$Qfthyroid = Qfthyroid_{percent}/(100-(Qfbrain_{percent}+Qfkidney_{percent}+Qfgut_{percent}))* (1-(Qfbrain_{percent}+Qfkidney_{percent}+Qfgut_{percent}));$$

$$Qfrest = Qfcardiac - (Qfplacenta + Qfgut + Qfliver + Qfthyroid + Qfkidney + Qfbrain);$$

$$Qfbypass = Qfcardiac - Qflung;$$

Value

list containing:

BW	Maternal body weight, kg
Wadipose	Maternal adipose fraction of total weight
Wfkidney	Fetal kidney fraction of total weight
Wfthyroid	Fetal thyroid fraction of total weight
Wfliver	Fetal liver fraction of total weight
Wfbrain	Fetal brain fraction of total weight
Wfgut	Fetal gut fraction of total weight
Wflung	Fetal lung fraction of total weight
hematocrit	Maternal hematocrit fraction of blood
Rblood2plasma	Maternal Rblood2plasma
fhematocrit	Fetal hematocrit fraction of blood
Rfblood2plasma	Fetal Rfblood2plasma
fBW	Fetal body weight, kg
Vplacenta	Volume of Vplacenta, L
Vamnf	Volume of amniotic fluid, L
Vplasma	Maternal volume of plasma, L
Vrbcs	Maternal volume of red blood cells, L
Vven	Maternal volume of venous blood, L
Vart	Maternal volume of arterial blood, L
Vadipose	Maternal volume of adipose, L
Vffmx	Fetal volume of Vffmx, L
Vallx	Vallx, L
Vrest	Maternal volume of rest of body, L
Vfart	Fetal volume of arterial blood, L
Vfven	Fetal volume of venous blood, L
Vfkidney	Fetal volume of kidney, L
Vfthyroid	Fetal volume of thyroid, L
Vfliver	Fetal volume of liver, L
Vfbrain	Fetal volume of brain, L
Vfgut	Fetal volume of gut, L
Vflung	Fetal volume of lung, L
Vfrest	Fetal volume of rest of body, L
Qcardiac	Maternal cardiac output blood flow, L/day
Qgut	Maternal blood flow to gut, L/day
Qkidney	Maternal blood flow to kidney, L/day
Qliver	Maternal blood flow to liver, L/day
Qthyroid	Maternal blood flow to thyroid, L/day
Qplacenta	Maternal blood flow to placenta, L/day

Qadipose	Maternal blood flow to adipose, L/day
Qrest	Maternal blood flow to rest, L/day
Qgfr	Maternal glomerular filtration rate in kidney, L/day
Qfrvtl	Fetal blood flow to right ventricle, L/day
Qflvtl	Fetal blood flow to left ventricle, L/day
Qfda	Fetal blood flow to Qfda, L/day
Qfartb	Fetal blood flow to Qfartb, L/day
Qfcardiac	Fetal cardiac output blood flow, L/day
Qflung	Fetal blood flow to lung, L/day
Qfplacenta	Fetal blood flow to placenta, L/day
Qfdv	Fetal blood flow to Qfdv, L/day
Qfgut	Fetal blood flow to gut, L/day
Qfkidney	Fetal blood flow to kidney, L/day
Qfbrain	Fetal blood flow to brain, L/day
Qfliver	Fetal blood flow to liver, L/day
Qfthyroid	Fetal blood flow to thyroid, L/day
Qfrest	Fetal blood flow to rest, L/day
Qfbypass	Fetal blood flow to Qfbypass, L/day

Author(s)

John Wambaugh

References

Kapraun, Dustin F., et al. "Empirical models for anatomical and physiological changes in a human mother and fetus during pregnancy and gestation." PloS one 14.5 (2019): e0215906.

calc_half_life	<i>Calculates the half-life for a one compartment model.</i>
----------------	--

Description

This function calculates the half life from the three compartment steady state model where elimination is entirely due to metabolism by the liver and glomerular filtration in the kidneys.

Usage

```
calc_half_life(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  parameters = NULL,
  species = "Human",
  suppress.messages = FALSE,
  default.to.human = FALSE,
```

```

restrictive.clearance = TRUE,
adjusted.Funbound.plasma = TRUE,
regression = TRUE,
well.stirred.correction = TRUE,
clint.pvalue.threshold = 0.05,
minimum.Funbound.plasma = 1e-04
)

```

Arguments

chem.cas	Either the cas number or the chemical name must be specified.
chem.name	Either the chemical name or the cas number must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_steadystate or 1compartment function, overrides chem.name and chem.cas.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
suppress.messages	Whether or not the output message is suppressed.
default.to.human	Substitutes missing animal values with human values if true.
restrictive.clearance	In calculating elimination rate, protein binding is not taken into account (set to 1) in liver clearance if FALSE.
adjusted.Funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
well.stirred.correction	Uses correction in calculation of hepatic clearance for -stirred model if TRUE. This assumes clearance relative to amount unbound in whole blood instead of plasma, but converted to use with plasma concentration.
clint.pvalue.threshold	Hepatic clearance for chemicals where the in vitro clearance assay result has a p-values greater than the threshold are set to zero.
minimum.Funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

Details

Half life is calculated by dividing the natural-log of 2 by the elimination rate from the one compartment model.

Value

Half life Units of h.

Author(s)

Sarah E. Davidson

See Also

[calc_elimination_rate()] for the elimination rate calculation

Examples

```
calc_half_life(chem.name="Bisphenol A")
calc_half_life(chem.name="Bisphenol A", species="Rat")
calc_half_life(chem.cas="80-05-7")
```

calc_hepatic_clearance

Calculate the hepatic clearance (deprecated).

Description

This function is included for backward compatibility. It calls `calc_hep_clearance` which calculates the hepatic clearance in plasma for a well-stirred model or other type if specified. Based on Ito and Houston (2004)

Usage

```
calc_hepatic_clearance(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  parameters = NULL,
  species = "Human",
  default.to.human = FALSE,
  hepatic.model = "well-stirred",
  suppress.messages = FALSE,
  well.stirred.correction = TRUE,
  restrictive.clearance = TRUE,
  adjusted.funbound.plasma = TRUE,
  ...
)
```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_steadystate function, overrides chem.name and chem.cas.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
default.to.human	Substitutes missing animal values with human values if true.

`hepatic.model` Model used in calculating hepatic clearance, unscaled, parallel tube, dispersion, or default well-stirred.
`suppress.messages` Whether or not to suppress the output message.
`well.stirred.correction` Uses correction in calculation of hepatic clearance for well-stirred model if TRUE for hepatic.model well-stirred. This assumes clearance relative to amount unbound in whole blood instead of plasma, but converted to use with plasma concentration.
`restrictive.clearance` Protein binding not taken into account (set to 1) in liver clearance if FALSE.
`adjusted.funbound.plasma` Uses adjusted Funbound.plasma when set to TRUE.
`...` Additional parameters passed to `parameterize_steadystate` if parameters is NULL.

Value

Hepatic Clearance
 Units of L/h/kg BW.

Author(s)

John Wambaugh and Robert Pearce

References

Ito, K., & Houston, J. B. (2004). "Comparison of the use of liver models for predicting drug clearance using in vitro kinetic data from hepatic microsomes and isolated hepatocytes." *Pharmaceutical Research*, 21(5), 785-792.

Examples

```

calc_hep_clearance(chem.name="Ibuprofen",hepatic.model='unscaled')
calc_hep_clearance(chem.name="Ibuprofen",well.stirred.correction=FALSE)
  
```

calc_hep_bioavailability

Calculate first pass metabolism

Description

For models that don't described first pass blood flow from the gut, need to calculate a hepatic bioavailability, that is, the fraction of chemical systemically available after metabolism during the first pass through the liver (Rowland, 1973 Equation 29, where k_{21} is blood flow through the liver and k_{23} is clearance from the liver in Figure 1).

Usage

```
calc_hep_bioavailability(  
  chem.cas = NULL,  
  chem.name = NULL,  
  dtxsid = NULL,  
  parameters = NULL,  
  restrictive.clearance = TRUE,  
  flow.34 = TRUE  
)
```

Arguments

chem.cas	Chemical Abstract Services Registry Number (CAS-RN) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
chem.name	Chemical name (spaces and capitalization ignored) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Parameters from the appropriate parameterization function for the model indicated by argument model
restrictive.clearance	Protein binding not taken into account (set to 1) in liver clearance if FALSE.
flow.34	A logical constraint

Value

A data.table whose columns are the parameters of the HHTK model specified in model1.

Author(s)

John Wambaugh

References

Rowland, Malcolm, Leslie Z. Benet, and Garry G. Graham. "Clearance concepts in pharmacokinetics." Journal of pharmacokinetics and biopharmaceutics 1.2 (1973): 123-136.

calc_hep_clearance	<i>Calculate the hepatic clearance.</i>
--------------------	---

Description

This function calculates the hepatic clearance in plasma for using the Houston (2004) are also available. In vitro measured hepatic clearance is corrected for the free fraction in the assay using the model of Kilford et al. (2008).

Usage

```
calc_hep_clearance(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  parameters = NULL,
  species = "Human",
  default.to.human = FALSE,
  hepatic.model = "well-stirred",
  suppress.messages = FALSE,
  well.stirred.correction = TRUE,
  restrictive.clearance = TRUE,
  adjusted.Funbound.plasma = TRUE,
  ...
)
```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_steadystate function, overrides chem.name and chem.cas.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
default.to.human	Substitutes missing animal values with human values if true.
hepatic.model	Model used in calculating hepatic clearance, unscaled, parallel tube, dispersion, or default well-stirred.
suppress.messages	Whether or not to suppress the output message.
well.stirred.correction	Uses correction in calculation of hepatic clearance for well-stirred model if TRUE for hepatic.model well-stirred. This assumes clearance relative to amount unbound in whole blood instead of plasma, but converted to use with plasma concentration.
restrictive.clearance	Protein binding not taken into account (set to 1) in liver clearance if FALSE.
adjusted.Funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE.
...	Additional parameters passed to parameterize_steadystate if parameters is NULL.

Value

Hepatic Clearance
Units of L/h/kg BW.

Author(s)

John Wambaugh and Robert Pearce

References

Ito, K., & Houston, J. B. (2004). "Comparison of the use of liver models for predicting drug clearance using in vitro kinetic data from hepatic microsomes and isolated hepatocytes." *Pharmaceutical Research*, 21(5), 785-792.

Kilford, P. J., Gertz, M., Houston, J. B. and Galetin, A. (2008). Hepatocellular binding of drugs: correction for unbound fraction in hepatocyte incubations using microsomal binding or drug lipophilicity data. *Drug Metabolism and Disposition* 36(7), 1194-7, 10.1124/dmd.108.020834.

Examples

```
calc_hep_clearance(chem.name="Ibuprofen",hepatic.model='unscaled')
calc_hep_clearance(chem.name="Ibuprofen",well.stirred.correction=FALSE)
```

calc_hep_fu

Calculate the free chemical in the hepatic clearance assay

Description

Method from Kilford et al. (2008) for fraction of unbound chemical in the hepatocyte intrinsic clearance assay

Usage

```
calc_hep_fu(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  parameters = NULL,
  Vr = 0.005,
  pH = 7.4
)
```

Arguments

chem.cas	Chemical Abstract Services Registry Number (CAS-RN) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
chem.name	Chemical name (spaces and capitalization ignored) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Parameters from the appropriate parameterization function for the model indicated by argument model
Vr	Ratio of cell volume to incubation volume. Default is taken from
pH	pH of the incubation medium.

Value

A numeric fraction between zero and one

Author(s)

John Wambaugh and Robert Pearce

References

Kilford, Peter J., et al. "Hepatocellular binding of drugs: correction for unbound fraction in hepatocyte incubations using microsomal binding or drug lipophilicity data." *Drug Metabolism and Disposition* 36.7 (2008): 1194-1197.

Wetmore, Barbara A., et al. "Incorporating high-throughput exposure predictions with dosimetry-adjusted in vitro bioactivity to inform chemical toxicity testing." *Toxicological Sciences* 148.1 (2015): 121-136.

calc_ionization

Calculate the ionization.

Description

This function calculates the ionization of a compound at a given pH. The pKa's are either entered as parameters or taken from a specific compound in the package.

Usage

```
calc_ionization(  
  chem.cas = NULL,  
  chem.name = NULL,  
  dtxsid = NULL,  
  parameters = NULL,  
  pH = NULL,  
  pKa_Donor = NULL,  
  pKa_Accept = NULL  
)
```

Arguments

chem.cas	Either the chemical name or the CAS number must be specified.
chem.name	Either the chemical name or the CAS number must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from a parameterize_MODEL function, overrides chem.name and chem.cas.
pH	pH where ionization is evaluated.
pKa_Donor	Compound H dissociation equilibrium constant(s). Overwrites chem.name and chem.cas.
pKa_Accept	Compound H association equilibrium constant(s). Overwrites chem.name and chem.cas.

Details

The arguments pKa_Donor and pKa_Accept may be single numbers, characters, or vectors. We support characters because there are many instances with multiple predicted values and all those values can be included by concatenating with commas (for example, pKa_Donor = "8.1,8.6". Finally, pKa_Donor and pKa_Accept may be vectors of characters representing different chemicals or instances of chemical parameters to allow for uncertainty analysis.

The fractions are calculated by determining the coefficients for each species and dividing the particular species by the sum of all three. The positive, negative and zwitterionic/neutral coefficients are given by:

$$zwitter/neutral = 1$$

$$for(iin1 : pkaboveneutral)negative = negative + 10^{i * pH - pKa1 - ... - pKai}$$

$$for(iin1 : pkbelowneutral)positive = positive + 10^{pKa1 + ... + pKai - i * pH}$$

where i begins at 1 and ends at the number of points above(for negative) or below(for positive) the neutral/zwitterionic range. The neutral/zwitterionic range is either the pH range between 2 pKa's where the number of acceptors above is equal to the number of donors below, everything above the pKa acceptors if there are no donors, or everything below the pKa donors if there are no acceptors. Each of the terms in the sums represent a different ionization.

Value

```
fraction_neutral
      fraction of compound neutral
fraction_charged
      fraction of compound charged
fraction_negative
      fraction of compound negative
fraction_positive
      fraction of compound positive
fraction_zwitter
      fraction of compound zwitterionic
```

Author(s)

Robert Pearce and John Wambaugh

References

Pearce, Robert G., et al. "Evaluation and calibration of high-throughput predictions of chemical distribution to tissues." *Journal of Pharmacokinetics and Pharmacodynamics* 44.6 (2017): 549-565.

Strope, Cory L., et al. "High-throughput in-silico prediction of ionization equilibria for pharmacokinetic modeling." *Science of The Total Environment* 615 (2018): 150-160.

Examples

```
# Donor pKa's 9.78,10.39 -- Should be almost all neutral at plasma pH:
out <- calc_ionization(chem.name='bisphenola',pH=7.4)
print(out)
out[["fraction_neutral"]] == max(unlist(out))

# Donor pKa's 9.78,10.39 -- Should be almost all negative (anion) at higher pH:
out <- calc_ionization(chem.name='bisphenola',pH=11)
```

```

print(out)
out[["fraction_negative"]] == max(unlist(out))

# Fictious compound, should be almost all all negative (anion):
out <- calc_ionization(pKa_Donor=8,pKa_Accept="1,4",pH=9)
print(out)
out[["fraction_negative"]] > 0.9

# Donor pKa 6.54 -- Should be mostly negative (anion):
out <- calc_ionization(chem.name='Acephate',pH=7)
print(out)
out[["fraction_negative"]] == max(unlist(out))

#Acceptor pKa's "9.04,6.04" -- Should be almost all positive (cation) at plasma pH:
out <- calc_ionization(chem.cas="145742-28-5",pH=7.4)
print(out)
out[["fraction_positive"]] == max(unlist(out))

#Fictious Zwitteron:
out <- calc_ionization(pKa_Donor=6,pKa_Accept="8",pH=7.4)
print(out)
out[["fraction_zwitter"]] == max(unlist(out))

```

calc_krbc2pu

Back-calculates the Red Blood Cell to Unbound Plasma Partition Coefficient

Description

Given an observed ratio of chemical concentration in blood to plasma, this function calculates a Red Blood Cell to unbound plasma (K_{rbc2pu}) partition coefficient that would be consistent with that observation.

Usage

```

calc_krbc2pu(
  Rb2p,
  Funbound.plasma,
  hematocrit = NULL,
  default.to.human = FALSE,
  species = "Human",
  suppress.messages = TRUE
)

```

Arguments

Rb2p	The chemical blood:plasma concentration ratio
Funbound.plasma	The free fraction of chemical in the presence of plasma protein R _{blood2plasma} .
hematocrit	Overwrites default hematocrit value in calculating R _{blood2plasma} .
default.to.human	Substitutes missing animal values with human values if true.

species Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
 suppress.messages Determine whether to display certain usage feedback.

Value

The red blood cell to unbound chemical in plasma partition coefficient.

Author(s)

John Wambaugh and Robert Pearce

References

Pearce, Robert G., et al. "Evaluation and calibration of high-throughput predictions of chemical distribution to tissues." *Journal of pharmacokinetics and pharmacodynamics* 44.6 (2017): 549-565.
 Ruark, Christopher D., et al. "Predicting passive and active tissue: plasma partition coefficients: interindividual and interspecies variability." *Journal of pharmaceutical sciences* 103.7 (2014): 2189-2198.

calc_maternal_bw	<i>Calculate maternal body weight</i>
------------------	---------------------------------------

Description

This function initializes the parameters needed in the functions solve_fetal_pbt by calling solve_pbt and adding additional parameters.

Usage

```
calc_maternal_bw(week = 12)
```

Arguments

week Gestational week

Details

```
BW <- params$pre_pregnant_BW + params$BW_cubic_theta1 * tw + params$BW_cubic_theta2 * tw^2 + params$BW_cubic_theta3 * tw^3
```

Value

BW Maternal Body Weight, kg.

Author(s)

John Wambaugh

References

Kapraun, Dustin F., et al. "Empirical models for anatomical and physiological changes in a human mother and fetus during pregnancy and gestation." *PloS one* 14.5 (2019): e0215906.

calc_mc_css

*Find the monte carlo steady state concentration.***Description**

This function finds the analytical steady state plasma concentration(from calc_analytic_css) using a monte carlo simulation (monte_carlo).

Usage

```
calc_mc_css(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  parameters = NULL,
  samples = 1000,
  which.quantile = 0.95,
  species = "Human",
  suppress.messages = FALSE,
  model = "3compartmentss",
  httkpop = TRUE,
  invitrouv = TRUE,
  calcrb2p = TRUE,
  censored.params = list(),
  vary.params = list(),
  return.samples = FALSE,
  tissue = NULL,
  output.units = "mg/L",
  invitro.mc.arg.list = list(adjusted.Funbound.plasma = TRUE, poormetab = TRUE,
    fup.censored.dist = FALSE, fup.lod = 0.01, fup.meas.cv = 0.4, clint.meas.cv = 0.3,
    fup.pop.cv = 0.3, clint.pop.cv = 0.3),
  httkpop.generate.arg.list = list(method = "direct resampling", gendernum = NULL,
    agelim_years = NULL, agelim_months = NULL, weight_category = c("Underweight",
    "Normal", "Overweight", "Obese"), gfr_category = c("Normal", "Kidney Disease",
    "Kidney Failure"), reths = c("Mexican American", "Other Hispanic",
    "Non-Hispanic White", "Non-Hispanic Black", "Other")),
  convert.httkpop.arg.list = list(),
  parameterize.arg.list = list(default.to.human = FALSE, clint.pvalue.threshold = 0.05,
    restrictive.clearance = TRUE, regression = TRUE),
  calc.analytic.css.arg.list = list(well.stirred.correction = TRUE,
    adjusted.Funbound.plasma = TRUE, regression = TRUE, IVIVE = NULL, tissue = tissue,
    restrictive.clearance = TRUE, bioactive.free.invivo = FALSE),
  parameterize.args = list(default.to.human = F, adjusted.Funbound.plasma = T,
    regression = T, minimum.Funbound.plasma = 1e-04)
)
```

Arguments

chem.cas	Chemical Abstract Services Registry Number (CAS-RN) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
----------	--

chem.name	Chemical name (spaces and capitalization ignored) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Parameters from the appropriate parameterization function for the model indicated by argument model
samples	Number of samples generated in calculating quantiles.
which.quantile	Which quantile from Monte Carlo simulation is requested. Can be a vector.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human"). Species must be set to "Human" to run httkpop model.
suppress.messages	Whether or not to suppress output message.
model	Model used in calculation, 'gas_pbt' for the gas pbt model, 'pbt' for the multiple compartment model, '3compartment' for the three compartment model, '3compartmentss' for the three compartment steady state model, and '1compartment' for one compartment model. This only applies when httkpop=TRUE and species="Human", otherwise '3compartmentss' is used.
httkpop	Whether or not to use population generator and sampler from httkpop. This is overwrites censored.params and vary.params and is only for human physiology. Species must also be set to 'Human'.
invitrouv	Logical to indicate whether to include in vitro parameters in uncertainty and variability analysis
calcrb2p	Logical determining whether or not to recalculate the chemical ratio of blood to plasma
censored.params	The parameters listed in censored.params are sampled from a normal distribution that is censored for values less than the limit of detection (specified separately for each parameter). This argument should be a list of sublists. Each sublist is named for a parameter in "parameters" and contains two elements: "CV" (coefficient of variation) and "LOD" (limit of detection, below which parameter values are censored. New values are sampled with mean equal to the value in "parameters" and standard deviation equal to the mean times the CV. Censored values are sampled on a uniform distribution between 0 and the limit of detection. Not used with httkpop model.
vary.params	The parameters listed in vary.params are sampled from a normal distribution that is truncated at zero. This argument should be a list of coefficients of variation (CV) for the normal distribution. Each entry in the list is named for a parameter in "parameters". New values are sampled with mean equal to the value in "parameters" and standard deviation equal to the mean times the CV. Not used with httkpop model.
return.samples	Whether or not to return the vector containing the samples from the simulation instead of the selected quantile.
tissue	Desired steady state tissue concentration.
output.units	Plasma concentration units, either uM or default mg/L.
invitro.mc.arg.list	List of additional parameters passed to invitro_mc

httkpop.generate.arg.list
Additional parameters passed to [httkpop_generate](#).

convert.httkpop.arg.list
Additional parameters passed to the convert_httkpop_* function for the model.

parameterize.arg.list
Additional parameters passed to the parameterize_* function for the model.

calc.analytic.css.arg.list
Additional parameters passed to [calc_analytic_css](#).

parameterize.args
A list of arguments to be passed to the model parameterization function (that is, parameterize_MODEL) corresponding to argument "model". (Defaults to NULL.)

Details

All arguments after httkpop only apply if httkpop is set to TRUE and species to "Human".

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data (volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Tissue concentrations are calculated for the pbtk model with a default oral infusion dosing. All tissues other than gut, liver, and lung are the product of the steady state plasma concentration and the tissue to plasma partition coefficient.

The six sets of plausible *in vitro-in vivo* extrapolation (IVIVE) assumptions identified by Honda et al. (2019) are:

	<i>in vivo</i> Conc.	Metabolic Clearance	Bioactive Chemical Conc.	TK Statistic Used*
Honda1	Veinous (Plasma)	Restrictive	Free	Mean Conc.
Honda2	Veinous	Restrictive	Free	Max Conc.
Honda3	Veinous	Non-restrictive	Total	Mean Conc.
Honda4	Veinous	Non-restrictive	Total	Max Conc.
Honda5	Target Tissue	Non-restrictive	Total	Mean Conc.
Honda6	Target Tissue	Non-restrictive	Total	Max Conc.

*Assumption is currently ignored because analytical steady-state solutions are currently used by this function.

Value

Quantiles (specified by which.quantile) of the distribution of plasma steady-state concentration (Css) from the Monte Carlo simulation

Author(s)

Caroline Ring, Robert Pearce, John Wambaugh, Miyuki Breen

References

Wambaugh, John F., et al. "Toxicokinetic triage for environmental chemicals." *Toxicological Sciences* 147.1 (2015): 55-67.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment international* 106 (2017): 105-118.

Honda, Gregory S., et al. "Using the Concordance of In Vitro and In Vivo Data to Evaluate Extrapolation Assumptions." 2019. *PLoS ONE* 14(5): e0217564.

Rowland, Malcolm, Leslie Z. Benet, and Garry G. Graham. "Clearance concepts in pharmacokinetics." *Journal of pharmacokinetics and biopharmaceutics* 1.2 (1973): 123-136.

Examples

```
set.seed(1234)
calc_mc_css(chem.name='Bisphenol A',output.units='uM',
            samples=100,return.samples=TRUE)

set.seed(1234)
calc_mc_css(chem.name='Bisphenol A',output.units='uM',httkpop.generate.arg.list=list(method='vi'))

set.seed(1234)
calc_mc_css(chem.name='2,4-d',which.quantile=.9,httkpop=FALSE,tissue='heart')

set.seed(1234)
calc_mc_css(chem.cas = "80-05-7", which.quantile = 0.5,
            output.units = "uM", samples = 2000,
            httkpop.generate.arg.list=list(method='vi', gendernum=NULL,
            agelim_years=NULL, agelim_months=NULL, weight_category =
            c("Underweight", "Normal", "Overweight", "Obese")))

params <- parameterize_pbt(chem.cas="80-05-7")
set.seed(1234)
calc_mc_css(parameters=params,model="pbt")

set.seed(1234)
# Standard HTTK Monte Carlo:
NSAMP = 500
calc_mc_css(chem.cas="90-43-7",model="pbt",samples=NSAMP)
set.seed(1234)
calc_mc_css(chem.cas="90-43-7",
            model="pbt",
            samples=NSAMP,
            invitro.mc.arg.list = list(
              adjusted.funbound.plasma = TRUE,
              poormetab = TRUE,
              fup.censored.dist = FALSE,
              fup.lod = 0.01,
              fup.meas.cv = 0.0,
              clint.meas.cv = 0.0,
              fup.pop.cv = 0.3,
              clint.pop.cv = 0.3))
set.seed(1234)
# HTTK Monte Carlo with no HTTK-Pop physiological variability):
calc_mc_css(chem.cas="90-43-7",model="pbt",samples=NSAMP,httkpop=FALSE)
set.seed(1234)
# HTTK Monte Carlo with no in vitro uncertainty and variability):
```

```

calc_mc_css(chem.cas="90-43-7",model="pbt",samples=NSAMP,invitrouv=FALSE)
set.seed(1234)
# HTTK Monte Carlo with no HTTK-Pop and no in vitro uncertainty and variability):
calc_mc_css(chem.cas="90-43-7",model="pbt",samples=NSAMP,httkpop=FALSE,invitrouv=FALSE)
# Should be the same as the mean result:
calc_analytic_css(chem.cas="90-43-7",model="pbt",output.units="mg/L")
set.seed(1234)
# HTTK Monte Carlo using basic Monte Carlo sampler:
calc_mc_css(chem.cas="90-43-7",
model="pbt",
samples=NSAMP,
httkpop=FALSE,
invitrouv=FALSE,
vary.params=list(Pow=0.3))

```

calc_mc_oral_equiv	<i>Calculate Monte Carlo Oral Equivalent Dose</i>
--------------------	---

Description

This functions converts a chemical plasma concentration to an oral equivalent dose using a concentration obtained from [calc_mc_css](#).

Usage

```

calc_mc_oral_equiv(
  conc,
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  which.quantile = 0.95,
  species = "Human",
  input.units = "uM",
  output.units = "mgpkgpday",
  suppress.messages = FALSE,
  return.samples = FALSE,
  concentration = "plasma",
  restrictive.clearance = TRUE,
  bioactive.free.invivo = FALSE,
  tissue = NULL,
  IVIVE = NULL,
  ...
)

```

Arguments

conc	Bioactive in vitro concentration in units of uM.
chem.name	Either the chemical name or the CAS number must be specified.
chem.cas	Either the CAS number or the chemical name must be specified.

dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
which.quantile	Which quantile from Monte Carlo steady-state simulation (calc_mc_css) is requested. Can be a vector. Note that 95th concentration quantile is the same population as the 5th dose quantile.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
input.units	Units of given concentration, default of uM but can also be mg/L.
output.units	Units of dose, default of 'mgpkgpday' for mg/kg BW/ day or 'umolpkgpday' for umol/ kg BW/ day.
suppress.messages	Suppress text messages.
return.samples	Whether or not to return the vector containing the samples from the simulation instead of the selected quantile.
concentration	Desired concentration type, 'blood', 'tissue', or default 'plasma'.
restrictive.clearance	Protein binding not taken into account (set to 1) in liver clearance if FALSE.
bioactive.free.invivo	If FALSE (default), then the total concentration is treated as bioactive in vivo. If TRUE, the the unbound (free) plasma concentration is treated as bioactive in vivo. Only works with tissue = NULL in current implementation.
tissue	Desired steady state tissue concentration.
IVIVE	Honda et al. (2019) identified six plausible sets of assumptions for <i>in vitro-in vivo</i> extrapolation (IVIVE) assumptions. Argument may be set to "Honda1" through "Honda6". If used, this function overwrites the tissue, restrictive.clearance, and plasma.binding arguments. See Details below for more information.
...	Additional parameters passed to calc_mc_css for httkpop and variance of parameters.

Details

All arguments after httkpop only apply if httkpop is set to TRUE and species to "Human".

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Tissue concentrations are calculated for the pbtk model with oral infusion dosing. All tissues other than gut, liver, and lung are the product of the steady state plasma concentration and the tissue to plasma partition coefficient.

The six sets of plausible *in vitro-in vivo* extrapolation (IVIVE) assumptions identified by Honda et al. (2019) are:

	<i>in vivo</i> Conc.	Metabolic Clearance	Bioactive Chemical Conc.	TK Statistic Used*
Honda1	Veinous (Plasma)	Restrictive	Free	Mean Conc.
Honda2	Veinous	Restrictive	Free	Max Conc.
Honda3	Veinous	Non-restrictive	Total	Mean Conc.
Honda4	Veinous	Non-restrictive	Total	Max Conc.
Honda5	Target Tissue	Non-restrictive	Total	Mean Conc.
Honda6	Target Tissue	Non-restrictive	Total	Max Conc.

*Assumption is currently ignored because analytical steady-state solutions are currently used by this function.

Value

Equivalent dose in specified units, default of mg/kg BW/day.

Author(s)

John Wambaugh

References

- Wetmore, Barbara A., et al. "Incorporating high-throughput exposure predictions with dosimetry-adjusted in vitro bioactivity to inform chemical toxicity testing." *Toxicological Sciences* 148.1 (2015): 121-136.
- Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment international* 106 (2017): 105-118.
- Honda, Gregory S., et al. "Using the Concordance of In Vitro and In Vivo Data to Evaluate Extrapolation Assumptions." 2019. *PLoS ONE* 14(5): e0217564.
- Rowland, Malcolm, Leslie Z. Benet, and Garry G. Graham. "Clearance concepts in pharmacokinetics." *Journal of pharmacokinetics and biopharmaceutics* 1.2 (1973): 123-136.

Examples

```
calc_mc_oral_equiv(0.1, chem.cas="34256-82-1", which.quantile=c(0.05,0.5,0.95),  
  tissue='brain')
```

calc_mc_tk

Conduct multiple TK simulations using Monte Carlo

Description

This function finds the analytical steady state plasma concentration(from calc_analytic_css) using a monte carlo simulation (monte_carlo).

Usage

```
calc_mc_tk(  
  chem.cas = NULL,  
  chem.name = NULL,  
  dtxsid = NULL,  
  parameters = NULL,  
  samples = 1000,  
  which.quantile = 0.95,  
  species = "Human",
```

```

suppress.messages = FALSE,
model = "pbtk",
httkpop = TRUE,
invitrouv = TRUE,
calcrb2p = TRUE,
censored.params = list(),
vary.params = list(),
return.samples = FALSE,
tissue = NULL,
output.units = "mg/L",
solve.model.arg.list = list(times = c(0, 0.25, 0.5, 0.75, 1, 1.5, 2, 2.5, 3, 4, 5)),
invitro.mc.arg.list = list(adjusted.funbound.plasma = TRUE, poormetab = TRUE,
  fup.censored.dist = FALSE, fup.lod = 0.01, fup.meas.cv = 0.4, clint.meas.cv = 0.3,
  fup.pop.cv = 0.3, clint.pop.cv = 0.3),
httkpop.generate.arg.list = list(method = "direct resampling", gendernum = NULL,
  agelim.years = NULL, agelim.months = NULL, weight.category = c("Underweight",
  "Normal", "Overweight", "Obese"), gfr.category = c("Normal", "Kidney Disease",
  "Kidney Failure"), reths = c("Mexican American", "Other Hispanic",
  "Non-Hispanic White", "Non-Hispanic Black", "Other")),
convert.httkpop.arg.list = list(),
parameterize.arg.list = list(default.to.human = FALSE, clint.pvalue.threshold = 0.05,
  restrictive.clearance = TRUE, regression = TRUE),
return.all.sims = FALSE
)

```

Arguments

chem.cas	Either the CAS number, parameters, or the chemical name must be specified.
chem.name	Either the chemical parameters, name, or the CAS number must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Parameters from parameterize_steadystate. Not used with httkpop model.
samples	Number of samples generated in calculating quantiles.
which.quantile	Which quantile from Monte Carlo simulation is requested. Can be a vector.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human"). Species must be set to "Human" to run httkpop model.
suppress.messages	Whether or not to suppress output message.
model	Model used in calculation: 'pbtk' for the multiple compartment model, '3compartment' for the three compartment model, '3compartmentss' for the three compartment steady state model, and '1compartment' for one compartment model. This only applies when httkpop=TRUE and species="Human", otherwise '3compartmentss' is used.
httkpop	Whether or not to use population generator and sampler from httkpop. This is overwrites censored.params and vary.params and is only for human physiology. Species must also be set to 'Human'.
invitrouv	Logical to indicate whether to include in vitro parameters in uncertainty and variability analysis
calcrb2p	Logical determining whether or not to recalculate the chemical ratio of blood to plasma

censored.params	The parameters listed in censored.params are sampled from a normal distribution that is censored for values less than the limit of detection (specified separately for each parameter). This argument should be a list of sub-lists. Each sublist is named for a parameter in "parameters" and contains two elements: "CV" (coefficient of variation) and "LOD" (limit of detection, below which parameter values are censored. New values are sampled with mean equal to the value in "parameters" and standard deviation equal to the mean times the CV. Censored values are sampled on a uniform distribution between 0 and the limit of detection. Not used with httkpop model.
vary.params	The parameters listed in vary.params are sampled from a normal distribution that is truncated at zero. This argument should be a list of coefficients of variation (CV) for the normal distribution. Each entry in the list is named for a parameter in "parameters". New values are sampled with mean equal to the value in "parameters" and standard deviation equal to the mean times the CV. Not used with httkpop model.
return.samples	Whether or not to return the vector containing the samples from the simulation instead of the selected quantile.
tissue	Desired steady state tissue concentration.
output.units	Plasma concentration units, either uM or default mg/L.
solvemodel.arg.list	Additional arguments ultimately passed to solve_model
invitro.mc.arg.list	List of additional parameters passed to invitro_mc
httkpop.generate.arg.list	Additional parameters passed to httkpop_generate .
convert.httkpop.arg.list	Additional parameters passed to the <code>convert_httkpop_*</code> function for the model.
parameterize.arg.list	Additional parameters passed to the <code>parameterize_*</code> function for the model.
return.all.sims	Logical indicating whether to return the results of all simulations, in addition to the default toxicokinetic statistics

Details

All arguments after httkpop only apply if httkpop is set to TRUE and species to "Human".

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Tissue concentrations are calculated for the pbtk model with oral infusion dosing. All tissues other than gut, liver, and lung are the product of the steady state plasma concentration and the tissue to plasma partition coefficient.

The six sets of plausible *in vitro-in vivo* extrapolation (IVIVE) assumptions identified by Honda et al. (2019) are:

	<i>in vivo</i> Conc.	Metabolic Clearance	Bioactive Chemical Conc.	TK Statistic Used*
Honda1	Veinous (Plasma)	Restrictive	Free	Mean Conc.
Honda2	Veinous	Restrictive	Free	Max Conc.
Honda3	Veinous	Non-restrictive	Total	Mean Conc.

Honda4	Veinous	Non-restrictive	Total	Max Conc.
Honda5	Target Tissue	Non-restrictive	Total	Mean Conc.
Honda6	Target Tissue	Non-restrictive	Total	Max Conc.

*Assumption is currently ignored because analytical steady-state solutions are currently used by this function.

Value

If return.all.sims == FALSE (default) a list with:

means	The mean concentration for each model compartment as a function of time across the Monte Carlo simulation
sds	The standard deviation for each model compartment as a function of time across the Monte Carlo simulation

If return.all.sims == TRUE then a list is returned with:

stats	The list of means and sds from return.all.sims=FALSE
sims	The concentration vs. time results for each compartment for every (samples) set of parameters in the Monte Carlo simulation

Author(s)

John Wambaugh

Examples

```

NSAMP <- 50
chemname="Abamectin"
times<- c(0,0.25,0.5,0.75,1,1.5,2,2.5,3,4,5)
age.ranges <- seq(6,80,by=10)
forward <- NULL
for (age.lower in age.ranges)
{
  label <- paste("Ages ",age.lower,"-",age.lower+4,sep="")
  set.seed(1234)
  forward[[label]] <- calc_mc_tk(
    chem.name=chemname,
    samples=NSAMP,
    httkpop.generate.arg.list=list(
      method="d",
      agelim_years = c(age.lower, age.lower+9)),
    solvemodel.arg.list = list(
      times=times))
}

```

calc_rblood2plasma	<i>Calculate the constant ratio of the blood concentration to the plasma concentration.</i>
--------------------	---

Description

This function calculates the constant ratio of the blood concentration to the plasma concentration.

Usage

```
calc_rblood2plasma(  
  chem.cas = NULL,  
  chem.name = NULL,  
  dtxsid = NULL,  
  parameters = NULL,  
  hematocrit = NULL,  
  Krbc2pu = NULL,  
  Funbound.plasma = NULL,  
  default.to.human = FALSE,  
  species = "Human",  
  adjusted.Funbound.plasma = TRUE,  
  suppress.messages = TRUE  
)
```

Arguments

chem.cas	Either the CAS number or the chemical name must be specified.
chem.name	Either the chemical name or the CAS number must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Parameters from parameterize_schmitt
hematocrit	Overwrites default hematocrit value in calculating Rblood2plasma.
Krbc2pu	The red blood cell to unbound plasma chemical partition coefficient, typically from predict_partitioning_schmitt
Funbound.plasma	The fraction of chemical unbound (free) in the presence of plasma protein
default.to.human	Substitutes missing animal values with human values if true.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
adjusted.Funbound.plasma	Whether or not to use Funbound.plasma adjustment.
suppress.messages	Determine whether to display certain usage feedback.

Details

The red blood cell (RBC) partition coefficient as predicted by the Schmitt (2008) method is used in the calculation. The value is calculated with the equation: $1 - \text{hematocrit} + \text{hematocrit} * K_{\text{rbc2pu}} * \text{Funbound.plasma}$, summing the red blood cell to plasma and plasma:plasma (equal to 1) partition coefficients multiplied by their respective fractional volumes. When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data (hematocrit and temperature), but substitutes human fraction unbound and tissue volumes.

Value

The blood to plasma chemical concentration ratio

Author(s)

John Wambaugh and Robert Pearce

References

Schmitt W. "General approach for the calculation of tissue to plasma partition coefficients." *Toxicology In Vitro*, 22, 457-467 (2008).

Pearce, Robert G., et al. "Evaluation and calibration of high-throughput predictions of chemical distribution to tissues." *Journal of pharmacokinetics and pharmacodynamics* 44.6 (2017): 549-565.

Ruark, Christopher D., et al. "Predicting passive and active tissue: plasma partition coefficients: interindividual and interspecies variability." *Journal of pharmaceutical sciences* 103.7 (2014): 2189-2198.

Examples

```
calc_rblood2plasma(chem.name="Bisphenol A")
calc_rblood2plasma(chem.name="Bisphenol A",species="Rat")
```

calc_stats

Calculate toxicokinetic summary statistics (deprecated).

Description

#' This function is included for backward compatibility. It calls `calc_tkstats` which calculates the area under the curve, the mean, and the peak values for the venous blood or plasma concentration of a specified chemical or all chemicals if none is specified for the multiple compartment model with a given number of days, dose, and number of doses per day.

Usage

```
calc_stats(  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL,  
  parameters = NULL,  
  route = "oral",
```

```

stats = c("AUC", "peak", "mean"),
species = "Human",
days = 28,
daily.dose = 1,
dose = NULL,
doses.per.day = 1,
output.units = "uM",
concentration = "plasma",
tissue = "plasma",
model = "pbtk",
default.to.human = FALSE,
adjusted.funbound.plasma = TRUE,
regression = TRUE,
restrictive.clearance = TRUE,
suppress.messages = FALSE,
...
)

```

Arguments

chem.name	Name of desired chemical.
chem.cas	CAS number of desired chemical.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_pbtk function, overrides chem.name and chem.cas.
route	String specification of route of exposure for simulation: "oral", "iv", "inhalation", ...
stats	Desired values (either 'AUC', 'mean', 'peak', or a vector containing any combination).
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
days	Length of the simulation.
daily.dose	Total daily dose, mg/kg BW.
dose	Amount of a single dose at time zero, mg/kg BW.
doses.per.day	Number of doses per day.
output.units	Desired units (either "mg/L", "mg", "umol", or default "uM").
concentration	Desired concentration type, 'blood' or default 'plasma'.
tissue	Desired steady state tissue concentration.
model	Model used in calculation, 'pbtk' for the multiple compartment model, '3compartment' for the three compartment model, '3compartmentss' for the three compartment steady state model, and '1compartment' for one compartment model.
default.to.human	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
adjusted.funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.


```
restrictive.clearance
    Protein binding not taken into account (set to 1) in liver clearance if FALSE.
suppress.messages
    Whether to suppress output message.
...
    Arguments passed to solve function.
```

Details

Default value of 0 for doses.per.day solves for a single dose.

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

```
AUC          Area under the plasma concentration curve.
mean.conc    The area under the curve divided by the number of days.
peak.conc    The highest concentration.
```

Author(s)

Robert Pearce and John Wambaugh

calc_tkstats	<i>Calculate toxicokinetic summary statistics.</i>
--------------	--

Description

This function calculates the area under the curve, the mean, and the peak values for the venous blood or plasma concentration of a specified chemical or all chemicals if none is specified for the multiple compartment model with a given number of days, dose, and number of doses per day.

Usage

```
calc_tkstats(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  parameters = NULL,
  route = "oral",
  stats = c("AUC", "peak", "mean"),
  species = "Human",
  days = 28,
  daily.dose = 1,
  dose = NULL,
  doses.per.day = 1,
  output.units = "uM",
  concentration = "plasma",
  tissue = "plasma",
  model = "pbtk",
```

```

    default.to.human = FALSE,
    adjusted.funbound.plasma = TRUE,
    regression = TRUE,
    restrictive.clearance = TRUE,
    suppress.messages = FALSE,
    ...
)

```

Arguments

chem.name	Name of desired chemical.
chem.cas	CAS number of desired chemical.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Chemical parameters from parameterize_pbt function, overrides chem.name and chem.cas.
route	String specification of route of exposure for simulation: "oral", "iv", "inhalation", ...
stats	Desired values (either 'AUC', 'mean', 'peak', or a vector containing any combination).
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
days	Length of the simulation.
daily.dose	Total daily dose, mg/kg BW.
dose	Amount of a single dose at time zero, mg/kg BW.
doses.per.day	Number of doses per day.
output.units	Desired units (either "mg/L", "mg", "umol", or default "uM").
concentration	Desired concentration type, 'blood' or default 'plasma'.
tissue	Desired steady state tissue concentration.
model	Model used in calculation, 'pbt' for the multiple compartment model, '3compartment' for the three compartment model, '3compartmentss' for the three compartment steady state model, and '1compartment' for one compartment model.
default.to.human	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
adjusted.funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
restrictive.clearance	Protein binding not taken into account (set to 1) in liver clearance if FALSE.
suppress.messages	Whether to suppress output message.
...	Arguments passed to solve function.

Details

Default value of 0 for doses.per.day solves for a single dose.

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data (volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

AUC	Area under the plasma concentration curve.
mean.conc	The area under the curve divided by the number of days.
peak.conc	The highest concentration.

Author(s)

Robert Pearce and John Wambaugh

Examples

```
calc_tkstats(chem.name='Bisphenol-A',days=100,stats='mean',model='3compartment')

calc_tkstats(chem.name='Bisphenol-A',days=100,stats=c('peak','mean'),species='Rat')

triclosan.stats <- calc_tkstats(days=10, chem.name = "triclosan")
```

calc_total_clearance	<i>Calculate the total plasma clearance.</i>
----------------------	--

Description

This function calculates the total clearance rate for a one compartment model for plasma where clearance is entirely due to metabolism by the liver and glomerular filtration in the kidneys, identical to clearance of three compartment steady state model.

Usage

```
calc_total_clearance(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  parameters = NULL,
  species = "Human",
  suppress.messages = FALSE,
  default.to.human = FALSE,
  well.stirred.correction = TRUE,
  restrictive.clearance = TRUE,
  adjusted.funbound.plasma = TRUE,
  ...
)
```

Arguments

chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
chem.name	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXIDs
parameters	Chemical parameters from parameterize_steadystate function, overrides chem.name and chem.cas.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
suppress.messages	Whether or not the output message is suppressed.
default.to.human	Substitutes missing animal values with human values if true.
well.stirred.correction	Uses correction in calculation of hepatic clearance for well-stirred model if TRUE. This assumes clearance relative to amount unbound in whole blood instead of plasma, but converted to use with plasma concentration.
restrictive.clearance	Protein binding is not taken into account (set to 1) in liver clearance if FALSE.
adjusted.funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE.
...	Additional parameters passed to parameterize_steadystate if parameters is NULL.

Value

Total Clearance
Units of L/h/kg BW.

Author(s)

John Wambaugh

Examples

```
calc_total_clearance(chem.name="Ibuprofen")
```

calc_vdist

Calculate the volume of distribution for a one compartment model.

Description

This function predicts partition coefficients for all tissues, then lumps them into a single compartment.

Usage

```
calc_vdist(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  parameters = NULL,
  default.to.human = FALSE,
  species = "Human",
  suppress.messages = FALSE,
  adjusted.Funbound.plasma = TRUE,
  regression = TRUE,
  minimum.Funbound.plasma = 1e-04
)
```

Arguments

chem.cas	Either the CAS number or the chemical name must be specified when Funbound.plasma is not given in parameter list.
chem.name	Either the chemical name or the CAS number must be specified when Funbound.plasma is not given in parameter list.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Parameters from parameterize_3comp, parameterize_pbt or predict_partitioning_schmitt.
default.to.human	Substitutes missing animal values with human values if true.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
suppress.messages	Whether or not the output message is suppressed.
adjusted.Funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
minimum.Funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

Details

The effective volume of distribution is calculated by summing each tissues volume times it's partition coefficient relative to plasma. Plasma, and the partitioning into RBCs are also added to get the total volume of distribution in L/KG BW. Partition coefficients are calculated using Schmitt's (2008) method. When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

Volume of distribution
Units of L/ kg BW.

Author(s)

John Wambaugh and Robert Pearce

References

Schmitt W. "General approach for the calculation of tissue to plasma partition coefficients." *Toxicology In Vitro*, 22, 457-467 (2008). Peyret, T., Poulin, P., Krishnan, K., "A unified algorithm for predicting partition coefficients for PBPK modeling of drugs and environmental chemicals." *Toxicology and Applied Pharmacology*, 249, 197-207 (2010).

Examples

```
calc_vdist(chem.cas="80-05-7")  
calc_vdist(chem.name="Bisphenol A")  
calc_vdist(chem.name="Bisphenol A",species="Rat")
```

CAS.checksum

Test the check digit of a CAS number to confirm validity

Description

Chemical abstracts services registry numbers (CAS-RN) include a final digit as a "checksum" to test for validity (that is, that the number has not been corrupted).

Usage

```
CAS.checksum(CAS.string)
```

Arguments

CAS.string A character string of three numbers separated by two dashes

Details

The check digit (final number) is calculated by working from right to left, starting with the second to last digit of the CAS-RN. We multiply each digit by an increasing digit (1, 2, 3...) and sum as we work from right to left. The check digit should equal the final digit of the sum.

Value

logical (TRUE if final digit of CAS is consistent with other digits)

Author(s)

John Wambaugh

chem.invivo.PK.aggregate.data*Parameter Estimates from Wambaugh et al. (2018)*

Description

This table includes 1 and 2 compartment fits of plasma concentration vs time data aggregated from chem.invivo.PK.data, performed in Wambaugh et al. 2018. Data includes volume of distribution (Vdist, L/kg), elimination rate (kelim, 1/h), gut absorption rate (kgutabs, 1/h), fraction absorbed (Fgutabs), and steady state concentration (Css, mg/L).

Usage

chem.invivo.PK.aggregate.data

Format

data.frame

Author(s)

John Wambaugh

Source

Wambaugh et al. 2018 Toxicological Sciences, in press

chem.invivo.PK.data*Published toxicokinetic time course measurements*

Description

This data set includes time and dose specific measurements of chemical concentration in tissues taken from animals administered control doses of the chemicals either orally or intravenously. This plasma concentration-time data is from rat experiments reported in public sources. Toxicokinetic data were retrieved from those studies by the Netherlands Organisation for Applied Scientific Research (TNO) using curve stripping (TechDig v2). This data is provided for statistical analysis as in Wambaugh et al. 2018.

Usage

chem.invivo.PK.data

Format

A data.frame containing 597 rows and 13 columns.

Author(s)

Sieto Bosgra

Source

Wambaugh et al. 2018 Toxicological Sciences, in press

References

- Aanderud L, Bakke OM (1983). Pharmacokinetics of antipyrine, paracetamol, and morphine in rat at 71 ATA. *Undersea Biomed Res.* 10(3):193-201. PMID: 6636344
- Aasmoe L, Mathiesen M, Sager G (1999). Elimination of methoxyacetic acid and ethoxyacetic acid in rat. *Xenobiotica.* 29(4):417-24. PMID: 10375010
- Ako RA. Pharmacokinetics/pharmacodynamics (PK/PD) of oral diethylstilbestrol (DES) in recurrent prostate cancer patients and of oral dissolving film (ODF)-DES in rats. PhD dissertation, College of Pharmacy, University of Houston, USA, 2011.
- Anadon A, Martinez-Larranaga MR, Fernandez-Cruz ML, Diaz MJ, Fernandez MC, Martinez MA (1996). Toxicokinetics of deltamethrin and its 4'-HO-metabolite in the rat. *Toxicol Appl Pharmacol.* 141(1):8-16. PMID: 8917670
- Binkerd PE, Rowland JM, Nau H, Hendrickx AG (1988). Evaluation of valproic acid (VPA) developmental toxicity and pharmacokinetics in Sprague-Dawley rats. *Fundam Appl Toxicol.* 11(3):485-93. PMID: 3146521
- Boralli VB, Coelho EB, Cerqueira PM, Lanchote VL (2005). Stereoselective analysis of metoprolol and its metabolites in rat plasma with application to oxidative metabolism. *J Chromatogr B Analyt Technol Biomed Life Sci.* 823(2):195-202. PMID: 16029965
- Chan MP, Morisawa S, Nakayama A, Kawamoto Y, Sugimoto M, Yoneda M (2005). Toxicokinetics of 14C-endosulfan in male Sprague-Dawley rats following oral administration of single or repeated doses. *Environ Toxicol.* 20(5):533-41. PMID: 16161119
- Cruz L, Castaneda-Hernandez G, Flores-Murrieta FJ, Garcia-Lopez P, Guizar-Sahagun G (2002). Alteration of phenacetin pharmacokinetics after experimental spinal cord injury. *Proc West Pharmacol Soc.* 45:4-5. PMID: 12434508
- Della Paschoa OE, Mandema JW, Voskuyl RA, Danhof M (1998). Pharmacokinetic-pharmacodynamic modeling of the anticonvulsant and electroencephalogram effects of phenytoin in rats. *J Pharmacol Exp Ther.* 284(2):460-6. PMID: 9454785
- Du B, Li X, Yu Q, A Y, Chen C (2010). Pharmacokinetic comparison of orally disintegrating, beta-cyclodextrin inclusion complex and conventional tablets of nicardipine in rats. *Life Sci J.* 7(2):80-4.
- Farris FF, Dedrick RL, Allen PV, Smith JC (1993). Physiological model for the pharmacokinetics of methyl mercury in the growing rat. *Toxicol Appl Pharmacol.* 119(1):74-90. PMID: 8470126
- Hays SM, Elswick BA, Blumenthal GM, Welsch F, Conolly RB, Gargas ML (2000). Development of a physiologically based pharmacokinetic model of 2-methoxyethanol and 2-methoxyacetic acid disposition in pregnant rats. *Toxicol Appl Pharmacol.* 163(1):67-74. PMID: 10662606
- Igari Y, Sugiyama Y, Awazu S, Hanano M (1982). Comparative physiologically based pharmacokinetics of hexobarbital, phenobarbital and thiopental in the rat. *J Pharmacokinet Biopharm.* 10(1):53-75. PMID: 7069578
- Ito K, Houston JB (2004). Comparison of the use of liver models for predicting drug clearance using in vitro kinetic data from hepatic microsomes and isolated hepatocytes. *Pharm Res.* 21(5):785-92. PMID: 15180335
- Jia L, Wong H, Wang Y, Garza M, Weitman SD (2003). Carbendazim: disposition, cellular permeability, metabolite identification, and pharmacokinetic comparison with its nanoparticle. *J Pharm Sci.* 92(1):161-72. PMID: 12486692

- Kawai R, Mathew D, Tanaka C, Rowland M (1998). Physiologically based pharmacokinetics of cyclosporine A: extension to tissue distribution kinetics in rats and scale-up to human. *J Pharmacol Exp Ther.* 287(2):457-68. PMID: 9808668
- Kim YC, Kang HE, Lee MG (2008). Pharmacokinetics of phenytoin and its metabolite, 4'-HPPH, after intravenous and oral administration of phenytoin to diabetic rats induced by alloxan or streptozotocin. *Biopharm Drug Dispos.* 29(1):51-61. PMID: 18022993
- Kobayashi S, Takai K, Iga T, Hanano M (1991). Pharmacokinetic analysis of the disposition of valproate in pregnant rats. *Drug Metab Dispos.* 19(5):972-6. PMID: 1686245
- Kotegawa T, Laurijssens BE, Von Moltke LL, Cotreau MM, Perloff MD, Venkatakrishnan K, Warrington JS, Granda BW, Harmatz JS, Greenblatt DJ (2002). In vitro, pharmacokinetic, and pharmacodynamic interactions of ketoconazole and midazolam in the rat. *J Pharmacol Exp Ther.* 302(3):1228-37. PMID: 12183684
- Krug AK, Kolde R, Gaspar JA, Rempel E, Balmer NV, Meganathan K, Vojnits K, Baquie M, Waldmann T, Ensenat-Waser R, Jagtap S, Evans RM, Julien S, Peterson H, Zagoura D, Kadereit S, Gerhard D, Sotiriadou I, Heke M, Natarajan K, Henry M, Winkler J, Marchan R, Stoppini L, Bosgra S, Westerhout J, Verwei M, Vilo J, Kortenkamp A, Hescheler J, Hothorn L, Bremer S, van Thriel C, Krause KH, Hengstler JG, Rahnenfuhrer J, Leist M, Sachinidis A (2013). Human embryonic stem cell-derived test systems for developmental neurotoxicity: a transcriptomics approach. *Arch Toxicol.* 87(1):123-43. PMID: 23179753
- Leon-Reyes MR, Castaneda-Hernandez G, Ortiz MI (2009). Pharmacokinetic of diclofenac in the presence and absence of glibenclamide in the rat. *J Pharm Pharm Sci.* 12(3):280-7. PMID: 20067705
- Nagata M, Hidaka M, Sekiya H, Kawano Y, Yamasaki K, Okumura M, Arimori K (2007). Effects of pomegranate juice on human cytochrome P450 2C9 and tolbutamide pharmacokinetics in rats. *Drug Metab Dispos.* 35(2):302-5. PMID: 17132763
- Okiyama M, Ueno K, Ohmori S, Igarashi T, Kitagawa H (1988). Drug interactions between imipramine and benzodiazepines in rats. *J Pharm Sci.* 77(1):56-63. PMID: 2894451
- Pelissier-Alicot AL, Schreiber-Deturmeny E, Simon N, Gantenbein M, Bruguerolle B (2002). Time-of-day dependent pharmacodynamic and pharmacokinetic profiles of caffeine in rats. *Naunyn Schmiedebergs Arch Pharmacol.* 365(4):318-25. PMID: 11919657
- Piersma AH, Bosgra S, van Duursen MB, Hermesen SA, Jonker LR, Kroese ED, van der Linden SC, Man H, Roelofs MJ, Schulpen SH, Schwarz M, Uibel F, van Vugt-Lussenburg BM, Westerhout J, Wolterbeek AP, van der Burg B (2013). Evaluation of an alternative in vitro test battery for detecting reproductive toxicants. *Reprod Toxicol.* 38:53-64. PMID: 23511061
- Pollack GM, Li RC, Ermer JC, Shen DD (1985). Effects of route of administration and repetitive dosing on the disposition kinetics of di(2-ethylhexyl) phthalate and its mono-de-esterified metabolite in rats. *Toxicol Appl Pharmacol.* Jun 30;79(2):246-56. PMID: 4002226
- Saadeddin A, Torres-Molina F, Carcel-Trullols J, Araico A, Peris JE (2004). Pharmacokinetics of the time-dependent elimination of all-trans-retinoic acid in rats. *AAPS J.* 6(1):1-9. PMID: 18465253
- Satterwhite JH, Boudinot FD (1991). Effects of age and dose on the pharmacokinetics of ibuprofen in the rat. *Drug Metab Dispos.* 19(1):61-7. PMID: 1673423
- Szymura-Oleksiak J, Panas M, Chrusciel W (1983). Pharmacokinetics of imipramine after single and multiple intravenous administration in rats. *Pol J Pharmacol Pharm.* 35(2):151-7. PMID: 6622297
- Tanaka C, Kawai R, Rowland M (2000). Dose-dependent pharmacokinetics of cyclosporin A in rats: events in tissues. *Drug Metab Dispos.* 28(5):582-9. PMID: 10772639

- Timchalk C, Nolan RJ, Mendrala AL, Dittenber DA, Brzak KA, Mattsson JL (2002). A Physiologically based pharmacokinetic and pharmacodynamic (PBPK/PD) model for the organophosphate insecticide chlorpyrifos in rats and humans. *Toxicol Sci.* Mar;66(1):34-53. PMID: 11861971
- Tokuma Y, Sekiguchi M, Niwa T, Noguchi H (1988). Pharmacokinetics of nilvadipine, a new dihydropyridine calcium antagonist, in mice, rats, rabbits and dogs. *Xenobiotica* 18(1):21-8. PMID: 3354229
- Treiber A, Schneider R, Delahaye S, Clozel M (2004). Inhibition of organic anion transporting polypeptide-mediated hepatic uptake is the major determinant in the pharmacokinetic interaction between bosentan and cyclosporin A in the rat. *J Pharmacol Exp Ther.* 308(3):1121-9. PMID: 14617681
- Tsui BC, Feng JD, Buckley SJ, Yeung PK (1994). Pharmacokinetics and metabolism of diltiazem in rats following a single intra-arterial or single oral dose. *Eur J Drug Metab Pharmacokinet.* 19(4):369-73. PMID: 7737239
- Wambaugh, John F., et al. "Toxicokinetic triage for environmental chemicals." *Toxicological Sciences* (2015): 228-237.
- Wang Y, Roy A, Sun L, Lau CE (1999). A double-peak phenomenon in the pharmacokinetics of alprazolam after oral administration. *Drug Metab Dispos.* 27(8):855-9. PMID: 10421610
- Wang X, Lee WY, Or PM, Yeung JH (2010). Pharmacokinetic interaction studies of tanshinones with tolbutamide, a model CYP2C11 probe substrate, using liver microsomes, primary hepatocytes and in vivo in the rat. *Phytomedicine.* 17(3-4):203-11. PMID: 19679455
- Yang SH, Lee MG (2008). Dose-independent pharmacokinetics of ondansetron in rats: contribution of hepatic and intestinal first-pass effects to low bioavailability. *Biopharm Drug Dispos.* 29(7):414-26. PMID: 18697186
- Yeung PK, Alcos A, Tang J (2009). Pharmacokinetics and Hemodynamic Effects of Diltiazem in Rats Following Single vs Multiple Doses In Vivo. *Open Drug Metab J.* 3:56-62.

chem.invivo.PK.summary.data

Summary of published toxicokinetic time course experiments

Description

This data set summarizes the time course data in the chem.invivo.PK.data table. Maximum concentration (C_{max}), time integrated plasma concentration for the duration of treatment (AUC_{treatment}) and extrapolated to zero concentration (AUC_{infinity}) as well as half-life are calculated. Summary values are given for each study and dosage. These data can be used to evaluate toxicokinetic model predictions.

Usage

chem.invivo.PK.summary.data

Format

A data.frame containing 100 rows and 25 columns.

Author(s)

John Wambaugh

Source

Wambaugh et al. 2018 Toxicological Sciences, in press

References

- Aanderud L, Bakke OM (1983). Pharmacokinetics of antipyrine, paracetamol, and morphine in rat at 71 ATA. *Undersea Biomed Res.* 10(3):193-201. PMID: 6636344
- Aasmoe L, Mathiesen M, Sager G (1999). Elimination of methoxyacetic acid and ethoxyacetic acid in rat. *Xenobiotica.* 29(4):417-24. PMID: 10375010
- Ako RA. Pharmacokinetics/pharmacodynamics (PK/PD) of oral diethylstilbestrol (DES) in recurrent prostate cancer patients and of oral dissolving film (ODF)-DES in rats. PhD dissertation, College of Pharmacy, University of Houston, USA, 2011.
- Anadon A, Martinez-Larranaga MR, Fernandez-Cruz ML, Diaz MJ, Fernandez MC, Martinez MA (1996). Toxicokinetics of deltamethrin and its 4'-HO-metabolite in the rat. *Toxicol Appl Pharmacol.* 141(1):8-16. PMID: 8917670
- Binkerd PE, Rowland JM, Nau H, Hendrickx AG (1988). Evaluation of valproic acid (VPA) developmental toxicity and pharmacokinetics in Sprague-Dawley rats. *Fundam Appl Toxicol.* 11(3):485-93. PMID: 3146521
- Boralli VB, Coelho EB, Cerqueira PM, Lanchote VL (2005). Stereoselective analysis of metoprolol and its metabolites in rat plasma with application to oxidative metabolism. *J Chromatogr B Analyt Technol Biomed Life Sci.* 823(2):195-202. PMID: 16029965
- Chan MP, Morisawa S, Nakayama A, Kawamoto Y, Sugimoto M, Yoneda M (2005). Toxicokinetics of 14C-endosulfan in male Sprague-Dawley rats following oral administration of single or repeated doses. *Environ Toxicol.* 20(5):533-41. PMID: 16161119
- Cruz L, Castaneda-Hernandez G, Flores-Murrieta FJ, Garcia-Lopez P, Guizar-Sahagun G (2002). Alteration of phenacetin pharmacokinetics after experimental spinal cord injury. *Proc West Pharmacol Soc.* 45:4-5. PMID: 12434508
- Della Paschoa OE, Mandema JW, Voskuyl RA, Danhof M (1998). Pharmacokinetic-pharmacodynamic modeling of the anticonvulsant and electroencephalogram effects of phenytoin in rats. *J Pharmacol Exp Ther.* 284(2):460-6. PMID: 9454785
- Du B, Li X, Yu Q, A Y, Chen C (2010). Pharmacokinetic comparison of orally disintegrating, beta-cyclodextrin inclusion complex and conventional tablets of nicardipine in rats. *Life Sci J.* 7(2):80-4.
- Farris FF, Dedrick RL, Allen PV, Smith JC (1993). Physiological model for the pharmacokinetics of methyl mercury in the growing rat. *Toxicol Appl Pharmacol.* 119(1):74-90. PMID: 8470126
- Hays SM, Elswick BA, Blumenthal GM, Welsch F, Conolly RB, Gargas ML (2000). Development of a physiologically based pharmacokinetic model of 2-methoxyethanol and 2-methoxyacetic acid disposition in pregnant rats. *Toxicol Appl Pharmacol.* 163(1):67-74. PMID: 10662606
- Igari Y, Sugiyama Y, Awazu S, Hanano M (1982). Comparative physiologically based pharmacokinetics of hexobarbital, phenobarbital and thiopental in the rat. *J Pharmacokinet Biopharm.* 10(1):53-75. PMID: 7069578
- Ito K, Houston JB (2004). Comparison of the use of liver models for predicting drug clearance using in vitro kinetic data from hepatic microsomes and isolated hepatocytes. *Pharm Res.* 21(5):785-92. PMID: 15180335
- Jia L, Wong H, Wang Y, Garza M, Weitman SD (2003). Carbendazim: disposition, cellular permeability, metabolite identification, and pharmacokinetic comparison with its nanoparticle. *J Pharm Sci.* 92(1):161-72. PMID: 12486692

- Kawai R, Mathew D, Tanaka C, Rowland M (1998). Physiologically based pharmacokinetics of cyclosporine A: extension to tissue distribution kinetics in rats and scale-up to human. *J Pharmacol Exp Ther.* 287(2):457-68. PMID: 9808668
- Kim YC, Kang HE, Lee MG (2008). Pharmacokinetics of phenytoin and its metabolite, 4'-HPPH, after intravenous and oral administration of phenytoin to diabetic rats induced by alloxan or streptozotocin. *Biopharm Drug Dispos.* 29(1):51-61. PMID: 18022993
- Kobayashi S, Takai K, Iga T, Hanano M (1991). Pharmacokinetic analysis of the disposition of valproate in pregnant rats. *Drug Metab Dispos.* 19(5):972-6. PMID: 1686245
- Kotegawa T, Laurijssens BE, Von Moltke LL, Cotreau MM, Perloff MD, Venkatakrishnan K, Warrington JS, Granda BW, Harmatz JS, Greenblatt DJ (2002). In vitro, pharmacokinetic, and pharmacodynamic interactions of ketoconazole and midazolam in the rat. *J Pharmacol Exp Ther.* 302(3):1228-37. PMID: 12183684
- Krug AK, Kolde R, Gaspar JA, Rempel E, Balmer NV, Meganathan K, Vojnits K, Baquie M, Waldmann T, Ensenat-Waser R, Jagtap S, Evans RM, Julien S, Peterson H, Zagoura D, Kadereit S, Gerhard D, Sotiriadou I, Heke M, Natarajan K, Henry M, Winkler J, Marchan R, Stoppini L, Bosgra S, Westerhout J, Verwei M, Vilo J, Kortenkamp A, Hescheler J, Hothorn L, Bremer S, van Thriel C, Krause KH, Hengstler JG, Rahnenfuhrer J, Leist M, Sachinidis A (2013). Human embryonic stem cell-derived test systems for developmental neurotoxicity: a transcriptomics approach. *Arch Toxicol.* 87(1):123-43. PMID: 23179753
- Leon-Reyes MR, Castaneda-Hernandez G, Ortiz MI (2009). Pharmacokinetic of diclofenac in the presence and absence of glibenclamide in the rat. *J Pharm Pharm Sci.* 12(3):280-7. PMID: 20067705
- Nagata M, Hidaka M, Sekiya H, Kawano Y, Yamasaki K, Okumura M, Arimori K (2007). Effects of pomegranate juice on human cytochrome P450 2C9 and tolbutamide pharmacokinetics in rats. *Drug Metab Dispos.* 35(2):302-5. PMID: 17132763
- Okiyama M, Ueno K, Ohmori S, Igarashi T, Kitagawa H (1988). Drug interactions between imipramine and benzodiazepines in rats. *J Pharm Sci.* 77(1):56-63. PMID: 2894451
- Pelissier-Alicot AL, Schreiber-Deturmeny E, Simon N, Gantenbein M, Bruguerolle B (2002). Time-of-day dependent pharmacodynamic and pharmacokinetic profiles of caffeine in rats. *Naunyn Schmiedebergs Arch Pharmacol.* 365(4):318-25. PMID: 11919657
- Piersma AH, Bosgra S, van Duursen MB, Hermesen SA, Jonker LR, Kroese ED, van der Linden SC, Man H, Roelofs MJ, Schulpen SH, Schwarz M, Uibel F, van Vugt-Lussenburg BM, Westerhout J, Wolterbeek AP, van der Burg B (2013). Evaluation of an alternative in vitro test battery for detecting reproductive toxicants. *Reprod Toxicol.* 38:53-64. PMID: 23511061
- Pollack GM, Li RC, Ermer JC, Shen DD (1985). Effects of route of administration and repetitive dosing on the disposition kinetics of di(2-ethylhexyl) phthalate and its mono-de-esterified metabolite in rats. *Toxicol Appl Pharmacol.* Jun 30;79(2):246-56. PMID: 4002226
- Saadaddin A, Torres-Molina F, Carcel-Trullols J, Araico A, Peris JE (2004). Pharmacokinetics of the time-dependent elimination of all-trans-retinoic acid in rats. *AAPS J.* 6(1):1-9. PMID: 18465253
- Satterwhite JH, Boudinot FD (1991). Effects of age and dose on the pharmacokinetics of ibuprofen in the rat. *Drug Metab Dispos.* 19(1):61-7. PMID: 1673423
- Szymura-Oleksiak J, Panas M, Chrusciel W (1983). Pharmacokinetics of imipramine after single and multiple intravenous administration in rats. *Pol J Pharmacol Pharm.* 35(2):151-7. PMID: 6622297
- Tanaka C, Kawai R, Rowland M (2000). Dose-dependent pharmacokinetics of cyclosporin A in rats: events in tissues. *Drug Metab Dispos.* 28(5):582-9. PMID: 10772639

- Timchalk C, Nolan RJ, Mendrala AL, Dittenber DA, Brzak KA, Mattsson JL (2002). A Physiologically based pharmacokinetic and pharmacodynamic (PBPK/PD) model for the organophosphate insecticide chlorpyrifos in rats and humans. *Toxicol Sci.* Mar;66(1):34-53. PMID: 11861971
- Tokuma Y, Sekiguchi M, Niwa T, Noguchi H (1988). Pharmacokinetics of nilvadipine, a new dihydropyridine calcium antagonist, in mice, rats, rabbits and dogs. *Xenobiotica* 18(1):21-8. PMID: 3354229
- Treiber A, Schneider R, Delahaye S, Clozel M (2004). Inhibition of organic anion transporting polypeptide-mediated hepatic uptake is the major determinant in the pharmacokinetic interaction between bosentan and cyclosporin A in the rat. *J Pharmacol Exp Ther.* 308(3):1121-9. PMID: 14617681
- Tsui BC, Feng JD, Buckley SJ, Yeung PK (1994). Pharmacokinetics and metabolism of diltiazem in rats following a single intra-arterial or single oral dose. *Eur J Drug Metab Pharmacokinet.* 19(4):369-73. PMID: 7737239
- Wambaugh, John F., et al. "Toxicokinetic triage for environmental chemicals." *Toxicological Sciences* (2015): 228-237.
- Wang Y, Roy A, Sun L, Lau CE (1999). A double-peak phenomenon in the pharmacokinetics of alprazolam after oral administration. *Drug Metab Dispos.* 27(8):855-9. PMID: 10421610
- Wang X, Lee WY, Or PM, Yeung JH (2010). Pharmacokinetic interaction studies of tanshinones with tolbutamide, a model CYP2C11 probe substrate, using liver microsomes, primary hepatocytes and in vivo in the rat. *Phytomedicine.* 17(3-4):203-11. PMID: 19679455
- Yang SH, Lee MG (2008). Dose-independent pharmacokinetics of ondansetron in rats: contribution of hepatic and intestinal first-pass effects to low bioavailability. *Biopharm Drug Dispos.* 29(7):414-26. PMID: 18697186
- Yeung PK, Alcos A, Tang J (2009). Pharmacokinetics and Hemodynamic Effects of Diltiazem in Rats Following Single vs Multiple Doses In Vivo. *Open Drug Metab J.* 3:56-62.

chem.lists

Chemical membership in different research projects

Description

A static list of lists identifying chemical membership in different research projects. While it is our intent to keep these lists up-to-date, the information here is only for convenience and should not be considered to be definitive.

Usage

chem.lists

Format

A list containing ten lists.

Author(s)

John Wambaugh

References

Bucher, J. R. (2008). Guest Editorial: NTP: New Initiatives, New Alignment. Environ Health Perspect 116(1).

Judson, R. S., Houck, K. A., Kavlock, R. J., Knudsen, T. B., Martin, M. T., Mortensen, H. M., Reif, D. M., Rotroff, D. M., Shah, I., Richard, A. M. and Dix, D. J. (2010). In Vitro Screening of Environmental Chemicals for Targeted Testing Prioritization: The ToxCast Project. Environmental Health Perspectives 118(4), 485-492.

Wambaugh, J. F., Wang, A., Dionisio, K. L., Frame, A., Egeghy, P., Judson, R. and Setzer, R. W. (2014). High Throughput Heuristics for Prioritizing Human Exposure to Environmental Chemicals. Environmental Science & Technology, 10.1021/es503583j.

CDC (2014). National Health and Nutrition Examination Survey. Available at: <https://www.cdc.gov/nchs/nhanes.htm>.

chem.physical_and_invitro.data

Physico-chemical properties and in vitro measurements for toxicokinetics

Description

This data set contains the necessary information to make basic, high-throughput toxicokinetic (HTTK) predictions for compounds, including Funbound.plasma, molecular weight (g/mol), logP, logMA (membrane affinity), intrinsic clearance(uL/min/10⁶ cells), and pKa. These data have been compiled from multiple sources, and can be used to parameterize a variety of toxicokinetic models. See variable EPA.ref for information on the reference EPA.

Usage

chem.physical_and_invitro.data

Format

A data.frame containing 9411 rows and 54 columns.

Column Name	Description	Units
Compound	The preferred name of the chemical compound	none
CAS	The preferred Chemical Abstracts Service Registry Number	none
CAS.Checksum	A logical indicating whether the CAS number is valid	none
DTXSID	DSSTox Structure ID (http://comptox.epa.gov/dashboard)	none
Formula	The proportions of atoms within the chemical compound	none
SMILES.desalt	The simplified molecular-input line-entry system structure	none
All.Compound.Names	All names of the chemical as they occurred in the data	none
logHenry	The log10 Henry's law constant	log10(atmospheres)
logHenry.Reference	Reference for Henry's law constant	
logP	The log10 octanol:water partition coefficient (PC)	log10 unitless ratio
logP.Reference	Reference for logPow	
logPwa	The log10 water:air PC	log10 unitless ratio
logPwa.Reference	Reference for logPwa	
logMA	The log10 phospholipid:water PC or "Membrane affinity"	unitless ratio
logMA.Reference	Reference for membrane affinity	
#' logWSol	The log10 water solubility	log10(mole/L)

logWSol.Reference	Reference for logWSol	
MP	The chemical compound melting point	degrees Celsius
MP.Reference	Reference for melting point	
MW	The chemical compound molecular weight	g/mol
MW.Reference	Reference for molecular weight	
pKa_Accept	The hydrogen acceptor equilibria concentrations	logarithm
pKa_Accept.Reference	Reference for pKa_Accept	
pKa_Donor	The hydrogen acceptor equilibria concentrations	logarithm
pKa_Donor.Reference	Reference for pKa_Donor	
All.Species	All species for which data were available	none
DTXSID.Reference	Reference for DTXSID	
Formula.Reference	Reference for chemical formula	
[SPECIES].Clint	(Primary hepatocyte suspension) intrinsic hepatic clearance	uL/min/10 ⁶ hepa
[SPECIES].Clint.pValue	Probability that there is no clearance observed.	none
[SPECIES].Clint.pValue.Ref	Reference for Clint pValue	
[SPECIES].Clint.Reference	Reference for Clint	
[SPECIES].Fgutabs	Fraction of chemical absorbed from the gut	unitless fraction
[SPECIES].Fgutabs.Reference	Reference for Fgutabs	
[SPECIES].Funbound.plasma	Chemical fraction unbound in presence of plasma proteins	unitless fraction
[SPECIES].Funbound.plasma.Ref	Reference for Funbound.plasma	
[SPECIES].Rblood2plasma	Chemical concentration blood to plasma ratio	unitless ratio
[SPECIES].Rblood2plasma.Ref	Reference for Rblood2plasma	
SMILES.desalt.Reference"	Reference for SMILES structure	
Chemical.Class	All classes to which the chemical has been assigned	

Details

In some cases the rapid equilibrium dialysis method (Waters et al., 2008) fails to yield detectable concentrations for the free fraction of chemical. In those cases we assume the compound is highly bound (that is, *Fup* approaches zero). For some calculations (for example, steady-state plasma concentration) there is precedent (Rotroff et al., 2010) for using half the average limit of detection, that is 0.005. We do not recommend using other models where quantities like partition coefficients must be predicted using *Fup*. We also do not recommend including the value 0.005 in training sets for *Fup* predictive models.

Note that in some cases the **Funbound.plasma** and the **intrinsic clearance** are provided as a series of numbers separated by commas. These values are the result of Bayesian analysis and characterize a distribution: the first value is the median of the distribution, while the second and third values are the lower and upper 95th percentile (that is quantile 2.5 and 97.5) respectively. For intrinsic clearance a fourth value indicating a p-value for a decrease is provided. Typically 4000 samples were used for the Bayesian analysis, such that a p-value of "0" is equivalent to "<0.00025". See Wambaugh et al. (2019) for more details.

Any one chemical compound *may have multiple ionization equilibria* (see Strobe et al., 2018) may both for donating or accepting a proton (and therefore changing charge state). If there are multiple equilibria of the same type (donor/acceptor) they are concatenated by commas.

All species-specific information is initially from experimental measurements. The functions [load_sipes2017](#), [load_pradeep2020](#), and [load_dawson2021](#) may be used to add in silico, structure-based predictions for many thousands of additional compounds to this table.

Author(s)

John Wambaugh

Source

Wambaugh, John F., et al. "Toxicokinetic triage for environmental chemicals." *Toxicological Sciences* (2015): 228-237.

References

CompTox Chemicals Dashboard (<http://comptox.epa.gov/dashboard>)

EPI Suite, <https://www.epa.gov/opptintr/exposure/pubs/episuite.htm>

Hilal, S., Karickhoff, S. and Carreira, L. (1995). A rigorous test for SPARC's chemical reactivity models: Estimation of more than 4300 ionization pKas. *Quantitative Structure-Activity Relationships* 14(4), 348-355.

Honda, G. S., Pearce, R. G., Pham, L. L., Setzer, R. W., Wetmore, B. A., Sipes, N. S., ... & Wambaugh, J. F. (2019). Using the concordance of in vitro and in vivo data to evaluate extrapolation assumptions. *PloS one*, 14(5), e0217564.

Ito, K. and Houston, J. B. (2004). Comparison of the use of liver models for predicting drug clearance using in vitro kinetic data from hepatic microsomes and isolated hepatocytes. *Pharm Res* 21(5), 785-92.

Jones, O. A., Voulvoulis, N. and Lester, J. N. (2002). Aquatic environmental assessment of the top 25 English prescription pharmaceuticals. *Water research* 36(20), 5013-22.

Lau, Y. Y., Sapidou, E., Cui, X., White, R. E. and Cheng, K. C. (2002). Development of a novel in vitro model to predict hepatic clearance using fresh, cryopreserved, and sandwich-cultured hepatocytes. *Drug Metabolism and Disposition* 30(12), 1446-54.

Linakis, M. W., Sayre, R. R., Pearce, R. G., Sfeir, M. A., Sipes, N. S., Pangburn, H. A., ... & Wambaugh, J. F. (2020). Development and evaluation of a high-throughput inhalation model for organic chemicals. *Journal of Exposure Science & Environmental Epidemiology*, 1-12.

Lombardo, F., Berellini, G., & Obach, R. S. (2018). Trend analysis of a database of intravenous pharmacokinetic parameters in humans for 1352 drug compounds. *Drug Metabolism and Disposition*, 46(11), 1466-1477.

McGinnity, D. F., Soars, M. G., Urbanowicz, R. A. and Riley, R. J. (2004). Evaluation of fresh and cryopreserved hepatocytes as in vitro drug metabolism tools for the prediction of metabolic clearance. *Drug Metabolism and Disposition* 32(11), 1247-53, 10.1124/dmd.104.000026.

Naritomi, Y., Terashita, S., Kagayama, A. and Sugiyama, Y. (2003). Utility of Hepatocytes in Predicting Drug Metabolism: Comparison of Hepatic Intrinsic Clearance in Rats and Humans in Vivo and in Vitro. *Drug Metabolism and Disposition* 31(5), 580-588, 10.1124/dmd.31.5.580.

Obach, R. S. (1999). Prediction of human clearance of twenty-nine drugs from hepatic microsomal intrinsic clearance data: An examination of in vitro half-life approach and nonspecific binding to microsomes. *Drug Metabolism and Disposition* 27(11), 1350-9.

Paini, Alicia; Cole, Thomas; Meinero, Maria; Carpi, Donatella; Deceuninck, Pierre; Macko, Peter; Palosaari, Taina; Sund, Jukka; Worth, Andrew; Whelan, Maurice (2020): EURL ECVAM in vitro hepatocyte clearance and blood plasma protein binding dataset for 77 chemicals. European Commission, Joint Research Centre (JRC) [Dataset] PID: <https://data.europa.eu/89h/a2ff867f-db80-4acf-8e5c-e45502713bee>

Paixao, P., Gouveia, L. F., & Morais, J. A. (2012). Prediction of the human oral bioavailability by using in vitro and in silico drug related parameters in a physiologically based absorption model. *International journal of pharmaceutics*, 429(1), 84-98.

Pirovano, Alessandra, et al. "QSARs for estimating intrinsic hepatic clearance of organic chemicals in humans." *Environmental toxicology and pharmacology* 42 (2016): 190-197.

Schmitt, W. (2008). General approach for the calculation of tissue to plasma partition coefficients. *Toxicology in vitro : an international journal published in association with BIBRA* 22(2), 457-67, 10.1016/j.tiv.2007.09.010.

Shibata, Y., Takahashi, H., Chiba, M. and Ishii, Y. (2002). Prediction of Hepatic Clearance and Availability by Cryopreserved Human Hepatocytes: An Application of Serum Incubation Method. *Drug Metabolism and Disposition* 30(8), 892-896, 10.1124/dmd.30.8.892.

Tonnelier, A., Coecke, S. and Zaldivar, J.-M. (2012). Screening of chemicals for human bioaccumulative potential with a physiologically based toxicokinetic model. *Archives of Toxicology* 86(3), 393-403, 10.1007/s00204-011-0768-0.

Uchimura, Takahide, et al. "Prediction of human blood-to-plasma drug concentration ratio." *Biopharmaceutics & drug disposition* 31.5-6 (2010): 286-297.

Wambaugh, J. F., Wetmore, B. A., Ring, C. L., Nicolas, C. I., Pearce, R. G., Honda, G. S., ... & Badrinarayanan, A. (2019). Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization. *Toxicological Sciences*, 172(2), 235-251.

Wetmore, B. A., Wambaugh, J. F., Ferguson, S. S., Sochaski, M. A., Rotroff, D. M., Freeman, K., Clewell, H. J., 3rd, Dix, D. J., Andersen, M. E., Houck, K. A., Allen, B., Judson, R. S., Singh, R., Kavlock, R. J., Richard, A. M. and Thomas, R. S. (2012). Integration of dosimetry, exposure, and high-throughput screening data in chemical toxicity assessment. *Toxicological sciences : an official journal of the Society of Toxicology* 125(1), 157-74, 10.1093/toxsci/kfr254.

Wetmore, B. A., Wambaugh, J. F., Ferguson, S. S., Li, L., Clewell, H. J., Judson, R. S., Freeman, K., Bao, W., Sochaski, M. A., Chu, T.-M., Black, M. B., Healy, E., Allen, B., Andersen, M. E., Wolfinger, R. D. and Thomas, R. S. (2013). Relative Impact of Incorporating Pharmacokinetics on Predicting In Vivo Hazard and Mode of Action from High-Throughput In Vitro Toxicity Assays. *Toxicological Sciences* 132(2), 327-346, 10.1093/toxsci/kft012.

Wetmore, B. A., Wambaugh, J. F., Allen, B., Ferguson, S. S., Sochaski, M. A., Setzer, R. W., Houck, K. A., Strobe, C. L., Cantwell, K., Judson, R. S., LeCluyse, E., Clewell, H.J. III, Thomas, R.S., and Andersen, M. E. (2015). "Incorporating High-Throughput Exposure Predictions with Dosimetry-Adjusted In Vitro Bioactivity to Inform Chemical Toxicity Testing" *Toxicological Sciences*, kfv171.

ckd_epi_eq

CKD-EPI equation for GFR.

Description

Predict GFR from serum creatinine, gender, and age.

Usage

```
ckd_epi_eq(scr, gender, reth, age_years, ckd_epi_race_coeff = FALSE)
```

Arguments

scr	Vector of serum creatinine values in mg/dL.
gender	Vector of genders (either 'Male' or 'Female').
reth	Vector of races/ethnicities. Not used unless ckd_epi_race_coeff is TRUE.
age_years	Vector of ages in years.
ckd_epi_race_coeff	Whether to use the "race coefficient" in the CKD-EPI equation. Default is FALSE.

Details

From Levey AS, Stevens LA, Schmid CH, Zhang YL, Castro AF, Feldman HI, et al. A new equation to estimate glomerular filtration rate. *Ann Intern Med* 2009; 150(9):604-612. doi:10.7326/0003-4819-150-9-200905050-00006

Value

Vector of GFR values in mL/min/1.73m².

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

concentration_data_Linakis2020

Concentration data involved in Linakis 2020 vignette analysis.

Description

Concentration data involved in Linakis 2020 vignette analysis.

Usage

concentration_data_Linakis2020

Format

A data.frame containing x rows and y columns.

Author(s)

Matt Linakis

Source

Matt Linakis

References

DSStox database ([https:// www.epa.gov/ncct/dsstox](https://www.epa.gov/ncct/dsstox))

convert_httkpop_1comp	<i>Converts HHTK-Pop physiology into parameters relevant to the one compartment model</i>
-----------------------	---

Description

Converts HHTK-Pop physiology into parameters relevant to the one compartment model

Usage

```
convert_httkpop_1comp(parameters.dt, httkpop.dt, ...)
```

Arguments

parameters.dt	Data table returned by create_mc_samples
httkpop.dt	Data table returned by httkpop_generate
...	Additional arguments passed to propagate_invitrouv_1comp

Value

A data.table whose columns are the parameters of the HHTK model specified in model1.

Author(s)

Caroline Ring, John Wambaugh, and Greg Honda

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

convert_solve_x	<i>convert_solve_x</i>
-----------------	------------------------

Description

This function is designed to convert compartment values estimated from one of the HHTK models (e.g. "1compartment") using the solve_model function. It takes the HHTK model output matrix, model name, desired output units, and compound information to perform the conversion default model units to user specified units.

Usage

```

convert_solve_x(
  model.output.mat,
  model = NULL,
  output.units = NULL,
  MW = NULL,
  vol = NULL,
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  parameters = NULL,
  monitor.vars = NULL,
  suppress.messages = FALSE,
  verbose = FALSE,
  ...
)

```

Arguments

model.output.mat	Matrix of results from HTTK solve_model function.
model	Specified model to use in simulation: "pbtk", "3compartment", "3compartmentss", "1compartment", "schmitt", ...
output.units	Output units of interest for the compiled components. Defaults to NULL, and will provide values in model units if unspecified.
MW	Molecular weight of substance of interest in g/mole
vol	Volume for the target tissue of interest in liters (L). NOTE: Volume should not be in units of per BW, i.e. "kg".
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
chem.name	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID . (http://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs.
parameters	A set of model parameters, especially a set that includes MW (molecular weight) for our conversions.
monitor.vars	A vector of character strings indicating the model component variables to retain in the conversion factor table (assuming suppress.messages == FALSE). It should also be noted this option does NOT exclude columns from the input matrix provided in the 'model.output.mat' parameter. (Default is NULL, i.e. conversion factors for all model components are included in the reporting matrix.)
suppress.messages	Whether or not the output messages are suppressed. (Default is FALSE, i.e. show messages.)
verbose	Whether or not to display the full conversion factor table. (Default is FALSE, i.e. only include rows where the conversion factor is 1.)
...	Other parameters that can be passed to convert_units, e.g. temperature and compound state. See details in convert_units .

Details

The function can be used to convert all compartments to a single unit, only units for a single model compartment, or units for a set of model compartments.

More details on the unit conversion can be found in the documentation for [convert_units](#).

Value

'new.output.matrix' A matrix with a column for time (in days), each compartment, and the area under the curve (AUC) and a row for each time point. The compartment and AUC columns are converted from model specified units to user specified units.

'output.units.vector' A vector of character strings providing the model compartments and their corresponding units after `convert_solve_x`.

Author(s)

Sarah E. Davidson

See Also

`convert_units`

Examples

```
output.mat <- solve_1comp(dt xsid = "DTXSID0020573")
new.output.mat <- convert_solve_x(output.units = "mg",
                                  model.output.mat = output.mat,
                                  model = "1compartment",
                                  dt xsid = "DTXSID0020573")
```

convert_units

convert_units

Description

This function is designed to accept input units, output units, and the molecular weight (MW) of a substance of interest to then use a table lookup to return a scaling factor that can be readily applied for the intended conversion. It can also take chemical identifiers in the place of a specified molecular weight value to retrieve that value for its own use.

Usage

```
convert_units(
  input.units = NULL,
  output.units = NULL,
  MW = NULL,
  vol = NULL,
  chem.cas = NULL,
  chem.name = NULL,
  dt xsid = NULL,
  parameters = NULL,
```

```

    temp = 25,
    state = "liquid"
)

```

Arguments

input.units	Assigned input units of interest
output.units	Desired output units
MW	Molecular weight of substance of interest in g/mole
vol	Volume for the target tissue of interest in liters (L). NOTE: Volume should not be in units of per BW, i.e. "kg".
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
chem.name	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (http://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
parameters	A set of model parameters, especially a set that includes MW (molecular weight) for our conversions
temp	Temperature for conversions (default = 25 degrees C)
state	Chemical state (gas or default liquid)

Details

If input or output units not contained in the table are queried, it gives a corresponding error message. It gives a warning message about the handling of 'ppmv,' as the function is only set up to convert between ppmv and mass-based units (like mg/m³ or umol/L) in the context of ideal gases.

convert_units is not directly configured to accept and convert units based on BW, like mg/kg. For this purpose, see [scale_dosing](#).

The function supports a limited set of most relevant units across toxicological models, currently including umol, uM, mg, mg/L, mg/m³ or umol/L), and in the context of gases assumed to be ideal, ppmv.

Andersen and Clewell's Rules of PBPK Modeling:

- 1Check Your Units
- 2Check Your Units
- 3Check Mass Balance

Author(s)

Mark Sfeir, John Wambaugh, and Sarah E. Davidson

Examples

```

# MW BPA is 228.29 g/mol
# 1 mg/L -> 1/228.29*1000 = 4.38 uM
convert_units("mg/L", "uM", chem.cas="80-05-7")

# MW Diclofenac is 296.148 g/mol
# 1 uM -> 296.148/1000 = 0.296
convert_units("uM", "mg/L", chem.name="diclofenac")

```

```

convert_units("uM", "ppmv", chem.name="styrene")

# Compare with https://www3.epa.gov/ceampubl/learn2model/part-two/onsite/ia_unit_conversion.html
# 1 ug/L Toluene -> 0.263 ppmv
convert_units("ug/L", "ppmv", chem.name="toluene")
# 1 ppmv Toluene, 0.0038 mg/L
convert_units("ppmv", "mg/L", chem.name="toluene")

MW_pyrene <- get_physchem_param(param='MW', chem.name='pyrene')
conversion_factor <- convert_units(input.units='mg/L', output.units='uM',
  MW=MW_pyrene)

```

create_mc_samples

Create a data table of draws of parameter values for Monte Carlo

Description

This function creates a data table of draws of parameter values for use with Monte Carlo methods

Usage

```

create_mc_samples(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  parameters = NULL,
  samples = 1000,
  species = "Human",
  suppress.messages = FALSE,
  model = "3compartmentss",
  httkpop = TRUE,
  invitrouv = TRUE,
  calcrb2p = TRUE,
  censored.params = list(),
  vary.params = list(),
  return.samples = FALSE,
  tissue = NULL,
  httkpop.dt = NULL,
  invitro.mc.arg.list = list(adjusted.funbound.plasma = TRUE, poormetab = TRUE,
    fup.censored.dist = FALSE, fup.lod = 0.01, fup.meas.cv = 0.4, clint.meas.cv = 0.3,
    fup.pop.cv = 0.3, clint.pop.cv = 0.3),
  httkpop.generate.arg.list = list(method = "direct resampling", gendernum = NULL,
    agelim_years = NULL, agelim_months = NULL, weight_category = c("Underweight",
    "Normal", "Overweight", "Obese"), gfr_category = c("Normal", "Kidney Disease",
    "Kidney Failure"), reths = c("Mexican American", "Other Hispanic",
    "Non-Hispanic White", "Non-Hispanic Black", "Other")),
  convert.httkpop.arg.list = list(),
  propagate.invitrouv.arg.list = list(),
  parameterize.arg.list = list(restrictive.clearance = TRUE, default.to.human = FALSE,
    clint.pvalue.threshold = 0.05, regression = TRUE)
)

```

Arguments

chem.cas	Chemical Abstract Services Registry Number (CAS-RN) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
chem.name	Chemical name (spaces and capitalization ignored) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXSIDs
parameters	Parameters from the appropriate parameterization function for the model indicated by argument model
samples	Number of samples generated in calculating quantiles.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human"). Species must be set to "Human" to run httkpop model.
suppress.messages	Whether or not to suppress output message.
model	Model used in calculation: 'pbtk' for the multiple compartment model, '3compartment' for the three compartment model, '3compartmentss' for the three compartment steady state model, and '1compartment' for one compartment model. This only applies when httkpop=TRUE and species="Human", otherwise '3compartmentss' is used.
httkpop	Whether or not to use the Ring et al. (2017) "httkpop" population generator. Species must be 'Human'.
invitrouv	Logical to indicate whether to include in vitro parameters such as intrinsic hepatic clearance rate and fraction unbound in plasma in uncertainty and variability analysis
calcrb2p	Logical determining whether or not to recalculate the chemical ratio of blood to plasma
censored.params	The parameters listed in censored.params are sampled from a normal distribution that is censored for values less than the limit of detection (specified separately for each parameter). This argument should be a list of sub-lists. Each sublist is named for a parameter in "parameters" and contains two elements: "CV" (coefficient of variation) and "LOD" (limit of detection, below which parameter values are censored. New values are sampled with mean equal to the value in "parameters" and standard deviation equal to the mean times the CV. Censored values are sampled on a uniform distribution between 0 and the limit of detection. Not used with httkpop model.
vary.params	The parameters listed in vary.params are sampled from a normal distribution that is truncated at zero. This argument should be a list of coefficients of variation (CV) for the normal distribution. Each entry in the list is named for a parameter in "parameters". New values are sampled with mean equal to the value in "parameters" and standard deviation equal to the mean times the CV. Not used with httkpop model.
return.samples	Whether or not to return the vector containing the samples from the simulation instead of the selected quantile.
tissue	Desired steady state tissue concentration.
httkpop.dt	A data table generated by httkpop_generate . This defaults to NULL, in which case httkpop_generate is called to generate this table.

`invitro.mc.arg.list`
Additional parameters passed to `invitro_mc`.
`httkpop.generate.arg.list`
Additional parameters passed to `httkpop_generate`.
`convert.httkpop.arg.list`
Additional parameters passed to the `convert_httkpop_*` function for the model.
`propagate.invitrouv.arg.list`
Additional parameters passed to model's associated in vitro uncertainty and variability propagation function
`parameterize.arg.list`
Additional parameters passed to the `parameterize_*` function for the model.

Value

A data table where each column corresponds to parameters needed for the specified model and each row represents a different Monte Carlo sample of parameter values.

Author(s)

Caroline Ring, Robert Pearce, and John Wambaugh

References

Wambaugh, John F., et al. "Toxicokinetic triage for environmental chemicals." *Toxicological Sciences* 147.1 (2015): 55-67.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment international* 106 (2017): 105-118.

Examples

```
sample_set = create_mc_samples(chem.name = 'bisphenol a')
```

dawson2021

Dawson et al. 2021 data

Description

This table includes QSAR (Random Forest) model predicted values for unbound fraction plasma protein (fup) and intrinsic hepatic clearance (clint) for a subset of chemicals in the Tox21 library (see <https://www.epa.gov/chemical-research/toxicology-testing-21st-century-tox21>).

Usage

```
dawson2021
```

Format

```
data.frame
```

Details

Predictions were made with a set of Random Forest QSAR models, as reported in Dawson et al. (2021).

Author(s)

Daniel E. Dawson

Source

Dawson et al. 2021 Random Forest QSAR Model

References

Dawson, Daniel E. et al. "Designing QSARs for parameters of high-throughput toxicokinetic models using open-source descriptors." *Environmental Science & Technology*____. (2021):____.

EPA.ref

Reference for EPA Physico-Chemical Data

Description

The physico-chemical data in the chem.phys_and_invitro.data table are obtained from EPA's Comptox Chemicals dashboard. This variable indicates the date the Dashboard was accessed.

Usage

EPA.ref

Format

An object of class character of length 1.

Author(s)

John Wambaugh

Source

<https://comptox.epa.gov/dashboard>

estimate_gfr	<i>Predict GFR.</i>
--------------	---------------------

Description

Predict GFR using CKD-EPI equation (for adults) or BSA-based equation (for children).

Usage

```
estimate_gfr(gfrtmp.dt, gfr_resid_var = TRUE, ckd_epi_race_coeff = FALSE)
```

Arguments

gfrtmp.dt	A data.table with columns gender, reth, age_years, age_months, BSA_adj, serum_creat.
gfr_resid_var	Logical value indicating whether or not to include residual variability when generating GFR values. (Default is TRUE.)
ckd_epi_race_coeff	Logical value indicating whether or not to use the "race coefficient" from the CKD-EPI equation when estimating GFR values. (Default is FALSE.)

Details

Add residual variability based on reported residuals for each equation.

Value

The same data.table with a gfr_est column added, containing estimated GFR values.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

estimate_gfr_ped	<i>Predict GFR in children.</i>
------------------	---------------------------------

Description

BSA-based equation from Johnson et al. 2006, Clin Pharmacokinet 45(9) 931-56. Used in Wetmore et al. 2014.

Usage

```
estimate_gfr_ped(BSA)
```

Arguments

BSA Vector of body surface areas in m².

Value

Vector of GFRs in mL/min/1.73m².

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

estimate_hematocrit *Predict hematocrit using smoothing spline.*

Description

Using precalculated smoothing splines on NHANES log hematocrit vs. age in months (and KDE residuals) by gender and race/ethnicity, generate hematocrit values for individuals specified by age, gender, and race/ethnicity.

Usage

```
estimate_hematocrit(hcttmp_dt)
```

Arguments

hcttmp_dt A data.table with columns age_years, age_months, gender, reth.

Value

The same data.table with a hematocrit column added.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

export_pbtjk_jarnac	<i>Export model to jarnac.</i>
---------------------	--------------------------------

Description

This function exports the multiple compartment PBTK model to a jarnac file.

Usage

```
export_pbtjk_jarnac(  
  chem.cas = NULL,  
  chem.name = NULL,  
  species = "Human",  
  initial.amounts = list(Agutlumen = 0),  
  filename = "default.jan",  
  digits = 4  
)
```

Arguments

chem.cas	Either the chemical name or CAS number must be specified.
chem.name	Either the chemical name or CAS number must be specified.
species	Species desired (either "Rat", "Rabbit", "Dog", or default "Human").
initial.amounts	Must specify initial amounts in units of choice.
filename	The name of the jarnac file containing the model.
digits	Desired number of decimal places to round the parameters.

Details

Compartments to enter into the initial.amounts list includes Agutlumen, Aart, Aven, Alung, Agut, Aliver, Akidney, and Arest.

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

Text containing a Jarnac language version of the PBTK model.

Author(s)

Robert Pearce

Examples

```
export_pbtjk_jarnac(chem.name='Nicotine',initial.amounts=list(Agutlumen=1),filename='PBTKmodel.jan')
```

export_pbt_k_sbml	<i>Export model to sbml.</i>
-------------------	------------------------------

Description

This function exports the multiple compartment PBTK model to an sbml file.

Usage

```
export_pbt_k_sbml(
  chem.cas = NULL,
  chem.name = NULL,
  species = "Human",
  initial.amounts = list(Agutlumen = 0),
  filename = "default.xml",
  digits = 4
)
```

Arguments

chem.cas	Either the chemical name or CAS number must be specified.
chem.name	Either the chemical name or CAS number must be specified.
species	Species desired (either "Rat", "Rabbit", "Dog", or default "Human").
initial.amounts	Must specify initial amounts in units of choice.
filename	The name of the jarnac file containing the model.
digits	Desired number of decimal places to round the parameters.

Details

Compartments to enter into the initial.amounts list includes Agutlumen, Aart, Aven, Alung, Agut, Aliver, Akidney, and Arest.

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

Text describing the PBTK model in SBML.

Author(s)

Robert Pearce

Examples

```
export_pbt_k_sbml(chem.name='Nicotine',initial.amounts=list(Agutlumen=1),filename='PBTKmodel.xml')
```

fetalpcs

*Fetal Partition Coefficients***Description**

Partition coefficients were measured for tissues, including placenta, in vitro by Csanady et al. (2002) for Bisphenol A and Diadzen. Curley et al. (1969) measured the concentration of a variety of pesticides in the cord blood of newborns and in the tissues of infants that were stillborn.

Usage

fetalpcs

Format

data.frame

Details

Three of the chemicals studied by Curley et al. (1969) were modeled by Weijs et al. (2013) using the same partition coefficients for mother and fetus. The values used represented "prior knowledge" summarizing the available literature.

Source

Kapraun et al. 2021 (submitted)

References

Csanady G, Oberste-Frielinghaus H, Semder B, Baur C, Schneider K, Filser J (2002). "Distribution and unspecific protein binding of the xenoestrogens bisphenol A and daidzein." *Archives of toxicology*, **76**(5-6), 299–305. Curley A, Copeland MF, Kimbrough RD (1969). "Chlorinated hydrocarbon insecticides in organs of stillborn and blood of newborn babies." *Archives of Environmental Health: An International Journal*, **19**(5), 628–632. Weijs L, Yang RS, Das K, Covaci A, Blust R (2013). "Application of Bayesian population physiologically based pharmacokinetic (PBPK) modeling and Markov chain Monte Carlo simulations to pesticide kinetics studies in protected marine mammals: DDT, DDE, and DDD in harbor porpoises." *Environmental science & technology*, **47**(9), 4365–4374.

Frank2018invivo

*Literature In Vivo Data on Doses Causing Neurological Effects***Description**

Studies were selected from Table 1 in Mundy et al., 2015, as the studies in that publication were cited as examples of compounds with evidence for developmental neurotoxicity. There were sufficient in vitro toxicokinetic data available for this package for only 6 of the 42 chemicals.

Usage

Frank2018invivo

Format

A data.frame containing 14 rows and 16 columns.

Author(s)

Timothy J. Shafer

References

Frank, Christopher L., et al. "Defining toxicological tipping points in neuronal network development." *Toxicology and Applied Pharmacology* 354 (2018): 81-93.

Mundy, William R., et al. "Expanding the test set: Chemicals with potential to disrupt mammalian brain development." *Neurotoxicology and Teratology* 52 (2015): 25-35.

gen_age_height_weight *Generate ages, heights, and weights for a virtual population using the virtual-individuals method.*

Description

Generate ages, heights, and weights for a virtual population using the virtual-individuals method.

Usage

```
gen_age_height_weight(
  nsamp = NULL,
  gendernum = NULL,
  reths,
  weight_category,
  agelim_years,
  agelim_months
)
```

Arguments

nsamp	The desired number of individuals in the virtual population. nsamp need not be provided if gendernum is provided.
gendernum	Optional: A named list giving the numbers of male and female individuals to include in the population, e.g. <code>list(Male=100,Female=100)</code> . Default is NULL, meaning both males and females are included, in their proportions in the NHANES data. If both nsamp and gendernum are provided, they must agree (i.e., nsamp must be the sum of gendernum).
reths	Optional: a character vector giving the races/ethnicities to include in the population. Default is <code>c('Mexican American', 'Other Hispanic', 'Non-Hispanic White', 'Non-Hispanic Black', 'Other')</code> , to include all races and ethnicities in their proportions in the NHANES data. User-supplied vector must contain one or more of these strings.
weight_category	Optional: The weight categories to include in the population. Default is <code>c('Underweight', 'Normal', 'Overweight', 'Obese')</code> . User-supplied vector must contain one or more of these strings.

- `agelim_years` Optional: A two-element numeric vector giving the minimum and maximum ages (in years) to include in the population. Default is `c(0,79)`. If `agelim_years` is provided and `agelim_months` is not, `agelim_years` will override the default value of `agelim_months`.
- `agelim_months` Optional: A two-element numeric vector giving the minimum and maximum ages (in months) to include in the population. Default is `c(0, 959)`, equivalent to the default `agelim_years`. If `agelim_months` is provided and `agelim_years` is not, `agelim_months` will override the default values of `agelim_years`.

Value

A `data.table` containing variables

`gender` Gender of each virtual individual

`reth` Race/ethnicity of each virtual individual

`age_months` Age in months of each virtual individual

`age_years` Age in years of each virtual individual

`weight` Body weight in kg of each virtual individual

`height` Height in cm of each virtual individual

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

`importFrom survey svymean`

<code>gen_height_weight</code>	<i>Generate heights and weights for a virtual population.</i>
--------------------------------	---

Description

Generate heights and weights for a virtual population.

Usage

```
gen_height_weight(hbw_dt)
```

Arguments

`hbw_dt` A `data.table` describing the virtual population by race, gender, and age (in years and months). Must have variables `gender`, `reth`, `age`, and `age_years`.

Value

The same `data.table` with two new variables added: `weight` and `height`. Respectively, these give individual body weights in kg, and individual heights in cm.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

gen_serum_creatinine *Predict GFR.*

Description

Predict serum creatinine using smoothing splines and kernel density estimates of residual variability

Usage

```
gen_serum_creatinine(serumcreat.dt)
```

Arguments

serumcreat.dt A data.table with columns gender, reth, age_years, age_months, BSA_adj.

Value

The same data.table with a serum_creat column added, containing spline-interpolated serum creatinine values.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

get_cheminfo *Retrieve chemical information from HTK package*

Description

This function provides the information specified in "info=" (can be single entry or vector) for all chemicals for which a toxicokinetic model can be parameterized for a given species. Since different models have different requirements and not all chemicals have complete data, this function will return different number of chemicals depending on the model specified.

Usage

```
get_cheminfo(
  info = "CAS",
  species = "Human",
  fup.lod.default = 0.005,
  model = "3compartmentss",
  default.to.human = FALSE,
  median.only = FALSE,
  fup.ci.cutoff = TRUE,
  clint.pvalue.threshold = 0.05,
  suppress.messages = FALSE
)
```

Arguments

info	A single character vector (or collection of character vectors) from "Compound", "CAS", "DTXSID", "logP", "pKa_Donor", "pKa_Accept", "MW", "Clint", "Clint.pValue", "Funbound.plasma", "Structure_Formula", or "Substance_Type". info="all" gives all information for the model and species.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
fup.lod.default	Default value used for fraction of unbound plasma for chemicals where measured value was below the limit of detection. Default value is 0.0005.
model	Model used in calculation, 'pbtk' for the multiple compartment model, '1compartment' for the one compartment model, '3compartment' for three compartment model, '3compartmentss' for the three compartment model without partition coefficients, or 'schmitt' for chemicals with logP and fraction unbound (used in predict_partitioning_schmitt).
default.to.human	Substitutes missing values with human values if true.
median.only	Use median values only for fup and clint. Default is FALSE.
fup.ci.cutoff	Cutoff for the level of uncertainty in fup estimates. This value should be between (0,1). Default is 'NULL' specifying no filtering.
clint.pvalue.threshold	Hepatic clearance for chemicals where the in vitro clearance assay result has a p-values greater than the threshold are set to zero.
suppress.messages	Whether or not the output messages are suppressed.

Details

When default.to.human is set to TRUE, and the species-specific data, Funbound.plasma and Clint, are missing from [chem.physical_and_invitro.data](#), human values are given instead.

In some cases the rapid equilibrium dialysis method (Waters et al., 2008) fails to yield detectable concentrations for the free fraction of chemical. In those cases we assume the compound is highly bound (that is, Fup approaches zero). For some calculations (for example, steady-state plasma concentration) there is precedent (Rotroff et al., 2010) for using half the average limit of detection, that is, 0.005 (this value is configurable via the argument fup.lod.default). We do not recommend using other models where quantities like partition coefficients must be predicted using Fup. We also do not recommend including the value 0.005 in training sets for Fup predictive models.

Note that in some cases the **Funbound.plasma** and the **intrinsic clearance** are *provided as a series of numbers separated by commas*. These values are the result of Bayesian analysis and characterize a distribution: the first value is the median of the distribution, while the second and third values are the lower and upper 95th percentile (that is quantile 2.5 and 97.5) respectively. For intrinsic clearance a fourth value indicating a p-value for a decrease is provided. Typically 4000 samples were used for the Bayesian analysis, such that a p-value of "0" is equivalent to "<0.00025". See Wambaugh et al. (2019) for more details. If argument `median.only == TRUE` then only the median is reported for parameters with Bayesian analysis distributions. If the 95 credible interval is larger than `fup.ci.cutoff` (defaults to `NULL`) then the `Fup` is treated as too uncertain and the value `NA` is given.

Value

vector/data.table

Table (if `info` has multiple entries) or vector containing a column for each valid entry specified in the argument `"info"` and a row for each chemical with sufficient data for the model specified by argument `"model"`:

Column	Description	units
Compound	The preferred name of the chemical compound	none
CAS	The preferred Chemical Abstracts Service Registry Number	none
DTXSID	DSSTox Structure ID (http://comptox.epa.gov/dashboard)	none
logP	The log10 octanol:water partition coefficient	log10 unitless ratio
MW	The chemical compound molecular weight	g/mol
pKa_Accept	The hydrogen acceptor equilibria concentrations	logarithm
pKa_Donor	The hydrogen donor equilibria concentrations	logarithm
[SPECIES].Clint	(Primary hepatocyte suspension) intrinsic hepatic clearance	uL/min/10 ⁶ hepatocytes
[SPECIES].Clint.pValue	Probability that there is no clearance observed.	none
[SPECIES].Funbound.plasma	Chemical fraction unbound in presence of plasma proteins	unitless fraction
[SPECIES].Rblood2plasma	Chemical concentration blood to plasma ratio	unitless ratio

Author(s)

John Wambaugh, Robert Pearce, and Sarah E. Davidson

References

- Rotroff, Daniel M., et al. "Incorporating human dosimetry and exposure into high-throughput in vitro toxicity screening." *Toxicological Sciences* 117.2 (2010): 348-358.
- Waters, Nigel J., et al. "Validation of a rapid equilibrium dialysis approach for the measurement of plasma protein binding." *Journal of pharmaceutical sciences* 97.10 (2008): 4586-4595.
- Wambaugh, John F., et al. "Assessing toxicokinetic uncertainty and variability in risk prioritization." *Toxicological Sciences* 172.2 (2019): 235-251.

Examples

```
# List all CAS numbers for which the 3compartmentss model can be run in humans:
get_cheminfo()

get_cheminfo(info=c('compound', 'funbound.plasma', 'logP'), model='pbtk')
# See all the data for humans:
```

```

get_cheminfo(info="all")

TP0.cas <- c("741-58-2", "333-41-5", "51707-55-2", "30560-19-1", "5598-13-0",
"35575-96-3", "142459-58-3", "1634-78-2", "161326-34-7", "133-07-3", "533-74-4",
"101-05-3", "330-54-1", "6153-64-6", "15299-99-7", "87-90-1", "42509-80-8",
"10265-92-6", "122-14-5", "12427-38-2", "83-79-4", "55-38-9", "2310-17-0",
"5234-68-4", "330-55-2", "3337-71-1", "6923-22-4", "23564-05-8", "101-02-0",
"140-56-7", "120-71-8", "120-12-7", "123-31-9", "91-53-2", "131807-57-3",
"68157-60-8", "5598-15-2", "115-32-2", "298-00-0", "60-51-5", "23031-36-9",
"137-26-8", "96-45-7", "16672-87-0", "709-98-8", "149877-41-8", "145701-21-9",
"7786-34-7", "54593-83-8", "23422-53-9", "56-38-2", "41198-08-7", "50-65-7",
"28434-00-6", "56-72-4", "62-73-7", "6317-18-6", "96182-53-5", "87-86-5",
"101-54-2", "121-69-7", "532-27-4", "91-59-8", "105-67-9", "90-04-0",
"134-20-3", "599-64-4", "148-24-3", "2416-94-6", "121-79-9", "527-60-6",
"99-97-8", "131-55-5", "105-87-3", "136-77-6", "1401-55-4", "1948-33-0",
"121-00-6", "92-84-2", "140-66-9", "99-71-8", "150-13-0", "80-46-6", "120-95-6",
"128-39-2", "2687-25-4", "732-11-6", "5392-40-5", "80-05-7", "135158-54-2",
"29232-93-7", "6734-80-1", "98-54-4", "97-53-0", "96-76-4", "118-71-8",
"2451-62-9", "150-68-5", "732-26-3", "99-59-2", "59-30-3", "3811-73-2",
"101-61-1", "4180-23-8", "101-80-4", "86-50-0", "2687-96-9", "108-46-3",
"95-54-5", "101-77-9", "95-80-7", "420-04-2", "60-54-8", "375-95-1", "120-80-9",
"149-30-4", "135-19-3", "88-58-4", "84-16-2", "6381-77-7", "1478-61-1",
"96-70-8", "128-04-1", "25956-17-6", "92-52-4", "1987-50-4", "563-12-2",
"298-02-2", "79902-63-9", "27955-94-8")
httk.TP0.rat.table <- subset(get_cheminfo(info="all",species="rat"),
  CAS %in% TP0.cas)

httk.TP0.human.table <- subset(get_cheminfo(info="all",species="human"),
  CAS %in% TP0.cas)

```

get_chem_id

Retrieve chemical identity from HTK package

Description

Given one of chem.name, chem.cas (Chemical Abstract Service Registry Number), or DTXSID (DSStox Substance Identifier <https://comptox.epa.gov/dashboard>) this function checks if the chemical is available and, if so, returns all three pieces of information.

Usage

```
get_chem_id(chem.cas = NULL, chem.name = NULL, dtxsid = NULL)
```

Arguments

chem.cas	CAS registry number
chem.name	Chemical name
dtxsid	DSSTox Substance identifier

Value

A list containing the following chemical identifiers:

chem.cas	CAS registry number
chem.name	Name
dtxsid	DTXSID

Author(s)

John Wambaugh and Robert Pearce

get_gfr_category	<i>Categorize kidney function by GFR.</i>
------------------	---

Description

For adults: In general GFR > 60 is considered normal 15 < GFR < 60 is considered kidney disease
GFR < 15 is considered kidney failure

Usage

```
get_gfr_category(age_years, age_months, gfr_est)
```

Arguments

age_years	Vector of ages in years.
age_months	Vector of ages in months.
gfr_est	Vector of estimated GFR values in mL/min/1.73m ² .

Details

These values can also be used for children 2 years old and greater (see PEDIATRICS IN REVIEW
Vol. 29 No. 10 October 1, 2008 pp. 335-341 (doi: 10.1542/pir.29-10-335))

Value

Vector of GFR categories: 'Normal', 'Kidney Disease', 'Kidney Failure'.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

get_invitroPK_param	<i>Retrieve data from chem.physical_and_invitro.data table</i>
---------------------	--

Description

or fraction unbound in plasma) from the main HTTK data. This function looks for species-specific values.

Usage

```
get_invitroPK_param(  
  param,  
  species,  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL  
)
```

Arguments

param	The in vitro pharmacokinetic parameter needed.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs

Value

The value of the parameter, if found

Author(s)

John Wambaugh and Robert Pearce

get_lit_cheminfo	<i>Get literature Chemical Information.</i>
------------------	---

Description

This function provides the information specified in "info=" for all chemicals with data from the Wetmore et al. (2012) and (2013) publications and other literature.

Usage

```
get_lit_cheminfo(info = "CAS", species = "Human")
```

Arguments

info	A single character vector (or collection of character vectors) from "Compound", "CAS", "MW", "Raw.Experimental.Percentage.Unbound", "Entered.Experimental.Percentage.Unbound", "Fub", "source_PPB", "Renal_Clearance", "Met_Stab", "Met_Stab_entered", "r2", "p.val", "Concentration..uM.", "Css_lower_5th_perc.mg.L.", "Css_median_perc.mg.L.", "Css_upper_95th_perc.mg.L.", "Css_lower_5th_perc.uM.", "Css_median_perc.uM.", "Css_upper_95th_perc.uM." and "Species".
species	Species desired (either "Rat" or default "Human").

Value

info	Table/vector containing values specified in "info" for valid chemicals.
------	---

Author(s)

John Wambaugh

References

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Sochaski, M.A., Rotroff, D.M., Freeman, K., Clewell, H.J., Dix, D.H., Andersen, M.E., Houck, K.A., Allen, B., Judson, R.S., Sing, R., Kavlock, R.J., Richard, A.M., and Thomas, R.S., "Integration of Dosimetry, Exposure and High-Throughput Screening Data in Chemical Toxicity Assessment," *Toxicological Sciences* 125 157-174 (2012)

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Li, L., Clewell, H.J. III, Judson, R.S., Freeman, K., Bao, W., Sochaski, M.A., Chu T.-M., Black, M.B., Healy, E., Allen, B., Andersen M.E., Wolfinger, R.D., and Thomas R.S., "The Relative Impact of Incorporating Pharmacokinetics on Predicting in vivo Hazard and Mode-of-Action from High-Throughput in vitro Toxicity Assays" *Toxicological Sciences*, 132:327-346 (2013).

Wetmore, B. A., Wambaugh, J. F., Allen, B., Ferguson, S. S., Sochaski, M. A., Setzer, R. W., Houck, K. A., Strope, C. L., Cantwell, K., Judson, R. S., LeCluyse, E., Clewell, H.J. III, Thomas, R.S., and Andersen, M. E. (2015). "Incorporating High-Throughput Exposure Predictions with Dosimetry-Adjusted In Vitro Bioactivity to Inform Chemical Toxicity Testing" *Toxicological Sciences*, kfv171.

Examples

```
get_lit_cheminfo()
get_lit_cheminfo(info=c('CAS', 'MW'))
```

get_lit_css

Get literature Css

Description

This function retrieves a steady-state plasma concentration as a result of infusion dosing from the Wetmore et al. (2012) and (2013) publications and other literature.

Usage

```
get_lit_css(  
  chem.cas = NULL,  
  chem.name = NULL,  
  daily.dose = 1,  
  which.quantile = 0.95,  
  species = "Human",  
  clearance.assay.conc = NULL,  
  output.units = "mg/L",  
  suppress.messages = FALSE  
)
```

Arguments

chem.cas	Either the cas number or the chemical name must be specified.
chem.name	Either the chemical name or the CAS number must be specified.
daily.dose	Total daily dose infused in units of mg/kg BW/day. Defaults to 1 mg/kg/day.
which.quantile	Which quantile from the SimCYP Monte Carlo simulation is requested. Can be a vector.
species	Species desired (either "Rat" or default "Human").
clearance.assay.conc	Concentration of chemical used in measuring intrinsic clearance data, 1 or 10 uM.
output.units	Returned units for function, defaults to mg/L but can also be uM (specify units = "uM").
suppress.messages	Whether or not the output message is suppressed.

Value

A numeric vector with the literature steady-state plasma concentration (1 mg/kg/day) for the requested quantiles

Author(s)

John Wambaugh

References

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Sochaski, M.A., Rotroff, D.M., Freeman, K., Clewell, H.J., Dix, D.H., Andersen, M.E., Houck, K.A., Allen, B., Judson, R.S., Sing, R., Kavlock, R.J., Richard, A.M., and Thomas, R.S., "Integration of Dosimetry, Exposure and High-Throughput Screening Data in Chemical Toxicity Assessment," *Toxicological Sciences* 125 157-174 (2012)

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Li, L., Clewell, H.J. III, Judson, R.S., Freeman, K., Bao, W., Sochaski, M.A., Chu T.-M., Black, M.B., Healy, E., Allen, B., Andersen M.E., Wolfinger, R.D., and Thomas R.S., "The Relative Impact of Incorporating Pharmacokinetics on Predicting in vivo Hazard and Mode-of-Action from High-Throughput in vitro Toxicity Assays" *Toxicological Sciences*, 132:327-346 (2013).

Wetmore, B. A., Wambaugh, J. F., Allen, B., Ferguson, S. S., Sochaski, M. A., Setzer, R. W., Houck, K. A., Strobe, C. L., Cantwell, K., Judson, R. S., LeCluyse, E., Clewell, H.J. III, Thomas, R.S., and Andersen, M. E. (2015). "Incorporating High-Throughput Exposure Predictions with Dosimetry-Adjusted In Vitro Bioactivity to Inform Chemical Toxicity Testing" *Toxicological Sciences*, kfv171.

Examples

```
get_lit_css(chem.cas="34256-82-1")

get_lit_css(chem.cas="34256-82-1",species="Rat",which.quantile=0.5)

get_lit_css(chem.cas="80-05-7", daily.dose = 1,which.quantile = 0.5, output.units = "uM")
```

get_lit_oral_equiv	<i>Get Literature Oral Equivalent Dose</i>
--------------------	--

Description

This function converts a chemical plasma concentration to an oral equivalent dose using the values from the Wetmore et al. (2012) and (2013) publications and other literature.

Usage

```
get_lit_oral_equiv(
  conc,
  chem.name = NULL,
  chem.cas = NULL,
  suppress.messages = FALSE,
  which.quantile = 0.95,
  species = "Human",
  input.units = "uM",
  output.units = "mg",
  clearance.assay.conc = NULL,
  ...
)
```

Arguments

conc	Bioactive in vitro concentration in units of specified input.units, default of uM.
chem.name	Either the chemical name or the CAS number must be specified.
chem.cas	Either the CAS number or the chemical name must be specified.
suppress.messages	Suppress output messages.
which.quantile	Which quantile from the SimCYP Monte Carlo simulation is requested. Can be a vector. Papers include 0.05, 0.5, and 0.95 for humans and 0.5 for rats.
species	Species desired (either "Rat" or default "Human").
input.units	Units of given concentration, default of uM but can also be mg/L.
output.units	Units of dose, default of 'mg' for mg/kg BW/ day or 'mol' for mol/ kg BW/ day.
clearance.assay.conc	Concentration of chemical used in measuring intrinsic clearance data, 1 or 10 uM.
...	Additional parameters passed to get_lit_css.

Value

Equivalent dose in specified units, default of mg/kg BW/day.

Author(s)

John Wambaugh

References

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Sochaski, M.A., Rotroff, D.M., Freeman, K., Clewell, H.J., Dix, D.H., Andersen, M.E., Houck, K.A., Allen, B., Judson, R.S., Sing, R., Kavlock, R.J., Richard, A.M., and Thomas, R.S., "Integration of Dosimetry, Exposure and High-Throughput Screening Data in Chemical Toxicity Assessment," *Toxicological Sciences* 125 157-174 (2012)

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Li, L., Clewell, H.J. III, Judson, R.S., Freeman, K., Bao, W., Sochaski, M.A., Chu T.-M., Black, M.B., Healy, E., Allen, B., Andersen M.E., Wolfinger, R.D., and Thomas R.S., "The Relative Impact of Incorporating Pharmacokinetics on Predicting in vivo Hazard and Mode-of-Action from High-Throughput in vitro Toxicity Assays" *Toxicological Sciences*, 132:327-346 (2013).

Wetmore, B. A., Wambaugh, J. F., Allen, B., Ferguson, S. S., Sochaski, M. A., Setzer, R. W., Houck, K. A., Strope, C. L., Cantwell, K., Judson, R. S., LeCluyse, E., Clewell, H.J. III, Thomas, R.S., and Andersen, M. E. (2015). "Incorporating High-Throughput Exposure Predictions with Dosimetry-Adjusted In Vitro Bioactivity to Inform Chemical Toxicity Testing" *Toxicological Sciences*, kfv171.

Examples

```
table <- NULL
for(this.cas in sample(get_lit_cheminfo(),50)) table <- rbind(table,cbind(
as.data.frame(this.cas),as.data.frame(get_lit_oral_equiv(conc=1,chem.cas=this.cas))))
```

```
get_lit_oral_equiv(0.1,chem.cas="34256-82-1")
```

```
get_lit_oral_equiv(0.1,chem.cas="34256-82-1",which.quantile=c(0.05,0.5,0.95))
```

get_physchem_param	<i>Get physico-chemical parameters from chem.physical_and_invitro.data</i>
--------------------	--

Description

This function retrieves physico-chemical properties ("param") for the chemical specified by chem.name or chem.cas from the vLiver tables.

Usage

```
get_physchem_param(param, chem.name = NULL, chem.cas = NULL, dtxsid = NULL)
```

Arguments

param	The desired parameters, a vector or single value.
chem.name	The chemical names that you want parameters for, a vector or single value
chem.cas	The chemical CAS numbers that you want parameters for, a vector or single value
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs

Value

The parameters, either a single value, a named list for a single chemical, or a list of lists

Author(s)

John Wambaugh and Robert Pearce

Examples

```
get_physchem_param(param = 'logP', chem.cas = '80-05-7')
get_physchem_param(param = c('logP', 'MW'), chem.cas = c('80-05-7', '81-81-2'))
```

get_rblood2plasma	<i>Get ratio of the blood concentration to the plasma concentration.</i>
-------------------	--

Description

This function attempts to retrieve a measured species- and chemical-specific blood:plasma concentration ratio.

Usage

```
get_rblood2plasma(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  species = "Human",
  default.to.human = FALSE
)
```

Arguments

chem.name	Either the chemical name or the CAS number must be specified.
chem.cas	Either the CAS number or the chemical name must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
default.to.human	Substitutes missing animal values with human values if true.

Details

A value of NA is returned when the requested value is unavailable. Values are retrieved from chem.physical_and_invitro.data. details than the description above ~~

Value

A numeric value for the steady-state ratio of chemical concentration in blood to plasma

Author(s)

Robert Pearce

Examples

```
get_rblood2plasma(chem.name="Bisphenol A")
get_rblood2plasma(chem.name="Bisphenol A",species="Rat")
```

get_weight_class	<i>Given vectors of age, BMI, recumbent length, weight, and gender, categorizes weight classes using CDC and WHO categories.</i>
------------------	--

Description

Given vectors of age, BMI, recumbent length, weight, and gender, categorizes weight classes using CDC and WHO categories.

Usage

```
get_weight_class(age_years, age_months, bmi, recumlen, weight, gender)
```

Arguments

age_years	A vector of ages in years.
age_months	A vector of ages in months.
bmi	A vector of BMIs.
recumlen	A vector of heights or recumbent lengths in cm.
weight	A vector of body weights in kg.
gender	A vector of genders (as 'Male' or 'Female').

Value

A character vector of weight classes. Each element will be one of 'Underweight', 'Normal', 'Overweight', or 'Obese'.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

hematocrit_infants	<i>Predict hematocrit in infants under 1 year old.</i>
--------------------	--

Description

For infants under 1 year, hematocrit was not measured in NHANES. Assume a log-normal distribution where plus/minus 1 standard deviation of the underlying normal distribution is given by the reference range. Draw hematocrit values from these distributions by age.

Usage

```
hematocrit_infants(age_months)
```

Arguments

age_months Vector of ages in months; all must be ≤ 12 .

Details

Age	Reference range
<1 month	31-49
1-6 months	29-42
7-12 months	33-38

Value

Vector of hematocrit percentages corresponding to the input vector of ages.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

honda.ivive	<i>Return the assumptions used in Honda et al. 2019</i>
-------------	---

Description

This function returns four of the better performing sets of assumptions evaluated in Honda et al. 2019 (<https://doi.org/10.1371/journal.pone.0217564>). These include four different combinations of hepatic clearance assumption, in vivo bioactivity assumption, and relevant tissue assumption. Generally, this function is not called directly by the user, but instead called by setting the IVIVE option in `calc_mc_oral_equiv`, `calc_mc_css`, and `calc_analytic` functions. Currently, these IVIVE option is not implemented the `solve_lcomp` etc. functions.

Usage

```
honda.ivive(method = "Honda1", tissue = "liver")
```

Arguments

<code>method</code>	This is set to one of "Honda1", "Honda2", "Honda3", or "Honda4".
<code>tissue</code>	This is only relevant to "Honda4" and indicates the relevant tissue compartment.

Details

"Honda1" - `tissue = NULL`, `restrictive.clearance = TRUE`, `bioactive.free.invivo = TRUE` This assumption assumes restrictive hepatic clearance, and treats the free concentration in plasma as the bioactive concentration in vivo. This option must be used in combination with the concentration in vitro predicted by `armitage_eval()`, otherwise the result will be the same as "Honda2". This option corresponds to the result in Figure 8 panel c) restrictive, mean free plasma conc., Armitage in Honda et al. 2019. "Honda2" - `tissue = NULL`, `restrictive.clearance = TRUE`, `bioactive.free.invivo = TRUE` This assumption assumes restrictive hepatic clearance, and treats the free concentration in plasma as the bioactive concentration in vivo. This option corresponds to the result in Figure 8 panel b) restrictive, mean free plasma conc. in Honda et al. 2019. "Honda3" - `tissue = NULL`, `restrictive.clearance = TRUE`, `bioactive.free.invivo = TRUE` This assumption assumes restrictive hepatic clearance, and treats the free concentration in plasma as the bioactive concentration in vivo. This option corresponds to the result in Figure 8 panel a) restrictive, mean total plasma conc. in Honda et al. 2019. "Honda4" - `tissue = tissue`, `restrictive.clearance = FALSE`, `bioactive.free.invivo = TRUE` This assumption assumes restrictive hepatic clearance, and treats the free concentration in plasma as the bioactive concentration in vivo. The input tissue should be relevant to the in vitro assay endpoint used as input or that the result is being compared to. This option corresponds to the result in Figure 8 panel d) nonrestrictive, mean tissue conc. in Honda et al. 2019.

Value

A list of `tissue`, `bioactive.free.invivo`, and `restrictive.clearance` assumptions.

Author(s)

Greg Honda and John Wambaugh

References

Honda, Gregory S., et al. "Using the Concordance of In Vitro and In Vivo Data to Evaluate Extrapolation Assumptions." 2019. PLoS ONE 14(5): e0217564.

Examples

```
honda.i vive(method = "Honda1", tissue = NULL)
```

howgate	<i>Howgate 2006</i>
---------	---------------------

Description

This data set is only used in Vignette 5.

Usage

```
howgate
```

Format

A data.table containing 24 rows and 11 columns.

Author(s)

Caroline Ring

References

Howgate, E. M., et al. "Prediction of in vivo drug clearance from in vitro data. I: impact of inter-individual variability." *Xenobiotica* 36.6 (2006): 473-497.

httkpop	<i>httkpop: Virtual population generator for HTTK.</i>
---------	--

Description

The httkpop package generates virtual population physiologies for use in population TK.

Details

To simulate inter-individual variability in the TK model, a MC approach is used: the model parameters are sampled from known or assumed distributions, and the model is evaluated for each sampled set of parameters. To simulate variability across subpopulations, the MC approach needs to capture the parameter correlation structure. For example, kidney function changes with age (Levey et al., 2009), thus the distribution of GFR is likely different in 6-year-olds than in 65-year-olds. To directly measure the parameter correlation structure, all parameters need to be measured in each individual in a representative sample population. Such direct measurements are extremely limited. However, the correlation structure of the physiological parameters can be inferred from their known individual correlations with demographic and anthropometric quantities for which direct population measurements do exist. These quantities are sex, race/ethnicity, age, height, and weight (Howgate et al., 2006; Jamei et al., 2009a; Johnson et al., 2006; McNally et al., 2014; Price et al., 2003). Direct measurements of these quantities in a large, representative sample of the U.S. population are publicly available from NHANES. NHANES also includes laboratory measurements, including

both serum creatinine, which can be used to estimate GFR (Levey et al., 2009), and hematocrit. For conciseness, sex, race/ethnicity, age, height, weight, serum creatinine, and hematocrit will be called the NHANES quantities.

HTTK-Pop's correlated MC approach begins by sampling from the joint distribution of the NHANES quantities to simulate a population. Then, for each individual in the simulated population, HTTK-Pop predicts the physiological parameters from the NHANES quantities using regression equations from the literature (Barter et al., 2007; Baxter-Jones et al., 2011; Bosgra et al., 2012; Koo et al., 2000; Levey et al., 2009; Looker et al., 2013; McNally et al., 2014; Ogiu et al., 1997; Price et al., 2003; Schwartz and Work, 2009; Webber and Barr 2012). Correlations among the physiological parameters are induced by their mutual dependence on the correlated NHANES quantities. Finally, residual variability is added to the predicted physiological parameters using estimates of residual marginal variance (i.e., variance not explained by the regressions on the NHANES quantities) (McNally et al., 2014).

Data were combined from the three most recent publicly-available NHANES cycles: 2007-2008, 2009-2010, and 2011-2012. For each cycle, some NHANES quantities - height, weight, serum creatinine, and hematocrit - were measured only in a subset of respondents. Only these subsets were included in HTTK-Pop. The pooled subsets from the three cycles contained 29,353 unique respondents. Some respondents were excluded from analysis: those with age recorded as 80 years (because all NHANES respondents 80 years and older were marked as "80"); those with missing height, weight or hematocrit data; and those aged 12 years or older with missing serum creatinine data. These criteria excluded 4807 respondents, leaving 24,546 unique respondents. Each NHANES respondent was assigned a cycle-specific sample weight, which can be interpreted as the number of individuals in the total U.S. population represented by each NHANES respondent in each cycle (Johnson et al., 2013). Because data from three cycles were combined, the sample weights were rescaled (divided by the number of cycles being combined, as recommended in NHANES data analysis documentation) (Johnson et al., 2013). To handle the complex NHANES sampling structure, the R survey package was used to analyze the NHANES data (Lumley, 2004).

To allow generation of virtual populations specified by weight class, we coded a categorical variable for each NHANES respondent. The categories Underweight, Normal, Overweight, or Obese were assigned based on weight, age, and height/length (Grummer-Strawn et al., 2010; Kuczmarski et al., 2002; Ogden et al., 2014; WHO, 2006, 2010). We implemented two population simulation methods within HTTK-Pop: the direct-resampling method and the virtual-individuals method. The direct-resampling method simulated a population by sampling NHANES respondents with replacement, with probabilities proportional to the sample weights. Each individual in the resulting simulated population was an NHANES respondent, identified by a unique NHANES sequence number. By contrast, the second method generates "virtual individuals" - sets of NHANES quantities that obey the approximate joint distribution of the NHANES quantities (calculated using weighted smoothing functions and kernel density estimators), but do not necessarily correspond to any particular NHANES respondent. The direct-resampling method removed the possibility of generating unrealistic combinations of the NHANES quantities; the virtual-individuals method allowed the use of interpolation to simulate subpopulations represented by only a small number of NHANES respondents.

For either method, HTTK-Pop takes optional specifications about the population to be simulated and then samples from the appropriate conditional joint distribution of the NHANES quantities.

Once HTTK-Pop has simulated a population characterized by the NHANES quantities, the physiological parameters of the TK model are predicted from the NHANES quantities using regression equations from the literature. Liver mass was predicted for individuals over age 18 using allometric scaling with height from Reference Man (Valentin, 2002), and for individuals under 18 using regression relationships with height and weight published by Ogiu et al. (1997). Residual marginal variability was added for each individual as in PopGen (McNally et al., 2014). Similarly, hepatic portal vein blood flows (in L/h) are predicted as fixed fractions of a cardiac output allometrically

scaled with height from Reference Man (Valentin, 2002), and residual marginal variability is added for each individual (McNally et al., 2014). Glomerular filtration rate (GFR) (in L/h/1.73 m² body surface area) is predicted from age, race, sex, and serum creatinine using the CKD-EPI equation, for individuals over age 18 (Levey et al., 2009). For individuals under age 18, GFR is estimated from body surface area (BSA) (Johnson et al., 2006); BSA is predicted using Mosteller's formula (Verbraecken et al., 2006) for adults and Haycock's formula (Haycock et al., 1978) for children. Hepatocellularity (in millions of cells per gram of liver tissue) is predicted from age using an equation developed by Barter et al. (2007). Hematocrit is estimated from NHANES data for individuals 1 year and older. For individuals younger than 1 year, for whom NHANES did not measure hematocrit directly, hematocrit was predicted from age in months, using published reference ranges (Lubin, 1987).

In addition to the HTTK physiological parameters, the HTTK models include chemical-specific parameters representing the fraction of chemical unbound in plasma (Fup) and intrinsic clearance (CL_{int}). Because these parameters represent interactions of the chemical with the body, their values will vary between individuals. To simulate this variability, Fup and CL_{int} were included in MC simulations, by sampling from estimated or assumed distributions for the parameters defining them.

Variability in hematocrit was simulated either using NHANES data (for individuals ages 1 and older) or using age-based reference ranges (for individuals under age 1). Fup was treated as a random variable obeying a distribution censored below the average limit of quantification (LOQ) of the in vitro assay. Specifically, Fup was assumed to obey a normal distribution truncated below at 0 and above at 1, centered at the Fup value measured in vitro, with a 30 the average LOQ (0.01), Fup was instead drawn from a uniform distribution between 0 and 0.01. Fup was assumed to be independent of all other parameters. This censored normal distribution was chosen to match that used in Wambaugh et al. (2015).

Variability in hepatocellularity (106 cells/g liver) and M_{liver} (kg) were simulated. The remaining source of variability in CL_{int,h} is variability in CL_{int}, which was simulated using a Gaussian mixture distribution to represent the population proportions of poor metabolizers (PMs) and non-PMs of each substance. The true prevalence of PMs is isozyme-specific (Ma et al., 2002; Yasuda et al., 2008); however, isozyme-specific metabolism data were not available for the majority of chemicals considered. We therefore made a simplifying assumption that 5 slower than average. With 95 a normal distribution truncated below at zero, centered at the value measured in vitro, with a 30 CL_{int} was drawn from a PM distribution: a truncated normal distribution centered on one-tenth of the in vitro value with 30 Both CL_{int} itself and the probability of being a PM were assumed to be independent of all other parameters. The truncated normal nonePM distribution was chosen because it has been used (with 100 in previous work (Rotroff et al., 2010; Wambaugh et al., 2015; Wetmore et al., 2014; Wetmore et al., 2015; Wetmore et al., 2012); the PM distribution was chosen to comport with the nonePM distribution.

Main function to generate a population

If you just want to generate a table of (chemical-independent) population physiology parameters, use [httkpop_generate](#).

Using HTTK-Pop with HTTK

To generate a population and then run an HTTK model for that population, the workflow is as follows:

1. Generate a population using [httkpop_generate](#).
2. For a given HTTK chemical and general model, convert the population data to corresponding sets of HTTK model parameters using [httkpop_mc](#).

Author(s)

Caroline Ring

References

- Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118
- Levey, A.S., Stevens, L.A., Schmid, C.H., Zhang, Y.L., Castro, A.F., Feldman, H.I., et al., 2009. A new equation to estimate glomerular filtration rate. *Ann. Intern. Med.* 150, 604-612.
- Howgate, E., Rowland-Yeo, K., Proctor, N., Tucker, G., Rostami-Hodjegan, A., 2006. Prediction of in vivo drug clearance from in vitro data. I: impact of inter-individual variability. *Xenobiotica* 36, 473-497.
- Jamei, M., Dickinson, G.L., Rostami-Hodjegan, A., 2009a. A framework for assessing inter-individual variability in pharmacokinetics using virtual human populations and integrating general knowledge of physical chemistry, biology, anatomy, physiology and genetics: a tale of 'bottom-up' vs 'top-down' recognition of covariates. *Drug Metab. Pharmacokinet.* 24, 53-75.
- Johnson, T.N., Rostami-Hodjegan, A., Tucker, G.T., 2006. Prediction of the clearance of eleven drugs and associated variability in neonates, infants and children. *Clin. Pharmacokinet.* 45, 931-956.
- McNally, K., Cotton, R., Hogg, A., Loizou, G., 2014. PopGen: a virtual human population generator. *Toxicology* 315, 70-85.
- Price, P.S., Conolly, R.B., Chaisson, C.F., Gross, E.A., Young, J.S., Mathis, E.T., et al., 2003. Modeling interindividual variation in physiological factors used in PBPK models of humans. *Crit. Rev. Toxicol.* 33, 469-503.
- Barter, Z.E., Bayliss, M.K., Beaune, P.H., Boobis, A.R., Carlile, D.J., Edwards, R.J., et al., 2007. Scaling factors for the extrapolation of in vivo metabolic drug clearance from in vitro data: reaching a consensus on values of human micro-somal protein and hepatocellularity per gram of liver. *Curr. Drug Metab.* 8, 33-45.
- Baxter-Jones, A.D., Faulkner, R.A., Forwood, M.R., Mirwald, R.L., Bailey, D.A., 2011. Bone mineral accrual from 8 to 30 years of age: an estimation of peak bone mass. *J. Bone Miner. Res.* 26, 1729-1739.
- Bosgra, S., van Eijkeren, J., Bos, P., Zeilmaker, M., Slob, W., 2012. An improved model to predict physiologically based model parameters and their inter-individual variability from anthropometry. *Crit. Rev. Toxicol.* 42, 751-767.
- Koo, W.W., Walters, J.C., Hockman, E.M., 2000. Body composition in human infants at birth and postnatally. *J. Nutr.* 130, 2188-2194.
- Looker, A., Borrud, L., Hughes, J., Fan, B., Shepherd, J., Sherman, M., 2013. Total body bone area, bone mineral content, and bone mineral density for individuals aged 8 years and over: United States, 1999-2006. In: *Vital and health statistics Series 11, Data from the National Health Survey*, pp. 1-78.
- Ogiu, N., Nakamura, Y., Ijiri, I., Hiraiwa, K., Ogiu, T., 1997. A statistical analysis of the internal organ weights of normal Japanese people. *Health Phys.* 72, 368-383.
- Schwartz, G.J., Work, D.F., 2009. Measurement and estimation of GFR in children and adolescents. *Clin. J. Am. Soc. Nephrol.* 4, 1832-1843.
- Webber, C.E., Barr, R.D., 2012. Age-and gender-dependent values of skeletal muscle mass in healthy children and adolescents. *J. Cachex. Sarcopenia Muscle* 3, 25-29.

- Johnson, C.L., Paulose-Ram, R., Ogden, C.L., Carroll, M.D., Kruszon-Moran, D., Dohrmann, S.M., et al., 2013. National health and nutrition examination survey: analytic guidelines, 1999-2010. *Vital and health statistics Series 2. Data Eval. Methods Res.* 1-24.
- Lumley, T., 2004. Analysis of complex survey samples. *J. Stat. Softw.* 9, 1-19.
- Grummer-Strawn, L.M., Reinold, C.M., Krebs, N.F., Control, C.f.D.; Prevention, 2010. Use of World Health Organization and CDC Growth Charts for Children Aged 0-59 Months in the United States. Department of Health and Human Services, Centers for Disease Control and Prevention.
- Kuczmarski, R.J., Ogden, C.L., Guo, S.S., Grummer-Strawn, L.M., Flegal, K.M., Mei, Z., et al., 2002. 2000 CDC growth charts for the United States: methods and development. *Vital Health Stat. Series 11, Data from the national health survey* 246, 1-190.
- Ogden, C.L., Carroll, M.D., Kit, B.K., Flegal, K.M., 2014. Prevalence of childhood and adult obesity in the United States, 2011-2012. *JAMA* 311, 806-814.
- WHO, 2006. In: WHO D.o.N.f.H.a.D. (Ed.), WHO Child Growth Standards: Length/Height-for-Age, Weight-for-Age, Weight-for-Length, Weight-for-Height and Body Mass Index-for-Age: Methods and Development.
- WHO, 2010. In: (WHO) W.H.O. (Ed.), WHO Anthro for Personal Computers Manual: Software for Assessing Growth and Development of the World's Children, Version 3.2.2, 2011. WHO, Geneva.
- Valentin, J., 2002. Basic anatomical and physiological data for use in radiological protection: reference values: ICRP publication 89. *Ann. ICRP* 32, 1-277.
- Johnson, T.N., Rostami-Hodjegan, A., Tucker, G.T., 2006. Prediction of the clearance of eleven drugs and associated variability in neonates, infants and children. *Clin. Pharmacokinet.* 45, 931-956.
- Verbraecken, J., Van de Heyning, P., De Backer, W., Van Gaal, L., 2006. Body surface area in normal-weight, overweight, and obese adults. A comparison study. *Metabolism* 55, 515-524.
- Haycock, G.B., Schwartz, G.J., Wisotsky, D.H., 1978. Geometric method for measuring body surface area: a height-weight formula validated in infants, children, and adults. *J. Pediatr.* 93, 62-66.
- Lubin, B., 1987. Reference values in infancy and childhood. In: Nathan, D., Oski, F. (Eds.), *Hematology of Infancy and Childhood*.
- Wambaugh, J.F., Wetmore, B.A., Pearce, R., Strobe, C., Goldsmith, R., Sluka, J.P., et al., 2015. Toxicokinetic triage for environmental chemicals. *Toxicol. Sci.* 147, 55-67.
- Ma, M.K., Woo, M.H., Mcleod, H.L., 2002. Genetic basis of drug metabolism. *Am. J. Health Syst. Pharm.* 59, 2061-2069.
- Yasuda, S.U., Zhang, L., Huang, S.M., 2008. The role of ethnicity in variability in response to drugs: focus on clinical pharmacology studies. *Clin. Pharmacol. Ther.* 84, 417-423.
- Rotroff, D.M., Wetmore, B.A., Dix, D.J., Ferguson, S.S., Clewell, H.J., Houck, K.A., et al., 2010. Incorporating human dosimetry and exposure into high-throughput in vitro toxicity screening. *Toxicol. Sci.* 117, 348-358.
- Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Sochaski, M.A., Rotroff, D.M., Freeman, K., et al., 2012. Integration of dosimetry, exposure, and high-throughput screening data in chemical toxicity assessment. *Toxicol. Sci.* 125, 157-174.
- Wetmore, B.A., Allen, B., Clewell 3rd, H.J., Parker, T., Wambaugh, J.F., Almond, L.M., et al., 2014. Incorporating population variability and susceptible subpopulations into dosimetry for high-throughput toxicity testing. *Toxicol. Sci.* 142, 210-224.
- Wetmore, B.A., Wambaugh, J.F., Allen, B., Ferguson, S.S., Sochaski, M.A., Setzer, R.W., et al., 2015. Incorporating high-throughput exposure predictions with Dosimetry-adjusted in vitro bioactivity to inform chemical toxicity testing. *Toxicol. Sci.* 148, 121-136.

httkpop_biotophys_default

Convert HTTK-Pop-generated parameters to HTTK physiological parameters

Description

Convert HTTK-Pop-generated parameters to HTTK physiological parameters

Usage

```
httkpop_biotophys_default(indiv_dt)
```

Arguments

indiv_dt The data.table object returned by httkpop_generate()

Value

A data.table with the physiological parameters expected by any HTTK model, including body weight (BW), hematocrit, tissue volumes per kg body weight, tissue flows as fraction of CO, CO per (kg BW)^{3/4}, GFR per (kg BW)^{3/4}, portal vein flow per (kg BW)^{3/4}, and liver density.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

httkpop_direct_resample

Generate a virtual population by directly resampling the NHANES data.

Description

Generate a virtual population by directly resampling the NHANES data.

Usage

```
httkpop_direct_resample(
  nsamp = NULL,
  gendernum = NULL,
  agelim_years = c(0, 79),
  agelim_months = c(0, 959),
  weight_category = c("Underweight", "Normal", "Overweight", "Obese"),
  gfr_category = c("Normal", "Kidney Disease", "Kidney Failure"),
```

```

reths = c("Mexican American", "Other Hispanic", "Non-Hispanic White",
          "Non-Hispanic Black", "Other"),
gfr_resid_var = TRUE,
ckd_epi_race_coeff = FALSE
)

```

Arguments

nsamp	The desired number of individuals in the virtual population. nsamp need not be provided if gendernum is provided.
gendernum	Optional: A named list giving the numbers of male and female individuals to include in the population, e.g. <code>list(Male=100,Female=100)</code> . Default is NULL, meaning both males and females are included, in their proportions in the NHANES data. If both nsamp and gendernum are provided, they must agree (i.e., nsamp must be the sum of gendernum).
agelim_years	Optional: A two-element numeric vector giving the minimum and maximum ages (in years) to include in the population. Default is <code>c(0,79)</code> . If agelim_years is provided and agelim_months is not, agelim_years will override the default value of agelim_months.
agelim_months	Optional: A two-element numeric vector giving the minimum and maximum ages (in months) to include in the population. Default is <code>c(0, 959)</code> , equivalent to the default agelim_years. If agelim_months is provided and agelim_years is not, agelim_months will override the default values of agelim_years.
weight_category	Optional: The weight categories to include in the population. Default is <code>c('Underweight', 'Normal', 'Overweight', 'Obese')</code> . User-supplied vector must contain one or more of these strings.
gfr_category	The kidney function categories to include in the population. Default is <code>c('Normal', 'Kidney Disease', 'Kidney Failure')</code> to include all kidney function levels.
reths	Optional: a character vector giving the races/ethnicities to include in the population. Default is <code>c('Mexican American', 'Other Hispanic', 'Non-Hispanic White', 'Non-Hispanic Black', 'Other')</code> , to include all races and ethnicities in their proportions in the NHANES data. User-supplied vector must contain one or more of these strings.
gfr_resid_var	Logical value indicating whether or not to include residual variability when generating GFR values. (Default is TRUE.)
ckd_epi_race_coeff	Logical value indicating whether or not to use the "race coefficient" from the CKD-EPI equation when estimating GFR values. (Default is FALSE.)

Value

A data.table where each row represents an individual, and each column represents a demographic, anthropometric, or physiological parameter.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

httkpop_direct_resample_inner

Inner loop function called by httkpop_direct_resample.

Description

Inner loop function called by httkpop_direct_resample.

Usage

```
httkpop_direct_resample_inner(
  nsamp,
  gendernum,
  agelim_months,
  agelim_years,
  reths,
  weight_category,
  gfr_resid_var,
  ckd_epi_race_coeff
)
```

Arguments

nsamp	The desired number of individuals in the virtual population. nsamp need not be provided if gendernum is provided.
gendernum	Optional: A named list giving the numbers of male and female individuals to include in the population, e.g. <code>list(Male=100,Female=100)</code> . Default is NULL, meaning both males and females are included, in their proportions in the NHANES data. If both nsamp and gendernum are provided, they must agree (i.e., nsamp must be the sum of gendernum).
agelim_months	Optional: A two-element numeric vector giving the minimum and maximum ages (in months) to include in the population. Default is <code>c(0, 959)</code> , equivalent to the default agelim_years. If agelim_months is provided and agelim_years is not, agelim_months will override the default values of agelim_years.
agelim_years	Optional: A two-element numeric vector giving the minimum and maximum ages (in years) to include in the population. Default is <code>c(0,79)</code> . If agelim_years is provided and agelim_months is not, agelim_years will override the default value of agelim_months.
reths	Optional: a character vector giving the races/ethnicities to include in the population. Default is <code>c('Mexican American', 'Other Hispanic', 'Non-Hispanic White', 'Non-Hispanic Black', 'Other')</code> , to include all races and ethnicities in their proportions in the NHANES data. User-supplied vector must contain one or more of these strings.

weight_category Optional: The weight categories to include in the population. Default is `c('Underweight', 'Normal', 'Overweight', 'Obese')`. User-supplied vector must contain one or more of these strings.

gfr_resid_var Logical value indicating whether or not to include residual variability when generating GFR values. (Default is TRUE, passed from `'httkpop_direct_resample'`.)

ckd_epi_race_coeff Logical value indicating whether or not to use the "race coefficient" from the CKD-EPI equation when estimating GFR values. (Default is FALSE, passed from `'httkpop_direct_resample'`.)

Value

A data.table where each row represents an individual, and each column represents a demographic, anthropometric, or physiological parameter.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

httkpop_generate	<i>Generate a virtual population</i>
------------------	--------------------------------------

Description

Generate a virtual population

Usage

```
httkpop_generate(
  method = "direct resampling",
  nsamp = NULL,
  gendernum = NULL,
  agelim_years = NULL,
  agelim_months = NULL,
  weight_category = c("Underweight", "Normal", "Overweight", "Obese"),
  gfr_category = c("Normal", "Kidney Disease", "Kidney Failure"),
  reths = c("Mexican American", "Other Hispanic", "Non-Hispanic White",
    "Non-Hispanic Black", "Other"),
  gfr_resid_var = TRUE,
  ckd_epi_race_coeff = FALSE
)
```


Arguments

method	The population-generation method to use. Either "virtual individuals" or "direct resampling." Short names may be used: "d" or "dr" for "direct resampling", and "v" or "vi" for "virtual individuals".
nsamp	The desired number of individuals in the virtual population. nsamp need not be provided if gendernum is provided.
gendernum	Optional: A named list giving the numbers of male and female individuals to include in the population, e.g. <code>list(Male=100,Female=100)</code> . Default is NULL, meaning both males and females are included, in their proportions in the NHANES data. If both nsamp and gendernum are provided, they must agree (i.e., nsamp must be the sum of gendernum).
agelim_years	Optional: A two-element numeric vector giving the minimum and maximum ages (in years) to include in the population. Default is <code>c(0,79)</code> . If only a single value is provided, both minimum and maximum ages will be set to that value; e.g. <code>agelim_years=3</code> is equivalent to <code>agelim_years=c(3,3)</code> . If <code>agelim_years</code> is provided and <code>agelim_months</code> is not, <code>agelim_years</code> will override the default value of <code>agelim_months</code> .
agelim_months	Optional: A two-element numeric vector giving the minimum and maximum ages (in months) to include in the population. Default is <code>c(0, 959)</code> , equivalent to the default <code>agelim_years</code> . If only a single value is provided, both minimum and maximum ages will be set to that value; e.g. <code>agelim_months=36</code> is equivalent to <code>agelim_months=c(36,36)</code> . If <code>agelim_months</code> is provided and <code>agelim_years</code> is not, <code>agelim_months</code> will override the default values of <code>agelim_years</code> .
weight_category	Optional: The weight categories to include in the population. Default is <code>c('Underweight', 'Normal', 'Overweight', 'Obese')</code> . User-supplied vector must contain one or more of these strings.
gfr_category	The kidney function categories to include in the population. Default is <code>c('Normal', 'Kidney Disease', 'Kidney Failure')</code> to include all kidney function levels.
reths	Optional: a character vector giving the races/ethnicities to include in the population. Default is <code>c('Mexican American', 'Other Hispanic', 'Non-Hispanic White', 'Non-Hispanic Black', 'Other')</code> , to include all races and ethnicities in their proportions in the NHANES data. User-supplied vector must contain one or more of these strings.
gfr_resid_var	TRUE to add residual variability to GFR predicted from serum creatinine; FALSE to not add residual variability
ckd_epi_race_coeff	TRUE to use the CKD-EPI equation as originally published (with a coefficient changing predicted GFR for individuals identified as "Non-Hispanic Black"); FALSE to set this coefficient to 1.

Value

A data.table where each row represents an individual, and each column represents a demographic, anthropometric, or physiological parameter.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

Examples

```
#Simply generate a virtual population of 100 individuals,
#using the direct-resampling method
set.seed(42)
httkpop_generate(method='direct resampling', nsamp=100)
#Generate a population using the virtual-individuals method,
#include 80 females and 20 males,
#include only ages 20-65,
#include only Mexican American and
#Non-Hispanic Black individuals,
#include only non-obese individuals
httkpop_generate(method = 'virtual individuals',
  gendernum=list(Female=80,
    Male=20),
  agelim_years=c(20,65),
  reths=c('Mexican American',
    'Non-Hispanic Black'),
  weight_category=c('Underweight',
    'Normal',
    'Overweight'))
```

httkpop_mc

Converts the HTTK-Pop population data table to a table of the parameters needed by HTTK, for a specific chemical.

Description

Takes the data table generated by [httkpop_generate](#), and converts it to the corresponding table of HTTK model parameters for a specified chemical and HTTK model.

Usage

```
httkpop_mc(model, samples = 1000, httkpop.dt = NULL, ...)
```

Arguments

model	One of the HTTK models: "1compartment", "3compartmentss", "3compartment", or "pbtk".
samples	The number of Monte Carlo samples to use (can often think of these as separate individuals)
httkpop.dt	A data table generated by httkpop_generate . This defaults to NULL, in which case httkpop_generate is called to generate this table.
...	Additional arguments passed on to httkpop_generate .

Value

A data.table with a row for each individual in the sample and a column for each parameter in the model.

Author(s)

Caroline Ring and John Wambaugh

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

Rowland, Malcolm, Leslie Z. Benet, and Garry G. Graham. "Clearance concepts in pharmacokinetics." *Journal of Pharmacokinetics and Biopharmaceutics* 1.2 (1973): 123-136.

Examples

```
set.seed(42)
indiv_examp <- httkpop_generate(method="d", nsamp=100)
httk_param <- httkpop_mc(httkpop.dt=indiv_examp,
model="1compartment")
```

httkpop_virtual_indiv *Generate a virtual population by the virtual individuals method.*

Description

Generate a virtual population by the virtual individuals method.

Usage

```
httkpop_virtual_indiv(
  nsamp = NULL,
  gendernum = NULL,
  agelim_years = c(0, 79),
  agelim_months = c(0, 959),
  weight_category = c("Underweight", "Normal", "Overweight", "Obese"),
  gfr_category = c("Normal", "Kidney Disease", "Kidney Failure"),
  reths = c("Mexican American", "Other Hispanic", "Non-Hispanic White",
    "Non-Hispanic Black", "Other"),
  gfr_resid_var = TRUE,
  ckd_epi_race_coeff = FALSE
)
```

Arguments

nsamp	The desired number of individuals in the virtual population. nsamp need not be provided if gendernum is provided.
-------	---

gendernum	Optional: A named list giving the numbers of male and female individuals to include in the population, e.g. <code>list(Male=100,Female=100)</code> . Default is NULL, meaning both males and females are included, in their proportions in the NHANES data. If both <code>nsamp</code> and <code>gendernum</code> are provided, they must agree (i.e., <code>nsamp</code> must be the sum of <code>gendernum</code>).
agelim_years	Optional: A two-element numeric vector giving the minimum and maximum ages (in years) to include in the population. Default is <code>c(0,79)</code> . If <code>agelim_years</code> is provided and <code>agelim_months</code> is not, <code>agelim_years</code> will override the default value of <code>agelim_months</code> .
agelim_months	Optional: A two-element numeric vector giving the minimum and maximum ages (in months) to include in the population. Default is <code>c(0, 959)</code> , equivalent to the default <code>agelim_years</code> . If <code>agelim_months</code> is provided and <code>agelim_years</code> is not, <code>agelim_months</code> will override the default values of <code>agelim_years</code> .
weight_category	Optional: The weight categories to include in the population. Default is <code>c('Underweight', 'Normal', 'Overweight', 'Obese')</code> . User-supplied vector must contain one or more of these strings.
gfr_category	The kidney function categories to include in the population. Default is <code>c('Normal', 'Kidney Disease', 'Kidney Failure')</code> to include all kidney function levels.
reths	Optional: a character vector giving the races/ethnicities to include in the population. Default is <code>c('Mexican American', 'Other Hispanic', 'Non-Hispanic White', 'Non-Hispanic Black', 'Other')</code> , to include all races and ethnicities in their proportions in the NHANES data. User-supplied vector must contain one or more of these strings.
gfr_resid_var	Logical value indicating whether or not to include residual variability when generating GFR values. (Default is TRUE.)
ckd_epi_race_coeff	Logical value indicating whether or not to use the "race coefficient" from the CKD-EPI equation when estimating GFR values. (Default is FALSE.)

Value

A `data.table` where each row represents an individual, and each column represents a demographic, anthropometric, or physiological parameter.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

`in.list`*Convenience Boolean (yes/no) functions to identify chemical membership in several key lists.*

Description

These functions allow easy identification of whether or not a chemical CAS is included in various research projects. While it is our intent to keep these lists up-to-date, the information here is only for convenience and should not be considered to be definitive.

Usage

```
in.list(chem.cas = NULL, which.list = "ToxCast")
```

Arguments

`chem.cas` The Chemical Abstracts Service Registry Number (CAS-RN) corresponding to the chemical of interest.

`which.list` A character string that can take the following values: "ToxCast", "Tox21", "ExpoCast", "NHANES", "NHANES.serum.parent", "NHANES.serum.analyte", "NHANES.blood.parent", "NHANES.urine.parent", "NHANES.urine.analyte"

Details

Tox21: Toxicology in the 21st Century (Tox21) is a U.S. federal High Throughput Screening (HTS) collaboration among EPA, NIH, including National Center for Advancing Translational Sciences and the National Toxicology Program at the National Institute of Environmental Health Sciences, and the Food and Drug Administration. (Bucher et al., 2008)

ToxCast: The Toxicity Forecaster (ToxCast) is a HTS screening project led by the U.S. EPA to perform additional testing of a subset of Tox21 chemicals. (Judson et al. 2010)

ExpoCast: ExpoCast (Exposure Forecaster) is an U.S. EPA research project to generate tentative exposure estimates (e.g., mg/kg BW/day) for thousands of chemicals that have little other information using models and informatics. (Wambaugh et al. 2014)

NHANES: The U.S. Centers for Disease Control (CDC) National Health and Nutrition Examination Survey (NHANES) is an on-going survey to characterize the health and biometrics (e.g., weight, height) of the U.S. population. One set of measurements includes the quantification of xenobiotic chemicals in various samples (blood, serum, urine) of the thousands of surveyed individuals. (CDC, 2014)

Value

`logical` A Boolean (1/0) value that is TRUE if the chemical is in the list.

Author(s)

John Wambaugh

References

Bucher, J. R. (2008). Guest Editorial: NTP: New Initiatives, New Alignment. *Environ Health Perspect* 116(1).

Judson, R. S., Houck, K. A., Kavlock, R. J., Knudsen, T. B., Martin, M. T., Mortensen, H. M., Reif, D. M., Rotroff, D. M., Shah, I., Richard, A. M. and Dix, D. J. (2010). In Vitro Screening of Environmental Chemicals for Targeted Testing Prioritization: The ToxCast Project. *Environmental Health Perspectives* 118(4), 485-492.

Wambaugh, J. F., Wang, A., Dionisio, K. L., Frame, A., Egeghy, P., Judson, R. and Setzer, R. W. (2014). High Throughput Heuristics for Prioritizing Human Exposure to Environmental Chemicals. *Environmental Science & Technology*, 10.1021/es503583j.

CDC (2014). National Health and Nutrition Examination Survey. Available at: <https://www.cdc.gov/nchs/nhanes.htm>.

See Also

[is.httk](#) for determining inclusion in httk project

Examples

```
httk.table <- get_cheminfo(info=c("CAS", "Compound"))
httk.table[, "Rat"] <- ""
httk.table[, "NHANES"] <- ""
httk.table[, "Tox21"] <- ""
httk.table[, "ToxCast"] <- ""
httk.table[, "ExpoCast"] <- ""
httk.table[, "PBTk"] <- ""
# To make this example run quickly, this loop is only over the first five
# chemicals. To build a table with all available chemicals use:
# for (this.cas in httk.table$CAS)
for (this.cas in httk.table$CAS[1:5])
{
  this.index <- httk.table$CAS==this.cas
  if (is.nhanes(this.cas)) httk.table[this.index, "NHANES"] <- "Y"
  if (is.tox21(this.cas)) httk.table[this.index, "Tox21"] <- "Y"
  if (is.toxcast(this.cas)) httk.table[this.index, "ToxCast"] <- "Y"
  if (is.expcast(this.cas)) httk.table[this.index, "ExpoCast"] <- "Y"
  if (is.httk(this.cas, model="PBTk")) httk.table[this.index, "PBTk"] <- "Y"
  if (is.httk(this.cas, species="rat")) httk.table[this.index, "Rat"] <- "Y"
}
```

invitro_mc

Draw in vitro TK parameters including uncertainty and variability.

Description

Given a CAS in the HTTK data set, a virtual population from HTTK-Pop, some user specifications on the assumed distributions of Funbound.plasma and Clint, draw "individual" values of Funbound.plasma and Clint from those distributions.

Usage

```

invitro_mc(
  parameters.dt = NULL,
  samples,
  fup.meas.cv = 0.4,
  clint.meas.cv = 0.3,
  fup.pop.cv = 0.3,
  clint.pop.cv = 0.3,
  poormetab = TRUE,
  fup.lod = 0.01,
  fup.censored.dist = FALSE,
  adjusted.Funbound.plasma = TRUE,
  clint.pvalue.threshold = 0.05,
  minimum.Funbound.plasma = 1e-04
)

```

Arguments

parameters.dt	A data table of physiological parameters
samples	The number of samples to draw.
fup.meas.cv	Coefficient of variation of distribution of measured Funbound.plasma values.
clint.meas.cv	Coefficient of variation of distribution of measured Clint values.
fup.pop.cv	Coefficient of variation of distribution of population Funbound.plasma values.
clint.pop.cv	Coefficient of variation of distribution of population Clint values.
poormetab	Logical. Whether to include poor metabolizers in the Clint distribution or not.
fup.lod	The average limit of detection for Funbound.plasma, below which distribution will be censored if fup.censored.dist is TRUE. Default 0.01.
fup.censored.dist	Logical. Whether to draw Funbound.plasma from a censored distribution or not.
adjusted.Funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE.
clint.pvalue.threshold	Hepatic clearance for chemicals where the in vitro clearance assay result has a p-values greater than the threshold are set to zero.
minimum.Funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).
parameters	A list of chemical-specific model parameters containing at least Funbound.plasma, Clint, and Fhep.assay.correction.

Value

A data.table with three columns: Funbound.plasma and Clint, containing the sampled values, and Fhep.assay.correction, containing the value for fraction unbound in hepatocyte assay.

Author(s)

Caroline Ring and John Wambaugh

References

Wambaugh, John F., et al. "Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization." *Toxicological Sciences* (2019).

is.httk

Convenience Boolean (yes/no) function to identify chemical membership and treatment within the httk project.

Description

Allows easy identification of whether or not a chemical CAS is included in various aspects of the httk research project (by model type and species of interest). While it is our intent to keep these lists up-to-date, the information here is only for convenience and should not be considered definitive.

Usage

```
is.httk(chem.cas, species = "Human", model = "3compartmentss")
```

Arguments

chem.cas	The Chemical Abstracts Service Registry Number (CAS-RN) corresponding to the chemical of interest.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
model	Model used in calculation, 'pbtk' for the multiple compartment model, '1compartment' for the one compartment model, '3compartment' for three compartment model, '3compartmentss' for the three compartment model without partition coefficients, or 'schmitt' for chemicals with logP and fraction unbound (used in predict_partitioning_schmitt).

Details

Tox21: Toxicology in the 21st Century (Tox21) is a U.S. federal High Throughput Screening (HTS) collaboration among EPA, NIH, including National Center for Advancing Translational Sciences and the National Toxicology Program at the National Institute of Environmental Health Sciences, and the Food and Drug Administration. (Bucher et al., 2008)

ToxCast: The Toxicity Forecaster (ToxCast) is a HTS screening project led by the U.S. EPA to perform additional testing of a subset of Tox21 chemicals. (Judson et al. 2010)

ExpoCast: ExpoCast (Exposure Forecaster) is an U.S. EPA research project to generate tentative exposure estimates (e.g., mg/kg BW/day) for thousands of chemicals that have little other information using models and informatics. (Wambaugh et al. 2014)

NHANES: The U.S. Centers for Disease Control (CDC) National Health and Nutrition Examination Survey (NHANES) is an on-going survey to characterize the health and biometrics (e.g., weight, height) of the U.S. population. One set of measurements includes the quantification of xenobiotic chemicals in various samples (blood, serum, urine) of the thousands of surveyed individuals. (CDC, 2014)

Value

logical	A Boolean (1/0) value that is TRUE if the chemical is included in the httk project with a given modeling scheme (PBTK) and a given species
---------	--

Author(s)

John Wambaugh

References

Bucher, J. R. (2008). Guest Editorial: NTP: New Initiatives, New Alignment. *Environ Health Perspect* 116(1).

Judson, R. S., Houck, K. A., Kavlock, R. J., Knudsen, T. B., Martin, M. T., Mortensen, H. M., Reif, D. M., Rotroff, D. M., Shah, I., Richard, A. M. and Dix, D. J. (2010). In Vitro Screening of Environmental Chemicals for Targeted Testing Prioritization: The ToxCast Project. *Environmental Health Perspectives* 118(4), 485-492.

Wambaugh, J. F., Wang, A., Dionisio, K. L., Frame, A., Egeghy, P., Judson, R. and Setzer, R. W. (2014). High Throughput Heuristics for Prioritizing Human Exposure to Environmental Chemicals. *Environmental Science & Technology*, 10.1021/es503583j.

CDC (2014). National Health and Nutrition Examination Survey. Available at: <https://www.cdc.gov/nchs/nhanes.htm>.

See Also

[in.list](#) for determining chemical membership in several other key lists

Examples

```
httk.table <- get_cheminfo(info=c("CAS", "Compound"))
httk.table[, "Rat"] <- ""
httk.table[, "NHANES"] <- ""
httk.table[, "Tox21"] <- ""
httk.table[, "ToxCast"] <- ""
httk.table[, "ExpoCast"] <- ""
httk.table[, "PBTk"] <- ""
# To make this example run quickly, this loop is only over the first five
# chemicals. To build a table with all available chemicals use:
# for (this.cas in httk.table$CAS)
for (this.cas in httk.table$CAS[1:5])
{
  this.index <- httk.table$CAS==this.cas
  if (is.nhanes(this.cas)) httk.table[this.index, "NHANES"] <- "Y"
  if (is.tox21(this.cas)) httk.table[this.index, "Tox21"] <- "Y"
  if (is.toxcast(this.cas)) httk.table[this.index, "ToxCast"] <- "Y"
  if (is.expocast(this.cas)) httk.table[this.index, "ExpoCast"] <- "Y"
  if (is.httk(this.cas, model="PBTk")) httk.table[this.index, "PBTk"] <- "Y"
  if (is.httk(this.cas, species="rat")) httk.table[this.index, "Rat"] <- "Y"
}
```

<code>is_in_inclusive</code>	<i>Checks whether a value, or all values in a vector, is within inclusive limits</i>
------------------------------	--

Description

Checks whether a value, or all values in a vector, is within inclusive limits

Usage

```
is_in_inclusive(x, lims)
```

Arguments

<code>x</code>	A numeric value, or vector of values.
<code>lims</code>	A two-element vector of (min, max) values for the inclusive limits. If <code>x</code> is a vector, <code>lims</code> may also be a two-column matrix with <code>nrow=length(x)</code> where the first column is lower limits and the second column is upper limits. If <code>x</code> is a vector and <code>lims</code> is a two-element vector, then each element of <code>x</code> will be checked against the same limits. If <code>x</code> is a vector and <code>lims</code> is a matrix, then each element of <code>x</code> will be checked against the limits given by the corresponding row of <code>lims</code> .

Value

A logical vector the same length as `x`, indicating whether each element of `x` is within the inclusive limits given by `lims`.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

johnson	<i>Johnson 2006</i>
---------	---------------------

Description

This data set is only used in Vignette 5.

Usage

```
johnson
```

Format

A `data.table` containing 60 rows and 11 columns.

Author(s)

Caroline Ring

References

Johnson, Trevor N., Amin Rostami-Hodjegan, and Geoffrey T. Tucker. "Prediction of the clearance of eleven drugs and associated variability in neonates, infants and children." *Clinical pharmacokinetics* 45.9 (2006): 931-956.

kapraun2019

Kapraun et al. 2019 data

Description

A list object containing time-varying parameters for the human maternal-fetal HTTK model. List elements contain scalar coefficients for the polynomial, logistic, Gompertz, and other functions of time describing blood flow rates, tissue volumes, hematocrits, and other anatomical/physiological quantities that change in the human mother and her fetus during pregnancy and gestation.

Usage

kapraun2019

Format

list

Author(s)

Dustin F. Kapraun

Source

Kapraun et al. 2019 Fetal PBTK Model

References

Kapraun DF, Wambaugh JF, Setzer RW, Judson RS (2019). "Empirical models for anatomical and physiological changes in a human mother and fetus during pregnancy and gestation." *PLOS ONE*, **14**(5), 1–56. doi: [10.1371/journal.pone.0215906](https://doi.org/10.1371/journal.pone.0215906).

kidney_mass_children *Predict kidney mass for children*

Description

For individuals under age 18, predict kidney mass from weight, height, and gender. using equations from Ogiu et al. 1997

Usage

```
kidney_mass_children(weight, height, gender)
```

Arguments

weight	Vector of weights in kg.
height	Vector of heights in cm.
gender	Vector of genders (either 'Male' or 'Female').

Value

A vector of kidney masses in kg.

Author(s)

Caroline Ring

References

Ogiu, Nobuko, et al. "A statistical analysis of the internal organ weights of normal Japanese people." Health physics 72.3 (1997): 368-383.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

liver_mass_children *Predict liver mass for children*

Description

For individuals under 18, predict the liver mass from height, weight, and gender, using equations from Ogiu et al. 1997

Usage

```
liver_mass_children(height, weight, gender)
```

Arguments

height	Vector of heights in cm.
weight	Vector of weights in kg.
gender	Vector of genders (either 'Male' or 'Female').

Value

A vector of liver masses in kg.

Author(s)

Caroline Ring

References

Ogiu, Nobuko, et al. "A statistical analysis of the internal organ weights of normal Japanese people." Health physics 72.3 (1997): 368-383.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

load_dawson2021

Load data from Dawson et al. 2021.

Description

This function returns an updated version of chem.physical_and_invitro.data that includes data predicted with Random Forest QSAR models developed and presented in Dawson et al. 2021, included in dawson2021.

Usage

```
load_dawson2021(overwrite = FALSE, exclude_oad = TRUE, target.env = .GlobalEnv)
```

Arguments

overwrite	Only matters if load.image=FALSE. If overwrite=TRUE then existing data in chem.physical_and_invitro.data will be replaced by any data/predictions in Dawson et al. (2021) that is for the same chemical and property. If overwrite=FALSE (DEFAULT) then new data for the same chemical and property are ignored. Fun-bound.plasma values of 0 (below limit of detection) are overwritten either way.
exclude_oad	Include the chemicals only within the applicability domain. If exlude_oad=TRUE (DEFAULT) chemicals outside the applicability domain do not have their predicted values loaded.
target.env	The environment where the new chem.physical_and_invitro.data is loaded. Defaults to global environment.

Value

data.frame An updated version of chem.physical_and_invitro.data.

Author(s)

Sarah E. Davidson

References

Dawson DE, Ingle BL, Phillips KA, Nichols JW, Wambaugh JF, Tornero-Velez R (2021). “Designing QSARs for Parameters of High-Throughput Toxicokinetic Models Using Open-Source Descriptors.” *Environmental Science & Technology*, **55**(9), 6505–6517. doi: [10.1021/acs.est.0c06117](https://doi.org/10.1021/acs.est.0c06117), PMID: 33856768.

Examples

```
## Not run:
chem.physical_and_invitro.data <- load_dawson2021()
chem.physical_and_invitro.data <- load_dawson2021(overwrite=TRUE)

## End(Not run)
```

load_pradeep2020	<i>Load data from Pradeep et al. 2020.</i>
------------------	--

Description

This function returns an updated version of chem.physical_and_invitro.data that includes data predicted with Support Vector Machine and Random Forest models developed and presented in Pradeep et al. 2020, included in pradeep2020.

Usage

```
load_pradeep2020(overwrite = FALSE, target.env = .GlobalEnv)
```

Arguments

overwrite	Only matters if load.image=FALSE. If overwrite=TRUE then existing data in chem.physical_and_invitro.data will be replaced by any data/predictions in Pradeep et al. (2020) that is for the same chemical and property. If overwrite=FALSE (DEFAULT) then new data for the same chemical and property are ignored. Funbound.plasma values of 0 (below limit of detection) are overwritten either way.
target.env	The environment where the new chem.physical_and_invitro.data is loaded. Defaults to global environment.

Value

data.frame	An updated version of chem.physical_and_invitro.data.
------------	---

Author(s)

Sarah E. Davidson

References

Pradeep P, Patlewicz G, Pearce R, Wambaugh J, Wetmore B, Judson R (2020). "Using chemical structure information to develop predictive models for in vitro toxicokinetic parameters to inform high-throughput risk-assessment." *Computational Toxicology*, **16**, 100136. ISSN 2468-1113, doi: [10.1016/j.comtox.2020.100136](https://doi.org/10.1016/j.comtox.2020.100136), <https://www.sciencedirect.com/science/article/pii/S2468111320300463>.

Examples

```
## Not run:
chem.physical_and_invitro.data <- load_pradeep2020()
chem.physical_and_invitro.data <- load_pradeep2020(overwrite=TRUE)

## End(Not run)
```

load_sipes2017	<i>Load data from Sipes et al 2017.</i>
----------------	---

Description

This function returns an updated version of chem.physical_and_invitro.data that includes data predicted with Simulations Plus' ADMET predictor that was used in Sipes et al. 2017, included in admet.data.

Usage

```
load_sipes2017(overwrite = FALSE, target.env = .GlobalEnv)
```

Arguments

overwrite	Only matters if load.image=FALSE. If overwrite=TRUE then existing data in chem.physical_and_invitro.data will be replaced by any data/predictions in Sipes et al. (2017) that is for the same chemical and property. If overwrite=FALSE (DEFAULT) then new data for the same chemical and property are ignored. Funbound.plasma values of 0 (below limit of detection) are overwritten either way.
target.env	The environment where the new chem.physical_and_invitro.data is loaded. Defaults to global environment.

Value

data.frame	An updated version of chem.physical_and_invitro.data.
------------	---

Author(s)

Robert Pearce and John Wambaugh

References

Sipes, Nisha S., et al. "An intuitive approach for predicting potential human health risk with the Tox21 10k library." *Environmental Science & Technology* 51.18 (2017): 10786-10796.

Examples

```
num.chems <- length(get_cheminfo())
load_sipes2017()

#We should have the ADMet Predicted chemicals from Sipes et al. (2017),
#this one is a good test since the logP is nearly 10
calc_css(chem.cas="26040-51-7")

#Let's see how many chemicals we have now with the Sipes (2017) data loaded:
length(get_cheminfo())

#Now let us reset
reset_httk()

# We should be back to our original number:
num.chems == length(get_cheminfo())
```

lump_tissues

Lump tissue parameters

Description

This function takes the parameters from `predict_partitioning_schmitt` and lumps the partition coefficients along with the volumes and flows based on the given tissue list. It is useful in Monte Carlo simulation of individual partition coefficients when calculating the rest of body partition coefficient.

Usage

```
lump_tissues(
  Ktissue2pu.in,
  parameters = NULL,
  tissuelist = NULL,
  species = "Human",
  tissue.vols = NULL,
  tissue.flows = NULL,
  model = "pbtk",
  suppress.messages = FALSE
)
```

Arguments

<code>Ktissue2pu.in</code>	List of partition coefficients from <code>predict_partitioning_schmitt</code> .
<code>parameters</code>	A list of physiological parameters including flows and volumes for tissues in <code>tissuelist</code>
<code>tissuelist</code>	Manually specifies compartment names and tissues, which override the standard compartment names and tissues that are usually specified in a model's associated <code>modelinfo</code> file. Remaining tissues in the model's associated <code>alltissues</code> listing are lumped in the rest of the body.

species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
tissue.vols	A list of volumes for tissues in tissuelist
tissue.flows	A list of flows for tissues in tissuelist
model	Specify which model (and therefore which tissues) are being considered
suppress.messages	Whether or not the output message is suppressed.

Details

This function returns the flows, volumes, and partition coefficients for the lumped tissues specified in tissue list `Ktissue2plasma` – tissue to free plasma concentration partition coefficients for every tissue specified by Schmitt (2008) (the `tissue.data` table) `tissuelist` – a list of character vectors, the name of each entry in the list is its own compartment. The tissues in the `alltissues` vector are the Schmitt (2008) tissues that are to be considered in the lumping process. The `tissuelist` can also be manually specified for alternate lumping schemes: for example, `tissuelist<-list(Rapid=c("Brain","Kidney"))` specifies the `flow.col` and `vol.col` in the `tissuedata.table`.

Value

<code>Krbc2pu</code>	Ratio of concentration of chemical in red blood cells to unbound concentration in plasma.
<code>Krest2pu</code>	Ratio of concentration of chemical in rest of body tissue to unbound concentration in plasma.
<code>Vrestc</code>	Volume of the rest of the body per kg body weight, L/kg BW.
<code>Vliverc</code>	Volume of the liver per kg body weight, L/kg BW.
<code>Qttotal.liverf</code>	Fraction of cardiac output flowing to the gut and liver, i.e. out of the liver.
<code>Qgutf</code>	Fraction of cardiac output flowing to the gut.
<code>Qkidneyf</code>	Fraction of cardiac output flowing to the kidneys.

Author(s)

John Wambaugh and Robert Pearce

References

Pearce, Robert G., et al. "Evaluation and calibration of high-throughput predictions of chemical distribution to tissues." *Journal of pharmacokinetics and pharmacodynamics* 44.6 (2017): 549-565.

Examples

```
pcs <- predict_partitioning_schmitt(chem.name='bisphenola')
tissuelist <- list(liver=c("liver"),kidney=c("kidney"),lung=c("lung"),gut=c("gut"),
,muscle.bone=c('muscle','bone'))
lump_tissues(pcs,tissuelist=tissuelist)
```

lung_mass_children	<i>Predict lung mass for children</i>
--------------------	---------------------------------------

Description

For individuals under 18, predict the liver mass from height, weight, and gender, using equations from Ogiu et al. 1997

Usage

```
lung_mass_children(height, weight, gender)
```

Arguments

height	Vector of heights in cm.
weight	Vector of weights in kg.
gender	Vector of genders (either 'Male' or 'Female').

Value

A vector of lung masses in kg.

Author(s)

Caroline Ring

References

Ogiu, Nobuko, et al. "A statistical analysis of the internal organ weights of normal Japanese people." *Health physics* 72.3 (1997): 368-383.

Price, Paul S., et al. "Modeling interindividual variation in physiological factors used in PBPK models of humans." *Critical reviews in toxicology* 33.5 (2003): 469-503.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

mcnally_dt	<i>Reference tissue masses and flows from tables in McNally et al. 2014.</i>
------------	--

Description

Reference tissue masses, flows, and marginal distributions from McNally et al. 2014.

Usage

```
mcnally_dt
```

Format

A data.table with variables:

tissue Body tissue

gender Gender: Male or Female

mass_ref Reference mass in kg, from Reference Man

mass_cv Coefficient of variation for mass

mass_dist Distribution for mass: Normal or Log-normal

flow_ref Reference flow in L/h, from Reference Man

flow_cv Coefficient of variation for flow (all normally distributed)

height_ref Reference heights (by gender)

CO_ref Reference cardiac output by gender

flow_frac Fraction of CO flowing to each tissue: flow_ref/CO_ref

Author(s)

Caroline Ring

Source

McNally K, Cotton R, Hogg A, Loizou G. "PopGen: A virtual human population generator." Toxicology 315, 70-85, 2004.

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

metabolism_data_Linakis2020

Metabolism data involved in Linakis 2020 vignette analysis.

Description

Metabolism data involved in Linakis 2020 vignette analysis.

Usage

metabolism_data_Linakis2020

Format

A data.frame containing x rows and y columns.

Author(s)

Matt Linakis

Source

Matt Linakis

References

DSStox database ([https:// www.epa.gov/ncct/dsstox](https://www.epa.gov/ncct/dsstox))

monte_carlo	<i>Monte Carlo for pharmacokinetic models</i>
-------------	---

Description

This function performs Monte Carlo to assess uncertainty and variability for toxicokinetic models.

Usage

```
monte_carlo(  
  parameters,  
  cv.params = NULL,  
  censored.params = NULL,  
  samples = 1000  
)
```

Arguments

parameters	These parameters that are also listed in either cv.params or censored.params are sampled using Monte Carlo.
cv.params	The parameters listed in cv.params are sampled from a normal distribution that is truncated at zero. This argument should be a list of coefficients of variation (cv) for the normal distribution. Each entry in the list is named for a parameter in "parameters". New values are sampled with mean equal to the value in "parameters" and standard deviation equal to the mean times the cv.
censored.params	The parameters listed in censored.params are sampled from a normal distribution that is censored for values less than the limit of detection (specified separately for each parameter). This argument should be a list of sub-lists. Each sublist is named for a parameter in "params" and contains two elements: "cv" (coefficient of variation) and "LOD" (limit of detection), below which parameter values are censored. New values are sampled with mean equal to the value in "params" and standard deviation equal to the mean times the cv. Censored values are sampled on a uniform distribution between 0 and the limit of detection.
samples	This argument is the number of samples to be generated for calculating quantiles.

Value

A data.table with a row for each individual in the sample and a column for each parameter in the model.

Author(s)

John Wambaugh

References

Pearce, Robert G., et al. "Htk: R package for high-throughput toxicokinetics." Journal of statistical software 79.4 (2017): 1.

Examples

```
#Example based on Pearce et al. (2017):

# Set up means:
params <- parameterize_pbt(chem.name="zoxamide")
# Nothing changes:
monte_carlo(params)

vary.params <- NULL
for (this.param in names(params)[!(names(params) %in%
  c("Funbound.plasma", "pKa_Donor", "pKa_Accept" )) &
  !is.na(as.numeric(params))]) vary.params[this.param] <- 0.2
# Most everything varies with CV of 0.2:
monte_carlo(
  parameters=params,
  cv.params = vary.params)

censored.params <- list(Funbound.plasma = list(cv = 0.2, lod = 0.01))
# Fup is censored below 0.01:
monte_carlo(
  parameters=params,
  cv.params = vary.params,
  censored.params = censored.params)
```

nhanes_mec_svy

Pre-processed NHANES data.

Description

NHANES data on demographics, anthropometrics, and some laboratory measures, cleaned and combined into a single data set.

Usage

```
nhanes_mec_svy
```

Format

A survey.design2 object, including masked cluster and strata. Variables are available as a data.table by nhanes_mec_svy\$variables. Variables are as described in NHANES Demographics and Examination documentation, with the exception of:

wtmec6yr 6-year sample weights for combining 3 cycles, computed by dividing 2-year sample weights by 3.

bmxhtlenavg Average of height and recumbent length if both were measured; if only one was measured, takes value of the one that was measured.

logbmwt Natural log of measured body weight.

logbmhtlenavg Natural log of bmxhtlenavg.

weight_class One of Underweight, Normal, Overweight, or Obese. Assigned using methods in `get_weight_class`.

Author(s)

Caroline Ring

Source

<https://www.cdc.gov/nchs/nhanes/Default.aspx>

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

Obach2008

Published Pharmacokinetic Parameters from Obach et al. 2008

Description

This data set is used in Vignette 4 for steady state concentration.

Usage

Obach2008

Format

A data.frame containing 670 rows and 8 columns.

References

Obach, R. Scott, Franco Lombardo, and Nigel J. Waters. "Trend analysis of a database of intravenous pharmacokinetic parameters in humans for 670 drug compounds." *Drug Metabolism and Disposition* 36.7 (2008): 1385-1405.

onlyp

NHANES Exposure Data

Description

This data set is only used in Vignette 6.

Usage

onlyp

Format

A data.table containing 1060 rows and 5 columns.

Author(s)

Caroline Ring

References

Wambaugh, John F., et al. "High throughput heuristics for prioritizing human exposure to environmental chemicals." *Environmental science & technology* 48.21 (2014): 12760-12767.

pancreas_mass_children

Predict pancreas mass for children

Description

For individuals under 18, predict the pancreas mass from height, weight, and gender, using equations from Ogiu et al.

Usage

```
pancreas_mass_children(height, weight, gender)
```

Arguments

height	Vector of heights in cm.
weight	Vector of weights in kg.
gender	Vector of genders (either 'Male' or 'Female').

Value

A vector of pancreas masses in kg.

Author(s)

Caroline Ring

References

Ogiu, Nobuko, et al. "A statistical analysis of the internal organ weights of normal Japanese people." Health physics 72.3 (1997): 368-383.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

parameterize_1comp	<i>Parameterize_1comp</i>
--------------------	---------------------------

Description

This function initializes the parameters needed in the function solve_1comp.

Usage

```
parameterize_1comp(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  species = "Human",
  default.to.human = FALSE,
  adjusted.Funbound.plasma = TRUE,
  regression = TRUE,
  restrictive.clearance = TRUE,
  well.stirred.correction = TRUE,
  suppress.messages = FALSE,
  clint.pvalue.threshold = 0.05,
  minimum.Funbound.plasma = 1e-04
)
```

Arguments

chem.cas	Chemical Abstract Services Registry Number (CAS-RN) – the chemical must be identified by either CAS, name, or DTXISD
chem.name	Chemical name (spaces and capitalization ignored) – the chemical must be identified by either CAS, name, or DTXISD
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) – the chemical must be identified by either CAS, name, or DTXSIDs
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
default.to.human	Substitutes missing rat values with human values if true.
adjusted.Funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with volume of distribution calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients in volume of distribution calculation.
restrictive.clearance	In calculating elimination rate and hepatic bioavailability, protein binding is not taken into account (set to 1) in liver clearance if FALSE.

well.stirred.correction	Uses correction in calculation of hepatic clearance for well-stirred model if TRUE. This assumes clearance relative to amount unbound in whole blood instead of plasma, but converted to use with plasma concentration.
suppress.messages	Whether or not to suppress messages.
clint.pvalue.threshold	Hepatic clearance for chemicals where the in vitro clearance assay result has a p-value greater than the threshold are set to zero.
minimum.funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

Value

Vdist	Volume of distribution, units of L/kg BW.
Fgutabs	Fraction of the oral dose absorbed, i.e. the fraction of the dose that enters the gutlumen.
Fhep.assay.correction	The fraction of chemical unbound in hepatocyte assay using the method of Kilford et al. (2008)
kelim	Elimination rate, units of 1/h.
hematocrit	Percent volume of red blood cells in the blood.
kgutabs	Rate chemical is absorbed, 1/h.
million.cells.per.gliver	Millions cells per gram of liver tissue.
MW	Molecular Weight, g/mol.
Rblood2plasma	The ratio of the concentration of the chemical in the blood to the concentration in the plasma. Not used in calculations but included for the conversion of plasma outputs.
hepatic.bioavailability	Fraction of dose remaining after first pass clearance, calculated from the corrected well-stirred model.
BW	Body Weight, kg.

Author(s)

John Wambaugh and Robert Pearce

References

- Pearce, Robert G., et al. "Htk: R package for high-throughput toxicokinetics." *Journal of statistical software* 79.4 (2017): 1.
- Kilford, P. J., Gertz, M., Houston, J. B. and Galetin, A. (2008). Hepatocellular binding of drugs: correction for unbound fraction in hepatocyte incubations using microsomal binding or drug lipophilicity data. *Drug Metabolism and Disposition* 36(7), 1194-7, 10.1124/dmd.108.020834.

Examples

```
parameters <- parameterize_1comp(chem.name='Bisphenol-A',species='Rat')
parameters <- parameterize_1comp(chem.cas='80-05-7',
                                restrictive.clearance=FALSE,
                                species='rabbit',
                                default.to.human=TRUE)
out <- solve_1comp(parameters=parameters)
```

parameterize_3comp	<i>Parameterize_3comp</i>
--------------------	---------------------------

Description

This function initializes the parameters needed in the function solve_3comp.

Usage

```
parameterize_3comp(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  species = "Human",
  default.to.human = FALSE,
  force.human.clint.fup = FALSE,
  clint.pvalue.threshold = 0.05,
  adjusted.Funbound.plasma = TRUE,
  regression = TRUE,
  suppress.messages = FALSE,
  restrictive.clearance = TRUE,
  minimum.Funbound.plasma = 1e-04
)
```

Arguments

chem.cas	Chemical Abstract Services Registry Number (CAS-RN) – the chemical must be identified by either CAS, name, or DTXISD
chem.name	Chemical name (spaces and capitalization ignored) – the chemical must be identified by either CAS, name, or DTXISD
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) – the chemical must be identified by either CAS, name, or DTXSIDs
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
default.to.human	Substitutes missing animal values with human values if true.
force.human.clint.fup	Forces use of human values for hepatic intrinsic clearance and fraction of unbound plasma if true.

clint.pvalue.threshold	Hepatic clearances with clearance assays having p-values greater than the threshold are set to zero.
adjusted.Funbound.plasma	Returns adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
suppress.messages	Whether or not the output message is suppressed.
restrictive.clearance	In calculating hepatic.bioavailability, protein binding is not taken into account (set to 1) in liver clearance if FALSE.
minimum.Funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

Value

BW	Body Weight, kg.
Clmetabolismc	Hepatic Clearance, L/h/kg BW.
Fgutabs	Fraction of the oral dose absorbed, i.e. the fraction of the dose that enters the gutlumen.
Funbound.plasma	Fraction of plasma that is not bound.
Fhep.assay.correction	The fraction of chemical unbound in hepatocyte assay using the method of Kilford et al. (2008)
hematocrit	Percent volume of red blood cells in the blood.
Kgut2pu	Ratio of concentration of chemical in gut tissue to unbound concentration in plasma.
Kliver2pu	Ratio of concentration of chemical in liver tissue to unbound concentration in plasma.
Krbc2pu	Ratio of concentration of chemical in red blood cells to unbound concentration in plasma.
Krest2pu	Ratio of concentration of chemical in rest of body tissue to unbound concentration in plasma.
million.cells.per.gliver	Millions cells per gram of liver tissue.
MW	Molecular Weight, g/mol.
Qcardiac	Cardiac Output, L/h/kg BW ^{3/4} .
Qgfr	Glomerular Filtration Rate, L/h/kg BW ^{3/4} , volume of fluid filtered from kidney and excreted.
Qgutf	Fraction of cardiac output flowing to the gut.
Qliverf	Fraction of cardiac output flowing to the liver.
Rblood2plasma	The ratio of the concentration of the chemical in the blood to the concentration in the plasma.
Vgut	Volume of the gut per kg body weight, L/kg BW.
Vliver	Volume of the liver per kg body weight, L/kg BW.
Vrest	Volume of the rest of the body per kg body weight, L/kg BW.

Author(s)

Robert Pearce and John Wambaugh

References

Pearce, Robert G., et al. "Htk: R package for high-throughput toxicokinetics." Journal of statistical software 79.4 (2017): 1.

Kilford, P. J., Gertz, M., Houston, J. B. and Galetin, A. (2008). Hepatocellular binding of drugs: correction for unbound fraction in hepatocyte incubations using microsomal binding or drug lipophilicity data. Drug Metabolism and Disposition 36(7), 1194-7, 10.1124/dmd.108.020834.

Examples

```
parameters <- parameterize_3comp(chem.name='Bisphenol-A',species='Rat')
parameters <- parameterize_3comp(chem.cas='80-05-7',
                                species='rabbit',default.to.human=TRUE)
out <- solve_3comp(parameters=parameters,plots=TRUE)
```

parameterize_fetal_pbt

Parameterize_fetal_PBT

Description

This function initializes the parameters needed in the functions solve_fetal_pbt by calling solve_pbt and adding additional parameters.

Usage

```
parameterize_fetal_pbt(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  species = "Human",
  fetal_fup_adjustment = TRUE,
  return.kapraun2019 = TRUE,
  suppress.messages = FALSE,
  ...
)
```

Arguments

chem.cas	Either the chemical name or the CAS number must be specified.
chem.name	Either the chemical name or the CAS number must be specified.
dtxsid	EPA's DSSTox Structure ID (http://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human"). Currently only a narrow human model is supported.

fetal_fup_adjustment	Logical indicator of whether to use an adjusted estimate for fetal fup based on the fetal:maternal plasma protein binding ratios presented in McNamara and Alcorn's 2002 study "Protein Binding Predictions in Infants." Defaults to TRUE.
return.kapraun2019	If TRUE (default) the empirical parameters for the Kapraun et al. (2019) maternal-fetal growth parameters are provided.
suppress.messages	Whether or not the output message is suppressed.
...	Arguments passed to parameterize_pbt.

Value

pre_pregnant_BW	Body Weight before pregnancy, kg.
Clmetabolismc	Hepatic Clearance, L/h/kg BW.
Fgutabs	Fraction of the oral dose absorbed, i.e. the fraction of the dose that enters the gutlumen.
Funbound.plasma	Fraction of plasma that is not bound.
Fhep.assay.correction	The fraction of chemical unbound in hepatocyte assay using the method of Kilford et al. (2008)
hematocrit	Percent volume of red blood cells in the blood.
Kgut2pu	Ratio of concentration of chemical in gut tissue to unbound concentration in plasma.
kgutabs	Rate that chemical enters the gut from gutlumen, 1/h.
Kkidney2pu	Ratio of concentration of chemical in kidney tissue to unbound concentration in plasma.
Kliver2pu	Ratio of concentration of chemical in liver tissue to unbound concentration in plasma.
Klung2pu	Ratio of concentration of chemical in lung tissue to unbound concentration in plasma.
Krbc2pu	Ratio of concentration of chemical in red blood cells to unbound concentration in plasma.
Krest2pu	Ratio of concentration of chemical in rest of body tissue to unbound concentration in plasma.
million.cells.per.gliver	Millions cells per gram of liver tissue.
MW	Molecular Weight, g/mol.
Qgfr	Glomerular Filtration Rate, L/h/kg BW ^{3/4} , volume of fluid filtered from kidney and excreted.
Rblood2plasma	The ratio of the concentration of the chemical in the blood to the concentration in the plasma from available_rblood2plasma.
Vgut	Volume of the gut per kg body weight, L/kg BW.
Vkidney	Volume of the kidneys per kg body weight, L/kg BW.
Vliver	Volume of the liver per kg body weight, L/kg BW.

Vlungc	Volume of the lungs per kg body weight, L/kg BW.
Vthyroidc	Volume of the thyroid per kg body weight, L/kg BW.
Kfgut2pu	Ratio of concentration of chemical in fetal gut tissue to unbound concentration in plasma.
Kfkidney2pu	Ratio of concentration of chemical in fetal kidney tissue to unbound concentration in plasma.
Kfliver2pu	Ratio of concentration of chemical in fetal liver tissue to unbound concentration in plasma.
Kflung2pu	Ratio of concentration of chemical in fetal lung tissue to unbound concentration in plasma.
Kfrest2pu	Ratio of concentration of chemical in fetal rest of body tissue to unbound concentration in plasma.
Kfbrain2pu	Ratio of concentration of chemical in fetal brain tissue to unbound concentration in plasma.
Kthyroid2pu	Ratio of concentration of chemical in fetal thyroid tissue to unbound concentration in plasma.
Kfthyroid2pu	Ratio of concentration of chemical in fetal thyroid tissue to unbound concentration in plasma.
Kplacenta2pu	Ratio of concentration of chemical in placental tissue to unbound concentration in maternal plasma.
Kfplacenta2pu	Ratio of concentration of chemical in placental tissue to unbound concentration in fetal plasma.

Author(s)

Robert Pearce, Mark Sfeir, John Wambaugh, and Dustin Kapraun

Mark Sfeir, Dustin Kapraun, John Wambaugh

References

Kilford, P. J., Gertz, M., Houston, J. B. and Galetin, A. (2008). Hepatocellular binding of drugs: correction for unbound fraction in hepatocyte incubations using microsomal binding or drug lipophilicity data. *Drug Metabolism and Disposition* 36(7), 1194-7, 10.1124/dmd.108.020834.

McNamara PJ, Alcorn J. Protein binding predictions in infants. *AAPS PharmSci.* 2002;4(1):E4. doi: 10.1208/ps040104. PMID: 12049488.

Examples

```
parameters <- parameterize_fetal_pbtk(chem.cas='80-05-7')
```

```
parameters <- parameterize_fetal_pbtk(chem.name='Bisphenol-A',species='Rat')
```

`parameterize_gas_pbt` *Parameterize_gas_pbt*

Description

This function initializes the parameters needed in the function `solve_gas_pbt`

Usage

```
parameterize_gas_pbt(  
  chem.cas = NULL,  
  chem.name = NULL,  
  dtxsid = NULL,  
  species = "Human",  
  default.to.human = FALSE,  
  tissuelist = list(liver = c("liver"), kidney = c("kidney"), lung = c("lung"), gut =  
    c("gut")),  
  force.human.clint.fup = FALSE,  
  clint.pvalue.threshold = 0.05,  
  adjusted.funbound.plasma = TRUE,  
  regression = TRUE,  
  vmax = 0,  
  km = 1,  
  exercise = FALSE,  
  fR = 12,  
  VT = 0.75,  
  VD = 0.15,  
  suppress.messages = FALSE,  
  minimum.funbound.plasma = 1e-04,  
  ...  
)
```

Arguments

<code>chem.cas</code>	Either the chemical name or the CAS number must be specified.
<code>chem.name</code>	Either the chemical name or the CAS number must be specified.
<code>dtxsid</code>	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
<code>species</code>	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
<code>default.to.human</code>	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
<code>tissuelist</code>	Specifies compartment names and tissues groupings. Remaining tissues in <code>tissue.data</code> are lumped in the rest of the body. However, <code>solve_pbt</code> only works with the default parameters.
<code>force.human.clint.fup</code>	Forces use of human values for hepatic intrinsic clearance and fraction of unbound plasma if true.

<code>clint.pvalue.threshold</code>	Hepatic clearance for chemicals where the in vitro clearance assay result has a p-values greater than the threshold are set to zero.
<code>adjusted.Funbound.plasma</code>	Returns adjusted <code>Funbound.plasma</code> when set to TRUE along with partition coefficients calculated with this value.
<code>regression</code>	Whether or not to use the regressions in calculating partition coefficients.
<code>vmax</code>	Michaelis-Menten <code>vmax</code> value in reactions/min
<code>km</code>	Michaelis-Menten concentration of half-maximal reaction velocity in desired output concentration units.
<code>exercise</code>	Logical indicator of whether to simulate an exercise-induced heightened respiration rate
<code>fR</code>	Respiratory frequency (breaths/minute), used especially to adjust breathing rate in the case of exercise. This parameter, along with VT and VD (below) gives another option for calculating Q _{alv} (Alveolar ventilation) in case pulmonary ventilation rate is not known
<code>VT</code>	Tidal volume (L), to be modulated especially as part of simulating the state of exercise
<code>VD</code>	Anatomical dead space (L), to be modulated especially as part of simulating the state of exercise
<code>suppress.messages</code>	Whether or not the output message is suppressed.
<code>minimum.Funbound.plasma</code>	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured <code>Fup</code> in our dataset).
<code>...</code>	Other parameters

Value

<code>BW</code>	Body Weight, kg.
<code>Clint</code>	Hepatic intrinsic clearance, uL/min/10 ⁶ cells
<code>Clint.dist</code>	Distribution of hepatic intrinsic clearance values (median, lower 95th, upper 95th, p value)
<code>Clmetabolismc</code>	Hepatic Clearance, L/h/kg BW.
<code>Fgutabs</code>	Fraction of the oral dose absorbed, i.e. the fraction of the dose that enters the gut lumen.
<code>Fhep.assay.correction</code>	The fraction of chemical unbound in hepatocyte assay using the method of Kilford et al. (2008)
<code>Funbound.plasma</code>	Fraction of chemical unbound to plasma.
<code>Funbound.plasma.adjustment</code>	Fraction unbound to plasma adjusted as described in Pearce et al. 2017
<code>Funbound.plasma.dist</code>	Distribution of fraction unbound to plasma (median, lower 95th, upper 95th)
<code>hematocrit</code>	Percent volume of red blood cells in the blood.
<code>Kblood2air</code>	Ratio of concentration of chemical in blood to air

Kgut2pu	Ratio of concentration of chemical in gut tissue to unbound concentration in plasma.
kgutabs	Rate that chemical enters the gut from gutlumen, 1/h.
Kkidney2pu	Ratio of concentration of chemical in kidney tissue to unbound concentration in plasma.
Kliver2pu	Ratio of concentration of chemical in liver tissue to unbound concentration in plasma.
Klung2pu	Ratio of concentration of chemical in lung tissue to unbound concentration in plasma.
km	Michaelis-Menten concentration of half-maximal activity
Kmuc2air	Mucus to air partition coefficient
Krbc2pu	Ratio of concentration of chemical in red blood cells to unbound concentration in plasma.
Krest2pu	Ratio of concentration of chemical in rest of body tissue to unbound concentration in plasma.
kUrtc	Unscaled upper respiratory tract uptake parameter ($L/h/kg^{0.75}$)
liver.density	Density of liver in g/mL
MA	phospholipid:water distribution coefficient, membrane affinity
million.cells.per.gliver	Millions cells per gram of liver tissue.
MW	Molecular Weight, g/mol.
pKa_Accept	compound H association equilibrium constant(s)
pKa_Donor	compound H dissociation equilibrium constant(s)
Pow	octanol:water partition coefficient (not log transformed)
Qalvc	Unscaled alveolar ventilation rate ($L/h/kg^{0.75}$)
Qcardiac	Cardiac Output, $L/h/kg BW^{3/4}$.
Qgfr	Glomerular Filtration Rate, $L/h/kg BW^{0.75}$, volume of fluid filtered from kidney and excreted.
Qgutf	Fraction of cardiac output flowing to the gut.
Qkidneyf	Fraction of cardiac output flowing to the kidneys.
Qliverf	Fraction of cardiac output flowing to the liver.
Qlungf	Fraction of cardiac output flowing to lung tissue.
Qrestf	Fraction of blood flow to rest of body
Rblood2plasma	The ratio of the concentration of the chemical in the blood to the concentration in the plasma from available_rblood2plasma.
Vartc	Volume of the arteries per kg body weight, L/kg BW.
Vgut	Volume of the gut per kg body weight, L/kg BW.
Vkidney	Volume of the kidneys per kg body weight, L/kg BW.
Vliver	Volume of the liver per kg body weight, L/kg BW.
Vlung	Volume of the lungs per kg body weight, L/kg BW.
vmax	Michaelis-Menten maximum reaction velocity (1/min)
Vmuc	Unscaled mucosal volume ($L/kg BW^{0.75}$)
Vrest	Volume of the rest of the body per kg body weight, L/kg BW.
Vvenc	Volume of the veins per kg body weight, L/kg BW.

Author(s)

Matt Linakis, Robert Pearce, John Wambaugh

References

Linakis, Matthew W., et al. "Development and Evaluation of a High Throughput Inhalation Model for Organic Chemicals", submitted

Kilford, P. J., Gertz, M., Houston, J. B. and Galetin, A. (2008). Hepatocellular binding of drugs: correction for unbound fraction in hepatocyte incubations using microsomal binding or drug lipophilicity data. *Drug Metabolism and Disposition* 36(7), 1194-7, 10.1124/dmd.108.020834.

Examples

```
parameters <- parameterize_gas_pbt(chem.cas='129-00-0')

parameters <- parameterize_gas_pbt(chem.name='pyrene', species='Rat')

parameterize_gas_pbt(chem.cas = '56-23-5')

parameters <- parameterize_gas_pbt(chem.name='Carbon tetrachloride', species='Rat')

# Change the tissue lumping:
compartments <- list(liver=c("liver"), fast=c("heart", "brain", "muscle", "kidney"),
                    lung=c("lung"), gut=c("gut"), slow=c("bone"))
parameterize_gas_pbt(chem.name="Bisphenol a", species="Rat", default.to.human=TRUE,
                    tissuelist=compartments)
```

parameterize_pbt	<i>Parameterize_PBT</i>
------------------	-------------------------

Description

This function initializes the parameters needed in the functions `solve_pbt`, `calc_css`, and others using the multiple compartment model.

Usage

```
parameterize_pbt(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  species = "Human",
  default.to.human = FALSE,
  tissuelist = list(liver = c("liver"), kidney = c("kidney"), lung = c("lung"), gut =
    c("gut")),
  force.human.clint.fup = FALSE,
  clint.pvalue.threshold = 0.05,
  adjusted.funbound.plasma = TRUE,
  regression = TRUE,
  suppress.messages = FALSE,
  restrictive.clearance = TRUE,
```

```

    minimum.Funbound.plasma = 1e-04
)

```

Arguments

chem.cas	Chemical Abstract Services Registry Number (CAS-RN) – the chemical must be identified by either CAS, name, or DTXISD
chem.name	Chemical name (spaces and capitalization ignored) – the chemical must be identified by either CAS, name, or DTXISD
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) – the chemical must be identified by either CAS, name, or DTXISDs
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
default.to.human	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
tissuelist	Specifies compartment names and tissues groupings. Remaining tissues in tissue.data are lumped in the rest of the body. However, solve_pbt only works with the default parameters.
force.human.clint.fup	Forces use of human values for hepatic intrinsic clearance and fraction of unbound plasma if true.
clint.pvalue.threshold	Hepatic clearance for chemicals where the in vitro clearance assay result has a p-values greater than the threshold are set to zero.
adjusted.Funbound.plasma	Returns adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
suppress.messages	Whether or not the output message is suppressed.
restrictive.clearance	In calculating hepatic.bioavailability, protein binding is not taken into account (set to 1) in liver clearance if FALSE.
minimum.Funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

Value

BW	Body Weight, kg.
Clmetabolismc	Hepatic Clearance, L/h/kg BW.
Fgutabs	Fraction of the oral dose absorbed, i.e. the fraction of the dose that enters the gutlumen.
Funbound.plasma	Fraction of plasma that is not bound.
Fhep.assay.correction	The fraction of chemical unbound in hepatocyte assay using the method of Kilford et al. (2008)
hematocrit	Percent volume of red blood cells in the blood.

Kgut2pu	Ratio of concentration of chemical in gut tissue to unbound concentration in plasma.
kgutabs	Rate that chemical enters the gut from gutlumen, 1/h.
Kkidney2pu	Ratio of concentration of chemical in kidney tissue to unbound concentration in plasma.
Kliver2pu	Ratio of concentration of chemical in liver tissue to unbound concentration in plasma.
Klung2pu	Ratio of concentration of chemical in lung tissue to unbound concentration in plasma.
Krbc2pu	Ratio of concentration of chemical in red blood cells to unbound concentration in plasma.
Krest2pu	Ratio of concentration of chemical in rest of body tissue to unbound concentration in plasma.
million.cells.per.gliver	Millions cells per gram of liver tissue.
MW	Molecular Weight, g/mol.
Qcardiac	Cardiac Output, L/h/kg BW ^{3/4} .
Qgfr	Glomerular Filtration Rate, L/h/kg BW ^{3/4} , volume of fluid filtered from kidney and excreted.
Qgut	Fraction of cardiac output flowing to the gut.
Qkidney	Fraction of cardiac output flowing to the kidneys.
Qliver	Fraction of cardiac output flowing to the liver.
Rblood2plasma	The ratio of the concentration of the chemical in the blood to the concentration in the plasma from available_rblood2plasma.
Vart	Volume of the arteries per kg body weight, L/kg BW.
Vgut	Volume of the gut per kg body weight, L/kg BW.
Vkidney	Volume of the kidneys per kg body weight, L/kg BW.
Vliver	Volume of the liver per kg body weight, L/kg BW.
Vlung	Volume of the lungs per kg body weight, L/kg BW.
Vrest	Volume of the rest of the body per kg body weight, L/kg BW.
Vven	Volume of the veins per kg body weight, L/kg BW.

Author(s)

John Wambaugh and Robert Pearce

References

- Pearce, Robert G., et al. "Htk: R package for high-throughput toxicokinetics." Journal of statistical software 79.4 (2017): 1.
- Kilford, P. J., Gertz, M., Houston, J. B. and Galetin, A. (2008). Hepatocellular binding of drugs: correction for unbound fraction in hepatocyte incubations using microsomal binding or drug lipophilicity data. Drug Metabolism and Disposition 36(7), 1194-7, 10.1124/dmd.108.020834.

Examples

```
parameters <- parameterize_pbtck(chem.cas='80-05-7')

parameters <- parameterize_pbtck(chem.name='Bisphenol-A',species='Rat')

# Change the tissue lumping (note, these model parameters will not work with our current solver):
compartments <- list(liver=c("liver"),fast=c("heart","brain","muscle","kidney"),
                     lung=c("lung"),gut=c("gut"),slow=c("bone"))
parameterize_pbtck(chem.name="Bisphenol a",species="Rat",default.to.human=TRUE,
                   tissuelist=compartments)
```

parameterize_schmitt *Get the Parameters for Schmitt's Tissue Partition Coefficient Method*

Description

This function provides the necessary parameters to run `predict_partitioning_schmitt`, excluding the data in `tissue.data`.

Usage

```
parameterize_schmitt(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  parameters = NULL,
  species = "Human",
  default.to.human = FALSE,
  force.human.fup = FALSE,
  suppress.messages = FALSE,
  minimum.funbound.plasma = 1e-04
)
```

Arguments

<code>chem.cas</code>	Chemical Abstract Services Registry Number (CAS-RN) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
<code>chem.name</code>	Chemical name (spaces and capitalization ignored) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXISD
<code>dtxsid</code>	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) – if parameters is not specified then the chemical must be identified by either CAS, name, or DTXSIDs
<code>parameters</code>	Chemical and physiological description parameters needed to run the Schmitt et al. (2008) model
<code>species</code>	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").

default.to.human
Substitutes missing fraction of unbound plasma with human values if true.

force.human.fup
Returns human fraction of unbound plasma in calculation for rats if true. When species is specified as rabbit, dog, or mouse, the human unbound fraction is substituted.

suppress.messages
Whether or not the output message is suppressed.

minimum.funbound.plasma
Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

Value

Funbound.plasma
corrected unbound fraction in plasma

unadjusted.funbound.plasma
measured unbound fraction in plasma (0.005 if below limit of detection)

Pow
octanol:water partition coefficient (not log transformed)

pKa_Donor
compound H dissociation equilibrium constant(s)

pKa_Accept
compound H association equilibrium constant(s)

MA
phospholipid:water distribution coefficient, membrane affinity

Fprotein.plasma
protein fraction in plasma

plasma.pH
pH of the plasma

Author(s)

Robert Pearce and John Wambaugh

References

Schmitt, Walter. "General approach for the calculation of tissue to plasma partition coefficients." *Toxicology in Vitro* 22.2 (2008): 457-467.

Schmitt, Walter. "Corrigendum to: General approach for the calculation of tissue to plasma partition coefficients" *Toxicology in Vitro* 22.6 (2008): 1666.

Peyret, Thomas, Patrick Poulin, and Kannan Krishnan. "A unified algorithm for predicting partition coefficients for PBPK modeling of drugs and environmental chemicals." *Toxicology and applied pharmacology* 249.3 (2010): 197-207.

Pearce, Robert G., et al. "Evaluation and calibration of high-throughput predictions of chemical distribution to tissues." *Journal of pharmacokinetics and pharmacodynamics* 44.6 (2017): 549-565.

Examples

```
parameterize_schmitt(chem.name='bisphenola')
```

parameterize_steadystate

Parameterize_SteadyState

Description

This function initializes the parameters needed in the functions `calc_mc_css`, `calc_mc_oral_equiv`, and `calc_analytic_css` for the three compartment steady state model ('3compartmentss').

Usage

```
parameterize_steadystate(
  chem.cas = NULL,
  chem.name = NULL,
  dtxsid = NULL,
  species = "Human",
  clint.pvalue.threshold = 0.05,
  default.to.human = FALSE,
  human.clint.fup = FALSE,
  adjusted.Funbound.plasma = TRUE,
  restrictive.clearance = TRUE,
  fup.lod.default = 0.005,
  suppress.messages = FALSE,
  minimum.Funbound.plasma = 1e-04
)
```

Arguments

<code>chem.cas</code>	Chemical Abstract Services Registry Number (CAS-RN) – the chemical must be identified by either CAS, name, or DTXISD
<code>chem.name</code>	Chemical name (spaces and capitalization ignored) – the chemical must be identified by either CAS, name, or DTXISD
<code>dtxsid</code>	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) – the chemical must be identified by either CAS, name, or DTXSIDs
<code>species</code>	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
<code>clint.pvalue.threshold</code>	Hepatic clearances with clearance assays having p-values greater than the threshold are set to zero.
<code>default.to.human</code>	Substitutes missing rat values with human values if true.
<code>human.clint.fup</code>	Uses human hepatic intrinsic clearance and fraction of unbound plasma in calculation of partition coefficients for rats if true.
<code>adjusted.Funbound.plasma</code>	Returns adjusted Funbound.plasma when set to TRUE.
<code>restrictive.clearance</code>	In calculating hepatic.bioavailability, protein binding is not taken into account (set to 1) in liver clearance if FALSE.

fup.lod.default Default value used for fraction of unbound plasma for chemicals where measured value was below the limit of detection. Default value is 0.0005.

suppress.messages Whether or not the output message is suppressed.

minimum.Funbound.plasma Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

Value

Clint Hepatic Intrinsic Clearance, uL/min/10⁶ cells.

Fgutabs Fraction of the oral dose absorbed, i.e. the fraction of the dose that enters the gutlumen.

Funbound.plasma Fraction of plasma that is not bound.

Qtotall.liverc Flow rate of blood exiting the liver, L/h/kg BW^{3/4}.

Qgfrc Glomerular Filtration Rate, L/h/kg BW^{3/4}, volume of fluid filtered from kidney and excreted.

BW Body Weight, kg

MW Molecular Weight, g/mol

million.cells.per.gliver Millions cells per gram of liver tissue.

Vliverc Volume of the liver per kg body weight, L/kg BW.

liver.density Liver tissue density, kg/L.

Fhep.assay.correction The fraction of chemical unbound in hepatocyte assay using the method of Kilford et al. (2008)

hepatic.bioavailability Fraction of dose remaining after first pass clearance, calculated from the corrected well-stirred model.

Author(s)

John Wambaugh

References

Pearce, Robert G., et al. "Htk: R package for high-throughput toxicokinetics." Journal of statistical software 79.4 (2017): 1.

Kilford, P. J., Gertz, M., Houston, J. B. and Galetin, A. (2008). Hepatocellular binding of drugs: correction for unbound fraction in hepatocyte incubations using microsomal binding or drug lipophilicity data. Drug Metabolism and Disposition 36(7), 1194-7, 10.1124/dmd.108.020834.

Examples

```
parameters <- parameterize_steadystate(chem.name='Bisphenol-A',species='Rat')
parameters <- parameterize_steadystate(chem.cas='80-05-7')
```

pc.data*Partition Coefficient Data*

Description

Measured rat in vivo partition coefficients and data for predicting them.

Usage

pc.data

Format

A data.frame.

Author(s)

Jimena Davis and Robert Pearce

References

- Schmitt, W., General approach for the calculation of tissue to plasma partition coefficients. *Toxicology in Vitro*, 2008. 22(2): p. 457-467.
- Schmitt, W., Corrigendum to: "General approach for the calculation of tissue to plasma partition coefficients" [*Toxicology in Vitro* 22 (2008) 457-467]. *Toxicology in Vitro*, 2008. 22(6): p. 1666.
- Poulin, P. and F.P. Theil, A priori prediction of tissue: plasma partition coefficients of drugs to facilitate the use of physiologically based pharmacokinetic models in drug discovery. *Journal of pharmaceutical sciences*, 2000. 89(1): p. 16-35.
- Rodgers, T. and M. Rowland, Physiologically based pharmacokinetic modelling 2: predicting the tissue distribution of acids, very weak bases, neutrals and zwitterions. *Journal of pharmaceutical sciences*, 2006. 95(6): p. 1238-1257.
- Rodgers, T., D. Leahy, and M. Rowland, Physiologically based pharmacokinetic modeling 1: predicting the tissue distribution of moderate-to-strong bases. *Journal of pharmaceutical sciences*, 2005. 94(6): p. 1259-1276.
- Rodgers, T., D. Leahy, and M. Rowland, Tissue distribution of basic drugs: Accounting for enantiomeric, compound and regional differences amongst beta-blocking drugs in rat. *Journal of pharmaceutical sciences*, 2005. 94(6): p. 1237-1248.
- Gueorguieva, I., et al., Development of a whole body physiologically based model to characterise the pharmacokinetics of benzodiazepines. 1: Estimation of rat tissue-plasma partition ratios. *Journal of pharmacokinetics and pharmacodynamics*, 2004. 31(4): p. 269-298.
- Poulin, P., K. Schoenlein, and F.P. Theil, Prediction of adipose tissue: plasma partition coefficients for structurally unrelated drugs. *Journal of pharmaceutical sciences*, 2001. 90(4): p. 436-447.
- Bjorkman, S., Prediction of the volume of distribution of a drug: which tissue-plasma partition coefficients are needed? *Journal of pharmacy and pharmacology*, 2002. 54(9): p. 1237-1245.
- Yun, Y. and A. Edginton, Correlation-based prediction of tissue-to-plasma partition coefficients using readily available input parameters. *Xenobiotica*, 2013. 43(10): p. 839-852.
- Uchimura, T., et al., Prediction of human blood-to-plasma drug concentration ratio. *Biopharmaceutics & drug disposition*, 2010. 31(5-6): p. 286-297.

pearce2017regression	<i>Pearce et al. 2017 data</i>
----------------------	--------------------------------

Description

This table includes the adjusted and unadjusted regression parameter estimates for the chemical-specific plasma protein unbound fraction (fup) in 12 different tissue types.

Usage

pearce2017regression

Format

data.frame

Details

Predictions were made with regression models, as reported in Pearce et al. (2017).

Author(s)

Robert G. Pearce

Source

Pearce et al. 2017 Regression Models

References

Pearce, Robert G., et al. "Evaluation and calibration of high-throughput predictions of chemical distribution to tissues." *Journal of pharmacokinetics and pharmacodynamics* 44.6 (2017): 549-565.

pharma	<i>DRUGS\NORMAN: Pharmaceutical List with EU, Swiss, US Consumption Data</i>
--------	--

Description

SWISSPHARMA is a list of pharmaceuticals with consumption data from Switzerland, France, Germany and the USA, used for a suspect screening/exposure modelling approach described in Singer et al 2016, DOI: 10.1021/acs.est.5b03332. The original data is available on the NORMAN Suspect List Exchange.

Usage

pharma

Format

An object of class data.frame with 954 rows and 14 columns.

Source

https://comptox.epa.gov/dashboard/chemical_lists/swisspharma

References

Wambaugh et al. (2019) "Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization", Toxicological Sciences, 172(2), 235-251.

physiology.data	<i>Species-specific physiology parameters</i>
-----------------	---

Description

This data set contains values from Davies and Morris (1993) necessary to parameterize a toxicokinetic model for human, mouse, rat, dog, or rabbit. The temperature for each species are taken from Robertshaw et al. (2004), Gordon (1993), and Stammers(1926).

Usage

physiology.data

Format

A data.frame containing 11 rows and 7 columns.

Author(s)

John Wambaugh and Nisha Sipes

Source

Wambaugh, John F., et al. "Toxicokinetic triage for environmental chemicals." Toxicological Sciences (2015): 228-237.

References

Davies, B. and Morris, T. (1993). Physiological Parameters in Laboratory Animals and Humans. Pharmaceutical Research 10(7), 1093-1095, 10.1023/a:1018943613122.

Environment, in Dukes' Physiology of Domestic Animals, 12th ed., Reece W.O., Ed. Copyright 2004 by Cornell University. Stammers (1926) The blood count and body temperature in normal rats
Gordon (1993) Temperature Regulation in Laboratory Rodents

pksim.pcs

Partition Coefficients from PK-Sim

Description

Dallmann et al. (2018) made use of PK-Sim to predict chemical- and tissue- specific partition coefficients. The methods include both the default PK-Sim approach and PK-Sim Standard and Rodgers & Rowland (2006).

Usage

pksim.pcs

Format

data.frame

Source

Kapraun et al. 2021 (submitted)

References

Dallmann A, Ince I, Coboeken K, Eissing T, Hempel G (2018). "A physiologically based pharmacokinetic model for pregnant women to predict the pharmacokinetics of drugs metabolized via several enzymatic pathways." *Clinical pharmacokinetics*, **57**(6), 749–768.

pradeep2020

Pradeep et al. 2020

Description

This table includes Support Vector Machine and Random Forest model predicted values for unbound fraction plasma protein (fup) and intrinsic hepatic clearance (clint) values for a subset of chemicals in the Tox21 library (see <https://www.epa.gov/chemical-research/toxicology-testing-21st-century>).

Usage

pradeep2020

Format

data.frame

Details

Prediction were made with Support Vector Machine and Random Forest models, as reported in Pradeep et al. (2020).

Source

Pradeep et al. 2020 Chemical Structure Predictive Models for HTTK

References

Pradeep P, Patlewicz G, Pearce R, Wambaugh J, Wetmore B, Judson R (2020). "Using chemical structure information to develop predictive models for in vitro toxicokinetic parameters to inform high-throughput risk-assessment." *Computational Toxicology*, **16**, 100136. ISSN 2468-1113, doi: [10.1016/j.comtox.2020.100136](https://doi.org/10.1016/j.comtox.2020.100136), <https://www.sciencedirect.com/science/article/pii/S2468111320300463>.

predict_partitioning_schmitt

Predict partition coefficients using the method from Schmitt (2008).

Description

This function implements the method from Schmitt (2008) in predicting the tissue to unbound plasma partition coefficients for the tissues contained in the tissue.data table.

Usage

```
predict_partitioning_schmitt(  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL,  
  species = "Human",  
  model = "pbtk",  
  default.to.human = FALSE,  
  parameters = NULL,  
  alpha = 0.001,  
  adjusted.funbound.plasma = TRUE,  
  regression = TRUE,  
  regression.list = c("brain", "adipose", "gut", "heart", "kidney", "liver", "lung",  
    "muscle", "skin", "spleen", "bone"),  
  tissues = NULL,  
  minimum.funbound.plasma = 1e-04,  
  suppress.messages = FALSE  
)
```

Arguments

chem.name	Either the chemical name or the CAS number must be specified.
chem.cas	Either the chemical name or the CAS number must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
model	Model for which partition coefficients are needed (for example, "pbtk", "3compartment")

<code>default.to.human</code>	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
<code>parameters</code>	Chemical parameters from <code>parameterize_schmitt</code> overrides <code>chem.name</code> , <code>dtxsid</code> , and <code>chem.cas</code> .
<code>alpha</code>	Ratio of Distribution coefficient D of totally charged species and that of the neutral form
<code>adjusted.funbound.plasma</code>	Whether or not to use <code>Funbound.plasma</code> adjustment.
<code>regression</code>	Whether or not to use the regressions. Regressions are used by default.
<code>regression.list</code>	Tissues to use regressions on.
<code>tissues</code>	Vector of desired partition coefficients. Returns all by default.
<code>minimum.funbound.plasma</code>	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured <code>Fup</code> in our dataset).
<code>suppress.messages</code>	Whether or not the output message is suppressed.

Details

A separate regression is used when `adjusted.funbound.plasma` is FALSE.

A regression is used for membrane affinity when not provided. The regressions for correcting each tissue are performed on tissue plasma partition coefficients ($K_{tissue2pu} * Funbound.plasma$) calculated with the corrected `Funbound.plasma` value and divided by this value to get $K_{tissue2pu}$. Thus the regressions should be used with the corrected `Funbound.plasma`.

The red blood cell regression can be used but is not by default because of the span of the data used, reducing confidence in the regression for higher and lower predicted values.

Human tissue volumes are used for species other than Rat.

Value

Returns tissue to unbound plasma partition coefficients for each tissue.

Author(s)

Robert Pearce

References

- Schmitt, Walter. "General approach for the calculation of tissue to plasma partition coefficients." *Toxicology in Vitro* 22.2 (2008): 457-467.
- Birnbaum, L., et al. "Physiological parameter values for PBPK models." International Life Sciences Institute, Risk Science Institute, Washington, DC (1994).
- Pearce, Robert G., et al. "Evaluation and calibration of high-throughput predictions of chemical distribution to tissues." *Journal of pharmacokinetics and pharmacodynamics* 44.6 (2017): 549-565.
- Yun, Y. E., and A. N. Edginton. "Correlation-based prediction of tissue-to-plasma partition coefficients using readily available input parameters." *Xenobiotica* 43.10 (2013): 839-852.

Examples

```
predict_partitioning_schmitt(chem.name='ibuprofen', regression=FALSE)
```

pregnonpregaucs

*AUCs for Pregnant and Non-Pregnant Women***Description**

Dallmann et al. (2018) includes compiled literature descriptions of toxicokinetic summary statistics, including time-integrated plasma concentrations (area under the curve or AUC) for drugs administered to a sample of subjects including both pregnant and non-pregnant women. The circumstances of the dosing varied slightly between drugs and are summarized in the table.

Usage

```
pregnonpregaucs
```

Format

```
data.frame
```

Source

Kapraun et al. 2021 (submitted)

References

Dallmann A, Ince I, Coboeken K, Eissing T, Hempel G (2018). “A physiologically based pharmacokinetic model for pregnant women to predict the pharmacokinetics of drugs metabolized via several enzymatic pathways.” *Clinical pharmacokinetics*, **57**(6), 749–768.

```
propagate_invitrouv_1comp
```

Propagates uncertainty and variability in in vitro HTTK data into one compartment model parameters

Description

Propagates uncertainty and variability in in vitro HTTK data into one compartment model parameters

Usage

```
propagate_invitrouv_1comp(parameters.dt, ...)
```

Arguments

`parameters.dt` The data table of parameters being used by the Monte Carlo sampler
`...` Additional arguments passed to [calc_elimination_rate](#)

Value

A data.table whose columns are the parameters of the HTTK model specified in model.

Author(s)

John Wambaugh

propagate_invitrouv_3comp

Propagates uncertainty and variability in in vitro HTTK data into three compartment model parameters

Description

Propagates uncertainty and variability in in vitro HTTK data into three compartment model parameters

Usage

```
propagate_invitrouv_3comp(parameters.dt, ...)
```

Arguments

parameters.dt The data table of parameters being used by the Monte Carlo sampler
... Additional arguments passed to [calc_hep_clearance](#)

Value

A data.table whose columns are the parameters of the HTTK model specified in model.

Author(s)

John Wambaugh

propagate_invitrouv_pbt

Propagates uncertainty and variability in in vitro HTTK data into PBPK model parameters

Description

Propagates uncertainty and variability in in vitro HTTK data into PBPK model parameters

Usage

```
propagate_invitrouv_pbt(parameters.dt, ...)
```


Arguments

`parameters.dt` The data table of parameters being used by the Monte Carlo sampler
... Additional arguments passed to [calc_hep_clearance](#)

Value

A `data.table` whose columns are the parameters of the HHTK model specified in `model`.

Author(s)

John Wambaugh

`reset_httk`*Reset HHTK to Default Data Tables*

Description

This function returns an updated version of `chem.physical_and_invitro.data` that includes data predicted with Simulations Plus' ADMET predictor that was used in Sipes et al. 2017, included in `admet.data`.

Usage

```
reset_httk(target.env = .GlobalEnv)
```

Arguments

`target.env` The environment where the new `chem.physical_and_invitro.data` is loaded. Defaults to global environment.

Value

`data.frame` The package default version of `chem.physical_and_invitro.data`.

Author(s)

John Wambaugh

Examples

```
chem.physical_and_invitro.data <- load_sipes2017()
reset_httk()
```

rfun

Randomly draws from a one-dimensional KDE

Description

Randomly draws from a one-dimensional KDE

Usage

```
rfun(n, fhat)
```

Arguments

n	Number of samples to draw
fhat	A list with elements x, w, and h (h is the KDE bandwidth).

Value

A vector of n samples from the KDE fhat

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

r_left_censored_norm

Returns draws from a normal distribution with a lower censoring limit of lod (limit of detection)

Description

Returns draws from a normal distribution with a lower censoring limit of lod (limit of detection)

Usage

```
r_left_censored_norm(n, mean = 0, sd = 1, lod = 0.005, lower = 0, upper = 1)
```

Arguments

n	Number of samples to take
mean	Mean of censored distribution. Default 0.
sd	Standard deviation of censored distribution. Default 1.
lod	Bound below which to censor. Default 0.005.
lower	Lower bound on censored distribution. Default 0.
upper	Upper bound on censored distribution. Default 1.

Value

A vector of samples from the specified censored distribution.

scale_dosing	<i>Scale mg/kg body weight doses according to body weight and units</i>
--------------	---

Description

This function transforms the dose (in mg/kg) into the appropriate units. It handles single doses, matrices of doses, or daily repeated doses at varying intervals. Gut absorption is also factored in through the parameter `Fgutabs`, and scaling is currently avoided in the inhalation exposure case with a scale factor of 1

Usage

```
scale_dosing(
  dosing,
  parameters,
  route,
  input.units = NULL,
  output.units = "uM",
  vol = NULL
)
```

Arguments

dosing	List of dosing metrics used in simulation, which must include the general entries with names "initial.dose", "doses.per.day", "daily.dose", and "dosing.matrix". The "dosing.matrix" is used for more precise dose regimen specification, and is a matrix consisting of two columns or rows named "time" and "dose" containing the time and amount, in mg/kg BW, of each dose. The minimal usage case involves all entries but "initial.dose" set to NULL in value.
parameters	Chemical parameters from <code>parameterize_pbt</code> function, overrides <code>chem.name</code> and <code>chem.cas</code> .
route	String specification of route of exposure for simulation: "oral", "iv", "inhalation", ...
input.units	Units of the dose values being scaled. (Default is NULL.) Currently supported units "mg/L", "ug/L", "ug/mL", "uM", "umol/L", "ug/dL", "ug/g", "nmol/L", "nM", and "ppmw" (supported input.units subject to change).
output.units	Desired units (either "mg/L", "mg", "umol", or default "uM").
vol	Volume for the target tissue of interest. NOTE: Volume should not be in units of per BW, i.e. "kg".

Value

A list of numeric values for doses converted to `output.units`, potentially (depending on argument `dosing`) including:

initial.dose	The first dose given
dosing.matrix	A 2xN matrix where the first column is dose time and the second is dose amount for N doses
daily.dose	The total cumulative daily dose

Author(s)

John Wambaugh and Sarah E. Davidson

set_httk_precision	<i>set_httk_precision</i>
--------------------	---------------------------

Description

Although the ODE solver and other functions return very precise numbers, we cannot (or at least do not spend enough computing time to) be sure of the precision to an arbitrary level. This function both limits the number of significant figures reported and truncates the numerical precision.

Usage

```
set_httk_precision(in.num, sig.fig = 4, num.prec = 9)
```

Arguments

in.num	The numeric variable (or assembly of numerics) to be processed.
sig.fig	The number of significant figures reported. Defaults to 4.
num.prec	The precision maintained, digits below $10^{\text{num.prec}}$ are dropped. Defaults to 9.

Value

numeric values

Author(s)

John Wambaugh

sipes2017	<i>Sipes et al. 2017 data</i>
-----------	-------------------------------

Description

This table includes in silico predicted chemical-specific plasma protein unbound fraction (fup) and intrinsic hepatic clearance values for the entire Tox21 library (see <https://www.epa.gov/chemical-research/toxicology-testing-21st-century-tox21>). Predictions were made with Simulations Plus ADMET predictor, as reported in Sipes et al. (2017).

Usage

```
sipes2017
```

Format

data.frame

Author(s)

Nisha Sipes

Source

ADMET, Simulations Plus

References

Sipes, Nisha S., et al. "An Intuitive Approach for Predicting Potential Human Health Risk with the Tox21 10k Library." *Environmental Science & Technology* 51.18 (2017): 10786-10796.

skeletal_muscle_mass *Predict skeletal muscle mass*

Description

Predict skeletal muscle mass from age, height, and gender.

Usage

```
skeletal_muscle_mass(smm, age_years, height, gender)
```

Arguments

smm	Vector of allometrically-scaled skeletal muscle masses.
age_years	Vector of ages in years.
height	Vector of heights in cm.
gender	Vector of genders, either 'Male' or 'Female.'

Details

For individuals over age 18, use allometrically-scaled muscle mass with an age-based scaling factor, to account for loss of muscle mass with age (Janssen et al. 2000). For individuals under age 18, use [skeletal_muscle_mass_children](#).

Value

Vector of skeletal muscle masses in kg.

Author(s)

Caroline Ring

References

Janssen, Ian, et al. "Skeletal muscle mass and distribution in 468 men and women aged 18-88 yer." *Journal of Applied Physiology* 89.1 (2000): 81-88

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

See Also

[skeletal_muscle_mass_children](#)

skeletal_muscle_mass_children
Predict skeletal muscle mass for children

Description

For individuals under age 18, predict skeletal muscle mass from gender and age, using a nonlinear equation from Webber and Barr (2012)

Usage

```
skeletal_muscle_mass_children(gender, age_years)
```

Arguments

gender	Vector of genders (either 'Male' or 'Female').
age_years	Vector of ages in years.

Value

Vector of skeletal muscle masses in kg.

Author(s)

Caroline Ring

References

Webber, Colin E., and Ronald D. Barr. "Age-and gender-dependent values of skeletal muscle mass in healthy children and adolescents." Journal of cachexia, sarcopenia and muscle 3.1 (2012): 25-29.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." Environment International 106 (2017): 105-118

skin_mass_bosgra *Predict skin mass*

Description

Using equation from Bosgra et al. 2012, predict skin mass from body surface area.

Usage

```
skin_mass_bosgra(BSA)
```

Arguments

BSA	Vector of body surface areas in cm^2.
-----	---------------------------------------

Value

Vector of skin masses in kg.

Author(s)

Caroline Ring

References

Bosgra, Sieto, et al. "An improved model to predict physiologically based model parameters and their inter-individual variability from anthropometry." *Critical reviews in toxicology* 42.9 (2012): 751-767.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

solve_1comp

Solve one compartment TK model

Description

This function solves for the amount or concentration of a chemical in plasma for a one compartment model as a function of time based on the dose and dosing frequency.

Usage

```
solve_1comp(  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL,  
  times = NULL,  
  parameters = NULL,  
  days = 10,  
  tsteps = 4,  
  daily.dose = NULL,  
  dose = NULL,  
  doses.per.day = NULL,  
  initial.values = NULL,  
  plots = FALSE,  
  suppress.messages = FALSE,  
  species = "Human",  
  iv.dose = FALSE,  
  input.units = "mg/kg",  
  output.units = NULL,  
  method = "lsoda",  
  rtol = 1e-08,  
  atol = 1e-12,  
  default.to.human = FALSE,  
  recalc.blood2plasma = FALSE,  
  recalc.clearance = FALSE,  
  dosing.matrix = NULL,
```

```

adjusted.funbound.plasma = TRUE,
regression = TRUE,
restrictive.clearance = TRUE,
minimum.funbound.plasma = 1e-04,
monitor.vars = NULL,
...
)

```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
times	Optional time sequence for specified number of days.
parameters	Chemical parameters from parameterize_1comp function, overrides chem.name and chem.cas.
days	Length of the simulation.
tsteps	The number time steps per hour.
daily.dose	Total daily dose, default is mg/kg BW.
dose	Amount of a single dose, default is mg/kg BW.
doses.per.day	Number of doses per day.
initial.values	Vector containing the initial concentrations or amounts of the chemical in specified tissues with units corresponding to output.units. Defaults are zero.
plots	Plots all outputs if true.
suppress.messages	Whether or not the output message is suppressed.
species	Species desired (either "Rat", "Rabbit", "Dog", or default "Human").
iv.dose	Simulates a single i.v. dose if true.
input.units	Input units of interest assigned to dosing, defaults to "mg/kg" BW.
output.units	A named vector of output units expected for the model results. Default, NULL, returns model results in units specified in the 'modelinfo' file. See table below for details.
method	Method used by integrator (deSolve).
rtol	Argument passed to integrator (deSolve).
atol	Argument passed to integrator (deSolve).
default.to.human	Substitutes missing rat values with human values if true.
recalc.blood2plasma	Whether or not to recalculate the blood:plasma chemical concentration ratio
recalc.clearance	Whether or not to recalculate the elimination rate.
dosing.matrix	Vector of dosing times or a matrix consisting of two columns or rows named "dose" and "time" containing the time and amount, in mg/kg BW by default, of each dose.

<code>adjusted.funbound.plasma</code>	Uses <code>adjusted.funbound.plasma</code> when set to TRUE along with volume of distribution calculated with this value.
<code>regression</code>	Whether or not to use the regressions in calculating partition coefficients in volume of distribution calculation.
<code>restrictive.clearance</code>	In calculating elimination rate, protein binding is not taken into account (set to 1) in liver clearance if FALSE.
<code>minimum.funbound.plasma</code>	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured <code>Fup</code> in our dataset).
<code>monitor.vars</code>	Which variables are returned as a function of time. Defaults value of NULL provides "Agutlumen", "Ccompartment", "Ametabolized", "AUC"
<code>...</code>	Additional arguments passed to the integrator.

Details


Note that the model parameters have units of hours while the model output is in days.

Default value of NULL for `doses.per.day` solves for a single dose.

When `species` is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data (volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

AUC is area under plasma concentration curve.

Model Figure



altalt

Value

A matrix with a column for time(in days) and a column for the compartment and the area under the curve (concentration only).

Author(s)

Robert Pearce

References

Pearce, Robert G., et al. "Htk: R package for high-throughput toxicokinetics." Journal of statistical software 79.4 (2017): 1.

Examples

```
solve_1comp(chem.name='Bisphenol-A',days=1)
params <- parameterize_1comp(chem.cas="80-05-7")
solve_1comp(parameters=params)
```

solve_3comp

Solve_3comp

Description

This function solves for the amounts or concentrations of a chemical in different tissues as functions of time based on the dose and dosing frequency. It uses a three compartment model with partition coefficients.

Usage

```
solve_3comp(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  times = NULL,
  parameters = NULL,
  days = 10,
  tsteps = 4,
  daily.dose = NULL,
  dose = NULL,
  doses.per.day = NULL,
  initial.values = NULL,
  plots = FALSE,
  suppress.messages = FALSE,
  species = "Human",
  iv.dose = FALSE,
  input.units = "mg/kg",
  output.units = NULL,
  method = "lsoda",
  rtol = 1e-08,
  atol = 1e-12,
  default.to.human = FALSE,
  recalc.blood2plasma = FALSE,
  recalc.clearance = FALSE,
  dosing.matrix = NULL,
  adjusted.Funbound.plasma = TRUE,
  regression = TRUE,
  restrictive.clearance = TRUE,
  minimum.Funbound.plasma = 1e-04,
  monitor.vars = NULL,
  ...
)
```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's 'DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
times	Optional time sequence for specified number of days. The dosing sequence begins at the beginning of times.
parameters	Chemical parameters from parameterize_3comp function, overrides chem.name and chem.cas.
days	Length of the simulation.
tsteps	The number time steps per hour.
daily.dose	Total daily dose, mg/kg BW.
dose	Amount of a single dose, mg/kg BW.
doses.per.day	Number of doses per day.
initial.values	Vector containing the initial concentrations or amounts of the chemical in specified tissues with units corresponding to output.units. Defaults are zero.
plots	Plots all outputs if true.
suppress.messages	Whether or not the output message is suppressed.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
iv.dose	Simulates a single i.v. dose if true.
input.units	Input units of interest assigned to dosing, defaults to mg/kg BW
output.units	A named vector of output units expected for the model results. Default, NULL, returns model results in units specified in the 'modelinfo' file. See table below for details.
method	Method used by integrator (deSolve).
rtol	Argument passed to integrator (deSolve).
atol	Argument passed to integrator (deSolve).
default.to.human	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
recalc.blood2plasma	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters, calculated with hematocrit, Funbound.plasma, and Krbc2pu.
recalc.clearance	Recalculates the the hepatic clearance (Clmetabolism) with new million.cells.per.g liver parameter.
dosing.matrix	Vector of dosing times or a matrix consisting of two columns or rows named "dose" and "time" containing the time and amount, in mg/kg BW, of each dose.
adjusted.Funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
restrictive.clearance	Protein binding not taken into account (set to 1) in liver clearance if FALSE.

<code>minimum.funbound.plasma</code>	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).
<code>monitor.vars</code>	Which variables are returned as a function of time. Defaults value of NULL provides "Cliver", "Csyscomp", "Atubules", "Ametabolized", "AUC"
<code>...</code>	Additional arguments passed to the integrator.


Details

Note that the model parameters have units of hours while the model output is in days.

Default of NULL for `doses.per.day` solves for a single dose.

The compartments used in this model are the gutlumen, gut, liver, and rest-of-body, with the plasma equivalent to the liver plasma.

Model Figure



altalt

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

A matrix of class `deSolve` with a column for time(in days) and each compartment, the plasma concentration, area under the curve, and a row for each time point.

Author(s)

John Wambaugh and Robert Pearce

References

Pearce, Robert G., et al. "Htk: R package for high-throughput toxicokinetics." Journal of statistical software 79.4 (2017): 1.

Examples

```
solve_3comp(chem.name='Bisphenol-A',doses.per.day=2,daily.dose=.5,days=1,tsteps=2)

params <-parameterize_3comp(chem.cas="80-05-7")
solve_3comp(parameters=params)
```

solve_fetal_pbt

Solve_fetal_PBT

Description

This function solves for the amounts or concentrations in uM of a chemical in different tissues of a maternofetal system as functions of time based on the dose and dosing frequency.

Usage

```
solve_fetal_pbt(
  chem.name = NULL,
  chem.cas = NULL,
  dtxsid = NULL,
  times = seq(13 * 7, 40 * 7, 1),
  parameters = NULL,
  days = NULL,
  species = "human",
  tsteps = 4,
  dose = NULL,
  dosing.matrix = NULL,
  daily.dose = NULL,
  doses.per.day = NULL,
  initial.values = NULL,
  plots = FALSE,
  suppress.messages = FALSE,
  iv.dose = FALSE,
  input.units = "mg/kg",
  output.units = NULL,
  method = "lsoda",
  rtol = 1e-08,
  atol = 1e-12,
  default.to.human = FALSE,
  recalc.blood2plasma = FALSE,
  recalc.clearance = FALSE,
  adjusted.funbound.plasma = TRUE,
  regression = TRUE,
  restrictive.clearance = TRUE,
```

```

    minimum.Funbound.plasma = 1e-04,
    monitor.vars = NULL,
    ...
)

```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (http://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs
times	Optional time sequence in days. Dosing sequence begins at the beginning of times. Default is from 13th week of pregnancy to 40th due to data constraints.
parameters	Chemical parameters from parameterize_fetal_pbt function, overrides chem.name and chem.cas.
days	Length of the simulation.
species	Included for compatibility with other functions, but the model will not run for non-human species (default "Human").
tsteps	The number time steps per hour. Default of 4.
dose	Amount of a single dose, mg/kg BW.
dosing.matrix	A matrix of either one column (or row) with a set of dosing times or with two columns (or rows) correspondingly named "dose" and "time" containing the time and amount, in mg/kg BW, of each dose.
daily.dose	Total daily dose, mg.
doses.per.day	Number of doses per day.
initial.values	Vector containing the initial concentrations or amounts of the chemical in specified tissues with units corresponding to compartment.units. Defaults are zero.
plots	Plots all outputs if true.
suppress.messages	Whether or not the output message is suppressed.
iv.dose	Simulates a single i.v. dose if true.
input.units	Input units of interest assigned to dosing, defaults to mg/kg BW
output.units	A named vector of output units expected for the model results. Default, NULL, returns model results in units specified in the 'modelinfo' file. See table below for details.
method	Method used by integrator (deSolve).
rtol	Argument passed to integrator (deSolve).
atol	Argument passed to integrator (deSolve).
default.to.human	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
recalc.blood2plasma	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters, calculated with hematocrit, Funbound.plasma, and Krbc2pu.
recalc.clearance	Recalculates the the hepatic clearance (Clmetabolism) with new million.cells.per.g liver parameter.

<code>adjusted.funbound.plasma</code>	Uses <code>adjusted.funbound.plasma</code> when set to <code>TRUE</code> along with partition coefficients calculated with this value.
<code>regression</code>	Whether or not to use the regressions in calculating partition coefficients.
<code>restrictive.clearance</code>	Protein binding not taken into account (set to 1) in liver clearance if <code>FALSE</code> .
<code>minimum.funbound.plasma</code>	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured <code>Fup</code> in our dataset).
<code>monitor.vars</code>	Which variables to track by default
<code>...</code>	Additional arguments passed to the integrator.

Details

The stage of pregnancy simulated here begins by default at the 13th week due to a relative lack of data to support parameterization prior, in line with the recommendations of Kapraun et al. 2019 ("Empirical models for anatomical and physiological..."), and ends at the 40th week of pregnancy.

Note that the model parameters have units of hours while the model output is in days. Dose is in mg, not scaled for body weight.

Default `NULL` value for `doses.per.day` solves for a single dose.

The maternal compartments used in this model are the gut lumen, gut, liver, venous blood, arterial blood, lung, adipose tissue, kidney, thyroid, and rest of body. A placenta is modeled as a joint organ shared by mother and fetus, through which chemical exchange can occur with the fetus. Fetal compartments include arterial blood, venous blood, kidney, thyroid, liver, lung, gut, brain, and rest of body.

The extra compartments include the amounts or concentrations metabolized by the liver and excreted by the kidneys through the tubules.

AUC is the area under the curve of the plasma concentration.

This gestational model is only parameterized for humans.

Value

A matrix of class `deSolve` with a column for time(in days), each compartment, the area under the curve, and plasma concentration and a row for each time point.

Author(s)

John Wambaugh, Mark Sfeir, and Dustin Kapraun

Examples

```
out = solve_fetal_pbt(chem.name = 'bisphenol a', daily.dose = 1,
doses.per.day = 3, plots = TRUE)
```

solve_gas_pbtok	<i>solve_gas_pbtok</i>
-----------------	------------------------

Description

This function solves for the amounts or concentrations of a chemical in different tissues as functions of time as a result of inhalation exposure to an ideal gas.

Usage

```
solve_gas_pbtok(  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL,  
  parameters = NULL,  
  times = NULL,  
  days = 10,  
  tsteps = 4,  
  daily.dose = NULL,  
  doses.per.day = NULL,  
  dose = NULL,  
  dosing.matrix = NULL,  
  forcings = NULL,  
  exp.start.time = 0,  
  exp.conc = 1,  
  period = 24,  
  exp.duration = 12,  
  initial.values = NULL,  
  plots = FALSE,  
  suppress.messages = FALSE,  
  species = "Human",  
  iv.dose = FALSE,  
  input.units = "ppmv",  
  output.units = NULL,  
  method = "lsoda",  
  rtol = 1e-08,  
  atol = 1e-12,  
  default.to.human = FALSE,  
  recalc.blood2plasma = FALSE,  
  recalc.clearance = FALSE,  
  adjusted.funbound.plasma = TRUE,  
  regression = TRUE,  
  restrictive.clearance = TRUE,  
  minimum.funbound.plasma = 1e-04,  
  monitor.vars = NULL,  
  vmax = 0,  
  km = 1,  
  exercise = FALSE,  
  fR = 12,  
  VT = 0.75,  
  VD = 0.15,
```

```
    ...  
)
```

Arguments

chem.name	Either the chemical name, CAS number, or the parameters must be specified.
chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXIDs
parameters	Chemical parameters from parameterize_gas_pbt (or other bespoke) function, overrides chem.name and chem.cas.
times	Optional time sequence for specified number of days. Dosing sequence begins at the beginning of times.
days	Length of the simulation.
tsteps	The number of time steps per hour.
daily.dose	Total daily dose
doses.per.day	Number of doses per day.
dose	Amount of a single dose
dosing.matrix	Vector of dosing times or a matrix consisting of two columns or rows named "dose" and "time" containing the time and amount of each dose.
forcings	Manual input of 'forcings' data series argument for ode integrator. If left unspecified, 'forcings' defaults to NULL, and then other input parameters (see exp.start.time, exp.conc, exp.duration, and period) provide the necessary information to assemble a forcings data series.
exp.start.time	Start time in specifying forcing exposure series, default 0.
exp.conc	Specified inhalation exposure concentration for use in assembling "forcings" data series argument for integrator. Defaults to units of ppmv.
period	For use in assembling forcing function data series 'forcings' argument, specified in hours
exp.duration	For use in assembling forcing function data series 'forcings' argument, specified in hours
initial.values	Vector containing the initial concentrations or amounts of the chemical in specified tissues with units corresponding to those specified for the model outputs. Default values are zero.
plots	Plots all outputs if true.
suppress.messages	Whether or not the output message is suppressed.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
iv.dose	Simulates a single i.v. dose if true.
input.units	Input units of interest assigned to dosing, including forcings. Defaults to "ppmv" as applied to the default forcings scheme.
output.units	A named vector of output units expected for the model results. Default, NULL, returns model results in units specified in the 'modelinfo' file. See table below for details.
method	Method used by integrator (deSolve).
rtol	Argument passed to integrator (deSolve).

<code>atol</code>	Argument passed to integrator (deSolve).
<code>default.to.human</code>	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
<code>recalc.blood2plasma</code>	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters, calculated with hematocrit, <code>Funbound.plasma</code> , and <code>Krbc2pu</code> .
<code>recalc.clearance</code>	Recalculates the hepatic clearance (<code>Clmetabolism</code>) with new <code>million.cells.per.gliver</code> parameter.
<code>adjusted.Funbound.plasma</code>	Uses adjusted <code>Funbound.plasma</code> when set to TRUE along with partition coefficients calculated with this value.
<code>regression</code>	Whether or not to use the regressions in calculating partition coefficients.
<code>restrictive.clearance</code>	Protein binding not taken into account (set to 1) in liver clearance if FALSE.
<code>minimum.Funbound.plasma</code>	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured <code>Fup</code> in our dataset).
<code>monitor.vars</code>	Which variables are returned as a function of time. Defaults value of NULL provides "Cgut", "Cliver", "Cven", "Clung", "Cart", "Crest", "Ckidney", "Cplasma", "Calv", "Cendexh", "Cmixexh", "Cmuc", "Atubules", "Ametabolized", "AUC"
<code>vmax</code>	Michaelis-Menten <code>vmax</code> value in reactions/min
<code>km</code>	Michaelis-Menten concentration of half-maximal reaction velocity in desired output concentration units.
<code>exercise</code>	Logical indicator of whether to simulate an exercise-induced heightened respiration rate
<code>fR</code>	Respiratory frequency (breaths/minute), used especially to adjust breathing rate in the case of exercise. This parameter, along with <code>VT</code> and <code>VD</code> (below) gives another option for calculating <code>Qalv</code> (Alveolar ventilation) in case pulmonary ventilation rate is not known
<code>VT</code>	Tidal volume (L), to be modulated especially as part of simulating the state of exercise
<code>VD</code>	Anatomical dead space (L), to be modulated especially as part of simulating the state of exercise
<code>...</code>	Additional arguments passed to the integrator.

Details

The default dosing scheme involves a specification of the start time of exposure (`exp.start.time`), the concentration of gas inhaled (`exp.conc`), the period of a cycle of exposure and non-exposure (`period`), the duration of the exposure during that period (`exp.duration`), and the total days simulated. Together, these arguments determine the "forcings" passed to the ODE integrator. Forcings can also be specified manually, or effectively turned off by setting exposure concentration to zero, if the user prefers to simulate dosing by other means.

The "forcings" object is configured to be passed to the integrator with, at the most, a basic unit conversion among ppmv, mg/L, and uM. No scaling by BW is set to be performed on the forcings series.

Note that the model parameters have units of hours while the model output is in days.


Default NULL value for doses.per.day solves for a single dose.

The compartments used in this model are the gut lumen, gut, liver, kidneys, veins, arteries, lungs, and the rest of the body.

The extra compartments include the amounts or concentrations metabolized by the liver and excreted by the kidneys through the tubules.

AUC is the area under the curve of the plasma concentration.

Model Figure from (Linakis et al. 2020):



altalt

Model parameters are named according to the following convention:

prefix	suffic	Meaning	units
K		Partition coefficient for tissue to free plasma \ tab	unitless
V		Volume	L

Q		Flow	L/h
k		Rate	1/h
c	Parameter is proportional to body weight	1 / kg for volumes and 1/kg ^(3/4) for flows	

When species is specified but chemical-specific in vitro data are not available, the function uses the appropriate physiological data (volumes and flows) but `default.to.human = TRUE` must be used to substitute human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

A matrix of class `deSolve` with a column for time(in days), each compartment, the area under the curve, and plasma concentration and a row for each time point.

Author(s)

Matt Linakis, John Wambaugh, Mark Sfeir, Miyuki Breen

References

Linakis MW, Sayre RR, Pearce RG, Sfeir MA, Sipes NS, Pangburn HA, Gearhart JM, Wambaugh JF (2020). "Development and evaluation of a high-throughput inhalation model for organic chemicals." *Journal of exposure science & environmental epidemiology*, **30**(5), 866–877.

Pearce RG, Setzer RW, Strope CL, Wambaugh JF, Sipes NS (2017). "Httk: R package for high-throughput toxicokinetics." *Journal of statistical software*, **79**(4), 1.

Examples

```
solve_gas_pbt(chem.name = 'pyrene', exp.conc = 1, period = 24, expduration = 24)
```

```
out <- solve_gas_pbt(chem.name='pyrene',exp.conc = 0, doses.per.day = 2,
daily.dose = 3, input.units = "umol", plots=TRUE,initial.values=c(Aven=20))
```

```
out <- solve_gas_pbt(chem.name = 'pyrene',exp.conc = 3, period = 24,
exp.duration = 6, exercise = TRUE)
```

```
params <- parameterize_gas_pbt(chem.cas="80-05-7")
solve_gas_pbt(parameters=params)
```

```
# Note that different model compartments for this model have different units
# and that the final units can be controlled with the output.units argument:
head(solve_gas_pbt(chem.name="lindane"))
# Convert all compartment units to mg/L:
head(solve_gas_pbt(chem.name="lindane",output.units="mg/L"))
# Convert just the plasma to mg/L:
head(solve_gas_pbt(chem.name="lindane",output.units=list(Cplasma="mg/L")))
```

`solve_model`*Solve_model*

Description

`solve_model` is designed to accept systematized metadata (provided by the `model.list` defined in the `modelinfo` files) for a given toxicokinetic model, including names of variables, parameterization functions, and key units, and use it along with chemical information to prepare an ode system for numerical solution over time of the amounts or concentrations of chemical in different bodily compartments of a given species (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").

Usage

```
solve_model(  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL,  
  times = NULL,  
  parameters = NULL,  
  model = NULL,  
  route = "oral",  
  dosing = NULL,  
  days = 10,  
  tsteps = 4,  
  initial.values = NULL,  
  initial.value.units = NULL,  
  plots = FALSE,  
  monitor.vars = NULL,  
  suppress.messages = FALSE,  
  species = "Human",  
  input.units = "mg/kg",  
  output.units = NULL,  
  method = "lsoda",  
  rtol = 1e-08,  
  atol = 1e-12,  
  recalc.blood2plasma = FALSE,  
  recalc.clearance = FALSE,  
  adjusted.funbound.plasma = TRUE,  
  minimum.funbound.plasma = 1e-04,  
  parameterize.arg.list = list(default.to.human = FALSE, clint.pvalue.threshold = 0.05,  
    restrictive.clearance = TRUE, regression = TRUE),  
  ...  
)
```

Arguments

<code>chem.name</code>	Either the chemical name, CAS number, or the parameters must be specified.
<code>chem.cas</code>	Either the chemical name, CAS number, or the parameters must be specified.
<code>dtxsid</code>	EPA's DSSTox Structure ID (http://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXSIDs

times	Optional time sequence for specified number of days. Dosing sequence begins at the beginning of times.
parameters	List of chemical parameters, as output by parameterize_pbtk function. Overrides chem.name and chem.cas.
model	Specified model to use in simulation: "pbtk", "3compartment", "3compartmentss", "1compartment", "schmitt", ...
route	String specification of route of exposure for simulation: "oral", "iv", "inhalation", ...
dosing	List of dosing metrics used in simulation, which includes the namesake entries of a model's associated dosing.params. In the case of most htk models, these should include "initial.dose", "doses.per.day", "daily.dose", and "dosing.matrix". The "dosing.matrix" is used for more precise dose regimen specification, and is a matrix consisting of two columns or rows named "time" and "dose" containing the time and amount of each dose. If none of the namesake entries of the dosing list is set to a non-NULL value, solve_model uses a default dose of 1 mg/kg BW along with the dose type (add/multiply) specified for a given route (e.g. add the dose to gut lumen for oral route)
days	Simulated period. Default 10 days.
tsteps	The number of time steps per hour. Default of 4.
initial.values	Vector of numeric values containing the initial concentrations or amounts of the chemical in specified tissues with units corresponding to those specified for the model outputs. Default values are zero.
initial.value.units	Vector of character strings containing the units corresponding to 'initial.values' specified for the model outputs. Default is assuming the units match expected compartment units for the model.
plots	Plots all outputs if true.
monitor.vars	Which variables are returned as a function of time. Default values of NULL looks up variables specified in modelinfo_MODEL.R
suppress.messages	Whether or not the output messages are suppressed.
species	Species desired (models have been designed to be parameterized for some subset of the following species: "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
input.units	Input units of interest assigned to dosing. Defaults to mg/kg BW, in line with the default dosing scheme of a one-time dose of 1 mg/kg in which no other dosing parameters are specified.
output.units	Output units of interest for the compiled components. Defaults to NULL, and will provide values in model units if unspecified.
method	Method used by integrator (deSolve).
rtol	Argument passed to integrator (deSolve).
atol	Argument passed to integrator (deSolve).
recalc.blood2plasma	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters, calculated with hematocrit, Funbound.plasma, and Krbc2pu.
recalc.clearance	Recalculates the the hepatic clearance (Clmetabolism) with new million.cells.per.g liver parameter.

adjusted.funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
minimum.funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset)
parameterize.arg.list	Additional parameterized passed to the model parameterization function.
...	Additional arguments passed to the integrator.
default.to.human	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
regression	Whether or not to use the regressions in calculating partition coefficients.
restrictive.clearance	Protein binding not taken into account (set to 1) in liver clearance if FALSE.

Details

Dosing values with certain acceptable associated input.units (like mg/kg BW) are configured to undergo a unit conversion. All model simulations are intended to run with units as specified by "compartment.units" in the model.list (as defined by the modelinfo files).

The 'dosing' argument includes all parameters needed to describe exposure in terms of route of administration, frequency, and quantity short of scenarios that require use of a more precise forcing function. If the dosing argument's namesake entries are left NULL, solve_model defaults to a single-time dose of 1 mg/kg BW according to the given dosing route and associated type (either add/multiply, for example we typically add a dose to gut lumen when oral route is specified).

AUC is the area under the curve of the plasma concentration.

Model parameters are named according to the following convention:

prefix	suffix	Meaning	units
K		Partition coefficient for tissue to free plasma	unitless
V		Volume	L
Q		Flow	L/h
k		Rate	1/h
	c	Parameter is proportional to body weight	1 / kg for volumes and 1/kg ^(3/4) for flows

When species is specified but chemical-specific in vitro data are not available, the function uses the appropriate physiological data (volumes and flows) but default.to.human = TRUE must be used to substitute human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

A matrix of class deSolve with a column for time(in days), each compartment, the area under the curve, and plasma concentration and a row for each time point.

Author(s)

John Wambaugh, Robert Pearce, Miyuki Breen, Mark Sfeir, and Sarah E. Davidson

References

Pearce, Robert G., et al. "Htk: R package for high-throughput toxicokinetics." Journal of statistical software 79.4 (2017): 1.

solve_pbt

Solve_PBT

Description

This function solves for the amounts or concentrations in uM of a chemical in different tissues as functions of time based on the dose and dosing frequency.

Usage

```
solve_pbt(  
  chem.name = NULL,  
  chem.cas = NULL,  
  dtxsid = NULL,  
  times = NULL,  
  parameters = NULL,  
  days = 10,  
  tsteps = 4,  
  daily.dose = NULL,  
  dose = NULL,  
  doses.per.day = NULL,  
  initial.values = NULL,  
  plots = FALSE,  
  suppress.messages = FALSE,  
  species = "Human",  
  iv.dose = FALSE,  
  input.units = "mg/kg",  
  output.units = NULL,  
  method = "lsoda",  
  rtol = 1e-08,  
  atol = 1e-12,  
  default.to.human = FALSE,  
  recalc.blood2plasma = FALSE,  
  recalc.clearance = FALSE,  
  dosing.matrix = NULL,  
  adjusted.funbound.plasma = TRUE,  
  regression = TRUE,  
  restrictive.clearance = TRUE,  
  minimum.funbound.plasma = 1e-04,  
  monitor.vars = NULL,  
  ...  
)
```

Arguments

chem.name Either the chemical name, CAS number, or the parameters must be specified.

chem.cas	Either the chemical name, CAS number, or the parameters must be specified.
dtxsid	EPA's DSSTox Structure ID (https://comptox.epa.gov/dashboard) the chemical must be identified by either CAS, name, or DTXIDs
times	Optional time sequence for specified number of days. Dosing sequence begins at the beginning of times.
parameters	Chemical parameters from parameterize_pbt function, overrides chem.name and chem.cas.
days	Length of the simulation.
tsteps	The number of time steps per hour.
daily.dose	Total daily dose, defaults to mg/kg BW.
dose	Amount of a single dose, defaults to mg/kg BW.
doses.per.day	Number of doses per day.
initial.values	Vector containing the initial concentrations or amounts of the chemical in specified tissues with units corresponding to output.units. Defaults are zero.
plots	Plots all outputs if true.
suppress.messages	Whether or not the output message is suppressed.
species	Species desired (either "Rat", "Rabbit", "Dog", "Mouse", or default "Human").
iv.dose	Simulates a single i.v. dose if true.
input.units	Input units of interest assigned to dosing, defaults to mg/kg BW
output.units	A named vector of output units expected for the model results. Default, NULL, returns model results in units specified in the 'modelinfo' file. See table below for details.
method	Method used by integrator (deSolve).
rtol	Argument passed to integrator (deSolve).
atol	Argument passed to integrator (deSolve).
default.to.human	Substitutes missing animal values with human values if true (hepatic intrinsic clearance or fraction of unbound plasma).
recalc.blood2plasma	Recalculates the ratio of the amount of chemical in the blood to plasma using the input parameters, calculated with hematocrit, Funbound.plasma, and Krbc2pu.
recalc.clearance	Recalculates the the hepatic clearance (Clmetabolism) with new million.cells.per.g liver parameter.
dosing.matrix	Vector of dosing times or a matrix consisting of two columns or rows named "dose" and "time" containing the time and amount, in mg/kg BW, of each dose.
adjusted.Funbound.plasma	Uses adjusted Funbound.plasma when set to TRUE along with partition coefficients calculated with this value.
regression	Whether or not to use the regressions in calculating partition coefficients.
restrictive.clearance	Protein binding not taken into account (set to 1) in liver clearance if FALSE.
minimum.Funbound.plasma	Monte Carlo draws less than this value are set equal to this value (default is 0.0001 – half the lowest measured Fup in our dataset).

`monitor.vars` Which variables are returned as a function of time. The default value of NULL provides "Cgut", "Cliver", "Cven", "Clung", "Cart", "Crest", "Ckidney", "Cplasma", "Atubules", "Ametabolized", and "AUC"

... Additional arguments passed to the integrator.

Details

Note that the model parameters have units of hours while the model output is in days.


Default NULL value for `doses.per.day` solves for a single dose.

The compartments used in this model are the gutlumen, gut, liver, kidneys, veins, arteries, lungs, and the rest of the body.

The extra compartments include the amounts or concentrations metabolized by the liver and excreted by the kidneys through the tubules.

AUC is the area under the curve of the plasma concentration.

Model Figure



altalt

When species is specified as rabbit, dog, or mouse, the function uses the appropriate physiological data(volumes and flows) but substitutes human fraction unbound, partition coefficients, and intrinsic hepatic clearance.

Value

A matrix of class `deSolve` with a column for time(in days), each compartment, the area under the curve, and plasma concentration and a row for each time point.

Author(s)

John Wambaugh and Robert Pearce

References

Pearce, Robert G., et al. "Httk: R package for high-throughput toxicokinetics." Journal of statistical software 79.4 (2017): 1.

Examples

```
# Multiple doses per day:
head(solve_pbt(
  chem.name='Bisphenol-A',
  daily.dose=.5,
  days=5,
  doses.per.day=2,
  tsteps=2))

# Starting with an initial concentration:
out <- solve_pbt(
  chem.name='bisphenola',
  dose=0,
  output.units="mg/L",
  initial.values=c(Agut=200))

# Working with parameters (rather than having solve_pbt retrieve them):
params <- parameterize_pbt(chem.cas="80-05-7")
head(solve_pbt(parameters=params))

# We can change the parameters given to us by parameterize_pbt:
params <- parameterize_pbt(dtcsid="DTXSID4020406", species = "rat")
params["Funbound.plasma"] <- 0.1
out <- solve_pbt(parameters=params)

# A fifty day simulation:
out <- solve_pbt(
  chem.name = "Bisphenol A",
  days = 50,
  daily.dose=1,
  doses.per.day = 3)
plot.data <- as.data.frame(out)
css <- calc_analytic_css(chem.name = "Bisphenol A")

library("ggplot2")
c.vs.t <- ggplot(plot.data, aes(time, Cplasma)) +
  geom_line() +
  geom_hline(yintercept = css) +
  ylab("Plasma Concentration (uM)") +
  xlab("Day") +
  theme(
    axis.text = element_text(size = 16),
    axis.title = element_text(size = 16),
    plot.title = element_text(size = 17)) +
  ggtitle("Bisphenol A")
```

```
print(c.vs.t)
```

spleen_mass_children	<i>Predict spleen mass for children</i>
----------------------	---

Description

For individuals under 18, predict the spleen mass from height, weight, and gender, using equations from Ogiu et al. (1997)

Usage

```
spleen_mass_children(height, weight, gender)
```

Arguments

height	Vector of heights in cm.
weight	Vector of weights in kg.
gender	Vector of genders (either 'Male' or 'Female').

Value

A vector of spleen masses in kg.

Author(s)

Caroline Ring

References

Ogiu, Nobuko, et al. "A statistical analysis of the internal organ weights of normal Japanese people." *Health physics* 72.3 (1997): 368-383.

Price, Paul S., et al. "Modeling interindividual variation in physiological factors used in PBPK models of humans." *Critical reviews in toxicology* 33.5 (2003): 469-503.

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

spline_heightweight	<i>Smoothing splines for log height vs. age and log body weight vs. age, along with 2-D KDE residuals, by race and gender.</i>
---------------------	--

Description

#'Smoothing splines and KDE fits to joint distribution of height and weight residuals pre-calculated from NHANES height, weight, and age data by race/ethnicity and gender.

Usage

```
spline_heightweight
```

Format

A data.table with 6 variables:

g Gender: Male or Female

r Race/ethnicity: Mexican American, Other Hispanic, Non-Hispanic White, Non-Hispanic Black, Other

height_spline A list of smooth.spline objects, each giving a smoothed relationship between log height in cm and age in months

weight_spline A list of smooth.spline objects, each giving a smoothed relationship between log body weight in kg and age in months

hw_kde A list of kde objects; each is a 2-D KDE of the distribution of log height and log body weight residuals about the smoothing splines.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

spline_hematocrit	<i>Smoothing splines for log hematocrit vs. age in months, and KDE residuals, by race and gender.</i>
-------------------	---

Description

Smoothing splines and KDE residuals pre-calculated from NHANES hematocrit and age data by race/ethnicity and gender.

Usage

```
spline_hematocrit
```


Format

A data.table with 6 variables:

gender Gender: Male or Female

reth Race/ethnicity: Mexican American, Other Hispanic, Non-Hispanic White, Non-Hispanic Black, Other

hct_spline A list of smooth.spline objects, each giving a smoothed relationship between log hematocrit and age in months

hct_kde A list of kde objects; each is a KDE of the distribution of residuals about the smoothing spline.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

spline_serumcreat	<i>Smoothing splines for log serum creatinine vs. age in months, along with KDE residuals, by race and gender.</i>
-------------------	--

Description

Smoothing splines and KDE residuals pre-calculated from NHANES serum creatinine and age data by race/ethnicity and gender.

Usage

spline_serumcreat

Format

A data.table with 6 variables:

gender Gender: Male or Female

reth Race/ethnicity: Mexican American, Other Hispanic, Non-Hispanic White, Non-Hispanic Black, Other

sc_spline A list of smooth.spline objects, each giving a smoothed relationship between log serum creatinine and age in months

sc_kde A list of kde objects; each is a KDE of the distribution of residuals about the smoothing spline.

Author(s)

Caroline Ring

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

supptab1_Linakis2020 *Supplementary output from Linakis 2020 vignette analysis.*

Description

Supplementary output from Linakis 2020 vignette analysis.

Usage

supptab1_Linakis2020

Format

A data.frame containing x rows and y columns.

Author(s)

Matt Linakis

Source

Matt Linakis

References

DSStox database ([https:// www.epa.gov/ncct/dsstox](https://www.epa.gov/ncct/dsstox))

supptab2_Linakis2020 *More supplementary output from Linakis 2020 vignette analysis.*

Description

More supplementary output from Linakis 2020 vignette analysis.

Usage

supptab2_Linakis2020

Format

A data.frame containing x rows and y columns.

Author(s)

Matt Linakis

Source

Matt Linakis

References

DSStox database ([https:// www.epa.gov/ncct/dsstox](https://www.epa.gov/ncct/dsstox))

Tables.Rdata.stamp	<i>A timestamp of table creation</i>
--------------------	--------------------------------------

Description

The Tables.RData file is separately created as part of building a new release of HTTK. This time stamp indicates the script used to build the file and when it was run.

Usage

Tables.Rdata.stamp

Format

An object of class character of length 1.

Author(s)

John Wambaugh

tissue.data	<i>Tissue composition and species-specific physiology parameters</i>
-------------	--

Description

This data set contains values from Schmitt (2008) and Ruark et al. (2014) describing the composition of specific tissues and from Birnbaum et al. (1994) describing volumes of and blood flows to those tissues, allowing parameterization of toxicokinetic models for human, mouse, rat, dog, or rabbit. Tissue volumes were calculated by converting the fractional mass of each tissue with its density (both from ICRP), lumping the remaining tissues into the rest-of-body, excluding the mass of the gastrointestinal contents

Usage

tissue.data

Format

A data.frame containing 13 rows and 20 columns.

Author(s)

John Wambaugh, Robert Pearce, and Nisha Sipes

Source

Pearce et al. (2017), in preparation,

Wambaugh, John F., et al. "Toxicokinetic triage for environmental chemicals." *Toxicological Sciences* (2015): 228-237.

References

Birnbaum, L and Brown, R and Bischoff, K and Foran, J and Blancato, J and Clewell, H and Dedrick, R (1994). Physiological parameter values for PBPK model. International Life Sciences Institute, Risk Science Institute, Washington, DC

Ruark, Christopher D., et al. "Predicting passive and active tissue: plasma partition coefficients: Interindividual and interspecies variability." *Journal of pharmaceutical sciences* 103.7 (2014): 2189-2198.

Schmitt, W. (2008). General approach for the calculation of tissue to plasma partition coefficients. *Toxicology in vitro : an international journal published in association with BIBRA* 22(2), 457-67, 10.1016/j.tiv.2007.09.010.

ICRP. Report of the Task Group on Reference Man. ICRP Publication 23 1975

tissue_masses_flows	<i>Given a data.table describing a virtual population by the NHANES quantities, generates HHTK physiological parameters for each individual.</i>
---------------------	--

Description

Given a data.table describing a virtual population by the NHANES quantities, generates HHTK physiological parameters for each individual.

Usage

```
tissue_masses_flows(tmf_dt)
```

Arguments

tmf_dt	A data.table generated by <code>gen_age_height_weight()</code> , containing variables gender, reth, age_months, age_years, weight, and height.
--------	--

Value

The same data.table, with additional variables describing tissue masses and flows.

Author(s)

Caroline Ring

References

- Barter, Zoe E., et al. "Scaling factors for the extrapolation of in vivo metabolic drug clearance from in vitro data: reaching a consensus on values of human micro-somal protein and hepatocellularity per gram of liver." *Current Drug Metabolism* 8.1 (2007): 33-45.
- Birnbaum, L., et al. "Physiological parameter values for PBPK models." International Life Sciences Institute, Risk Science Institute, Washington, DC (1994).
- Geigy Pharmaceuticals, "Scientific Tables", 7th Edition, John Wiley and Sons (1970)
- McNally, Kevin, et al. "PopGen: a virtual human population generator." *Toxicology* 315 (2014): 70-85.
- Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

tissue_scale	<i>Allometric scaling.</i>
--------------	----------------------------

Description

Allometrically scale a tissue mass or flow based on $\text{height}^{3/4}$.

Usage

```
tissue_scale(height_ref, height_indiv, tissue_mean_ref)
```

Arguments

height_ref	Reference height in cm.
height_indiv	Individual height in cm.
tissue_mean_ref	Reference tissue mass or flow.

Value

Allometrically scaled tissue mass or flow, in the same units as `tissue_mean_ref`.

Author(s)

Caroline Ring

References

- Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

wambaugh2019

*in vitro Toxicokinetic Data from Wambaugh et al. (2019)***Description**

These data are the new HTTK in vitro data for chemicals reported in Wambaugh et al. (2019). They are the processed values used to make the figures in that manuscript. These data summarize the results of Bayesian analysis of the in vitro toxicokinetic experiments conducted by Cyprotex to characterize fraction unbound in the presence of pooled human plasma protein and the intrinsic hepatic clearance of the chemical by pooled human hepatocytes.

Usage

wambaugh2019

Format

A data frame with 496 rows and 17 variables:

Compound The name of the chemical

CAS The Chemical Abstracts Service Registry Number

Human.Clint Median of Bayesian credible interval for intrinsic hepatic clearance (uL/min/million hepatocytes)]

Human.Clint.pValue Probability that there is no clearance

Human.Funbound.plasma Median of Bayesian credible interval for fraction of chemical free in the presence of plasma

pKa_Accept pH(s) at which hydrogen acceptor sites (if any) are at equilibrium

pKa_Donor pH(s) at which hydrogen donor sites (if any) are at equilibrium

DSTox_Substance_Id Identifier for CompTox Chemical Dashboard

SMILES Simplified Molecular-Input Line-Entry System structure description

Human.Clint.Low95 Lower 95th percentile of Bayesian credible interval for intrinsic hepatic clearance (uL/min/million hepatocytes)

Human.Clint.High95 Upper 95th percentile of Bayesian credible interval for intrinsic hepatic clearance (uL/min/million hepatocytes)

Human.Clint.Point Point estimate of intrinsic hepatic clearance (uL/min/million hepatocytes)

Human.Funbound.plasma.Low95 Lower 95th percentile of Bayesian credible interval for fraction of chemical free in the presence of plasma

Human.Funbound.plasma.High95 Upper 95th percentile of Bayesian credible interval for fraction of chemical free in the presence of plasma

Human.Funbound.plasma.Point Point estimate of the fraction of chemical free in the presence of plasma

MW Molecular weight (Daltons)

logP log base ten of octanol:water partition coefficient

Author(s)

John Wambaugh

Source

Wambaugh et al. (2019)

References

Wambaugh et al. (2019) "Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization", *Toxicological Sciences*, 172(2), 235-251.

wambaugh2019.nhanes	<i>NHANES Chemical Intake Rates for chemicals in Wambaugh et al. (2019)</i>
---------------------	---

Description

These data are a subset of the Bayesian inferences reported by Ring et al. (2017) from the U.S. Centers for Disease Control and Prevention (CDC) National Health and Nutrition Examination Survey (NHANES). They reflect the population median intake rate (mg/kg body weight/day), with uncertainty.

Usage

wambaugh2019.nhanes

Format

A data frame with 20 rows and 4 variables:

IP The median of the Bayesian credible interval for median population intake rate (mg/kg body-weight/day)

IP.min The lower 95th percentile of the Bayesian credible interval for median population intake rate (mg/kg bodyweight/day)

IP.max The upper 95th percentile of the Bayesian credible interval for median population intake rate (mg/kg bodyweight/day)

CASRN The Chemical Abstracts Service Registry Number

Author(s)

John Wambaugh

Source

Wambaugh et al. (2019)

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment international* 106 (2017): 105-118

Wambaugh et al. (2019) "Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization", *Toxicological Sciences*, 172(2), 235-251.

wambaugh2019.raw

*Raw Bayesian in vitro Toxicokinetic Data Analysis from Wambaugh et al. (2019)***Description**

These data are the new HTTK in vitro data for chemicals reported in Wambaugh et al. (2019). They are the output of different Bayesian models evaluated to compare using a single protein concentration vs. the new three concentration titration protocol. These data summarize the results of Bayesian analysis of the in vitro toxicokinetic experiments conducted by Cyprotex to characterize fraction unbound in the presence of pooled human plasma protein and the intrinsic hepatic clearance of the chemical by pooled human hepatocytes. This file includes replicates (different Compound-Name id's but same chemical')

Usage

wambaugh2019.raw

Format

A data frame with 530 rows and 28 variables:

DTXSID Identifier for CompTox Chemical Dashboard

Name The name of the chemical

CAS The Chemical Abstracts Service Registry Number

CompoundName Sample name provided by EPA to Cyprotex

Fup.point Point estimate of the fraction of chemical free in the presence of plasma

Base.Fup.Med Median of Bayesian credible interval for fraction of chemical free in the presence of plasma for analysis of 100 physiological plasma protein data only (base model)

Base.Fup.Low Lower 95th percentile of Bayesian credible interval for fraction of chemical free in the presence of plasma for analysis of 100 physiological plasma protein data only (base model)

Base.Fup.High Upper 95th percentile of Bayesian credible interval for fraction of chemical free in the presence of plasma for analysis of 100 physiological plasma protein data only (base model)

Affinity.Fup.Med Median of Bayesian credible interval for fraction of chemical free in the presence of plasma for analysis of protein titration protocol data (affinity model)

Affinity.Fup.Low Lower 95th percentile of Bayesian credible interval for fraction of chemical free in the presence of plasma for analysis of protein titration protocol data (affinity model)

Affinity.Fup.High Upper 95th percentile of Bayesian credible interval for fraction of chemical free in the presence of plasma for analysis of protein titration protocol data (affinity model)

Affinity.Kd.Med Median of Bayesian credible interval for protein binding affinity from analysis of protein titration protocol data (affinity model)

Affinity.Kd.Low Lower 95th percentile of Bayesian credible interval for protein binding affinity from analysis of protein titration protocol data (affinity model)

Affinity.Kd.High Upper 95th percentile of Bayesian credible interval for protein binding affinity from analysis of protein titration protocol data (affinity model)

Decreases.Prob Probability that the chemical concentration decreased systematically during hepatic clearance assay.

Saturates.Prob Probability that the rate of chemical concentration decrease varied between the 1 and 10 uM hepatic clearance experiments.

Slope.1uM.Median Estimated slope for chemical concentration decrease in the 1 uM hepatic clearance assay.

Slope.10uM.Median Estimated slope for chemical concentration decrease in the 10 uM hepatic clearance assay.

CLint.1uM.Median Median of Bayesian credible interval for intrinsic hepatic clearance at 1 uM initial chemical concentration (uL/min/million hepatocytes)]

CLint.1uM.Low95th Lower 95th percentile of Bayesian credible interval for intrinsic hepatic clearance at 1 uM initial chemical concentration (uL/min/million hepatocytes)

CLint.1uM.High95th Upper 95th percentile of Bayesian credible interval for intrinsic hepatic clearance at 1 uM initial chemical concentration (uL/min/million hepatocytes)

CLint.10uM.Median Median of Bayesian credible interval for intrinsic hepatic clearance at 10 uM initial chemical concentration (uL/min/million hepatocytes)]

CLint.10uM.Low95th Lower 95th percentile of Bayesian credible interval for intrinsic hepatic clearance at 10 uM initial chemical concentration (uL/min/million hepatocytes)

CLint.10uM.High95th Upper 95th percentile of Bayesian credible interval for intrinsic hepatic clearance at 10 uM initial chemical concentration (uL/min/million hepatocytes)

CLint.1uM.Point Point estimate of intrinsic hepatic clearance (uL/min/million hepatocytes) for 1 uM initial chemical concentration

CLint.10uM.Point Point estimate of intrinsic hepatic clearance (uL/min/million hepatocytes) for 10 uM initial chemical concentration

Fit Classification of clearance observed

SMILES Simplified Molecular-Input Line-Entry System structure description

Author(s)

John Wambaugh

Source

Wambaugh et al. (2019)

References

Wambaugh et al. (2019) "Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization", *Toxicological Sciences*, 172(2), 235-251.

wambaugh2019.seem3	<i>ExpoCast SEEM3 Consensus Exposure Model Predictions for Chemical Intake Rates</i>
--------------------	--

Description

These data are a subset of the Bayesian inferences reported by Ring et al. (2019) for a consensus model of twelve exposure predictors. The predictors were calibrated based upon their ability to predict intake rates inferred National Health and Nutrition Examination Survey (NHANES). They reflect the population median intake rate (mg/kg body weight/day), with uncertainty.

Usage

wambaugh2019.seem3

Format

A data frame with 385 rows and 38 variables:

Author(s)

John Wambaugh

Source

Wambaugh et al. (2019)

References

Ring, Caroline L., et al. "Consensus modeling of median chemical intake for the US population based on predictions of exposure pathways." *Environmental science & technology* 53.2 (2018): 719-732.

Wambaugh et al. (2019) "Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization", *Toxicological Sciences*, 172(2), 235-251.

wambaugh2019.tox21	<i>Tox21 2015 Active Hit Calls (EPA)</i>
--------------------	--

Description

The ToxCast and Tox21 research programs employ batteries of high-throughput assays to assess chemical bioactivity in vitro. Not every chemical is tested through every assay. Most assays are conducted in concentration response, and each corresponding assay endpoint is analyzed statistically to determine if there is a concentration-dependent response or "hit" using the ToxCast Pipeline. Most assay endpoint-chemical combinations are non-responsive. Here, only the hits are treated as potential indicators of bioactivity. This bioactivity does not have a direct toxicological interpretation. The October 2015 release (invitrodb_v2) of the ToxCast and Tox21 data were used for this analysis. This object contains just the chemicals in Wambaugh et al. (2019) and only the quantiles across all assays for the ACC.

Usage

wambaugh2019.tox21

Format

A data.table with 401 rows and 6 columns

Author(s)

John Wambaugh

Source

ftp://newftp.epa.gov/COMPTOX/High_Throughput_Screening_Data/Previous_Data/ToxCast_Data_Release_Oct_2015/

References

Kavlock, Robert, et al. "Update on EPA's ToxCast program: providing high-throughput decision support tools for chemical risk management." *Chemical research in toxicology* 25.7 (2012): 1287-1302.

Tice, Raymond R., et al. "Improving the human hazard characterization of chemicals: a Tox21 update." *Environmental health perspectives* 121.7 (2013): 756-765.

Richard, Ann M., et al. "ToxCast chemical landscape: paving the road to 21st century toxicology." *Chemical research in toxicology* 29.8 (2016): 1225-1251.

Filer, Dayne L., et al. "tcpl: the ToxCast pipeline for high-throughput screening data." *Bioinformatics* 33.4 (2016): 618-620.

Wambaugh, John F., et al. "Assessing Toxicokinetic Uncertainty and Variability in Risk Prioritization." *Toxicological Sciences* 172.2 (2019): 235-251.

wang2018

Wang et al. 2018 Wang et al. (2018) screened the blood of 75 pregnant women for the presence of environmental organic acids (EOAs) and identified mass spectral features corresponding to 453 chemical formulae of which 48 could be mapped to likely structures. Of the 48 with tentative structures the identity of six were confirmed with available chemical standards.

Description

Wang et al. 2018 Wang et al. (2018) screened the blood of 75 pregnant women for the presence of environmental organic acids (EOAs) and identified mass spectral features corresponding to 453 chemical formulae of which 48 could be mapped to likely structures. Of the 48 with tentative structures the identity of six were confirmed with available chemical standards.

Usage

wang2018

Format

data.frame

Source

Kapraun et al. 2021 (submitted)

References

Wang A, Gerona RR, Schwartz JM, Lin T, Sirota M, Morello-Frosch R, Woodruff TJ (2018). "A Suspect Screening Method for Characterizing Multiple Chemical Exposures among a Demographically Diverse Population of Pregnant Women in San Francisco." *Environmental Health Perspectives*, **126**(7), 077009. doi: [10.1289/EHP2920](https://doi.org/10.1289/EHP2920), <https://ehp.niehs.nih.gov/doi/abs/10.1289/EHP2920>.

well_param	<i>Microtiter Plate Well Descriptions for Armitage et al. (2014) Model</i>
------------	--

Description

Microtiter Plate Well Descriptions for Armitage et al. (2014) model from Honda et al. (2019)

Usage

well_param

Format

A data frame / data table with 11 rows and 8 variables:

sysID Identifier for each multi-well plate system

well_desc Well description

well_number Number of wells on plate

area_bottom Area of well bottom in mm²

cell_yield Number of cells

diam Diameter of well in mm

v_total Total volume of well in uL

v_working Working volume of well in uL

Author(s)

Greg Honda

Source

<https://www.corning.com/catalog/cls/documents/application-notes/CLS-AN-209.pdf>

References

Armitage, J. M.; Wania, F.; Arnot, J. A. *Environ. Sci. Technol.* 2014, 48, 9770-9779. [dx.doi.org/10.1021/es501955g](https://doi.org/10.1021/es501955g)
 Honda, Gregory S., et al. "Using the Concordance of In Vitro and In Vivo Data to Evaluate Extrapolation Assumptions", *PloS ONE* 14.5 (2019): e0217564.

Wetmore.data*Published toxicokinetic predictions based on in vitro data*

Description

This data set gives the chemical specific predictions for serum concentration at steady state resulting from constant infusion exposure, as published in a series of papers from Barbara Wetmore's group at the Hamner Institutes for Life Sciences. Predictions include the median and 90% interval in uM and mg/L. Calculations were made using the 1 and 10 uM in vitro measured clearances.

Usage

Wetmore.data

Format

A data.frame containing 577 rows and 20 columns.

Source

Wambaugh, John F., et al. "Toxicokinetic triage for environmental chemicals." *Toxicological Sciences* (2015): 228-237.

References

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Sochaski, M.A., Rotroff, D.M., Freeman, K., Clewell, H.J., Dix, D.H., Andersen, M.E., Houck, K.A., Allen, B., Judson, R.S., Sing, R., Kavlock, R.J., Richard, A.M., and Thomas, R.S., "Integration of Dosimetry, Exposure and High-Throughput Screening Data in Chemical Toxicity Assessment," *Toxicological Sciences* 125 157-174 (2012)

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Li, L., Clewell, H.J. III, Judson, R.S., Freeman, K., Bao, W., Sochaski, M.A., Chu T.-M., Black, M.B., Healy, E., Allen, B., Andersen M.E., Wolfinger, R.D., and Thomas R.S., "The Relative Impact of Incorporating Pharmacokinetics on Predicting in vivo Hazard and Mode-of-Action from High-Throughput in vitro Toxicity Assays" *Toxicological Sciences*, 132:327-346 (2013).

Wetmore, B. A., Wambaugh, J. F., Allen, B., Ferguson, S. S., Sochaski, M. A., Setzer, R. W., Houck, K. A., Strope, C. L., Cantwell, K., Judson, R. S., LeCluyse, E., Clewell, H.J. III, Thomas, R.S., and Andersen, M. E. (2015). "Incorporating High-Throughput Exposure Predictions with Dosimetry-Adjusted In Vitro Bioactivity to Inform Chemical Toxicity Testing" *Toxicological Sciences*, kfv171.

Wetmore2012*Published toxicokinetic predictions based on in vitro data from Wetmore et al. 2012.*

Description

This data set overlaps with Wetmore.data and is used only in Vignette 4 for steady state concentration.

Usage

Wetmore2012

Format

A data.frame containing 13 rows and 15 columns.

References

Wetmore, B.A., Wambaugh, J.F., Ferguson, S.S., Sochaski, M.A., Rotroff, D.M., Freeman, K., Clewell, H.J., Dix, D.H., Andersen, M.E., Houck, K.A., Allen, B., Judson, R.S., Sing, R., Kavlock, R.J., Richard, A.M., and Thomas, R.S., "Integration of Dosimetry, Exposure and High-Throughput Screening Data in Chemical Toxicity Assessment," *Toxicological Sciences* 125 157-174 (2012)

wfl	<i>WHO weight-for-length charts</i>
-----	-------------------------------------

Description

Charts giving weight-for-length percentiles for boys and girls under age 2.

Usage

wfl

Format

A data.table object with variables

Sex 'Male' or 'Female'

Length length in cm

L, M, S LMS parameters; see https://www.cdc.gov/growthcharts/percentile_data_files.htm

P2.3, P5, P10, P25, P50, P75, P90, P95, **and** P97.7 weight percentiles

Details

For infants under age 2, weight class depends on weight for length percentile. #'

Underweight <2.3rd percentile

Normal weight 2.3rd-97.7th percentile

Obese >=97.7th percentile

Author(s)

Caroline Ring

Source

https://www.cdc.gov/growthcharts/who/girls_weight_head_circumference.htm and https://www.cdc.gov/growthcharts/who/boys_weight_head_circumference.htm

References

Ring, Caroline L., et al. "Identifying populations sensitive to environmental chemicals by simulating toxicokinetic variability." *Environment International* 106 (2017): 105-118

Index

- * **1compartment**
 - calc_analytic_css_1comp, [27](#)
 - calc_elimination_rate, [34](#)
 - calc_half_life, [41](#)
 - calc_total_clearance, [67](#)
 - calc_vdist, [68](#)
 - convert_httkpop_1comp, [83](#)
 - parameterize_1comp, [144](#)
 - propagate_invitrouv_1comp, [167](#)
 - solve_1comp, [175](#)
- * **3compartment**
 - calc_analytic_css_3comp, [28](#)
 - parameterize_3comp, [146](#)
 - propagate_invitrouv_3comp, [168](#)
 - solve_3comp, [179](#)
- * **3compss**
 - calc_analytic_css_3compss, [29](#)
 - parameterize_steadystate, [159](#)
- * **Dynamic**
 - scale_dosing, [171](#)
- * **Export**
 - export_pbt_k_jarnac, [93](#)
 - export_pbt_k_sbml, [94](#)
- * **Literature**
 - get_lit_cheminfo, [103](#)
 - get_lit_css, [104](#)
 - get_lit_oral_equiv, [106](#)
- * **Monte-Carlo**
 - calc_mc_css, [52](#)
 - calc_mc_oral_equiv, [56](#)
 - calc_mc_tk, [58](#)
 - create_mc_samples, [87](#)
 - get_lit_css, [104](#)
 - get_lit_oral_equiv, [106](#)
 - monte_carlo, [140](#)
- * **Parameter**
 - available_rblood2plasma, [18](#)
 - calc_elimination_rate, [34](#)
 - calc_fetal_phys, [36](#)
 - calc_half_life, [41](#)
 - calc_hep_clearance, [45](#)
 - calc_hepatic_clearance, [43](#)
 - calc_ionization, [48](#)
 - calc_krbc2pu, [50](#)
 - calc_maternal_bw, [51](#)
 - calc_rblood2plasma, [62](#)
 - calc_total_clearance, [67](#)
 - calc_vdist, [68](#)
 - get_rblood2plasma, [108](#)
 - lump_tissues, [136](#)
 - parameterize_1comp, [144](#)
 - parameterize_3comp, [146](#)
 - parameterize_fetal_pbt_k, [148](#)
 - parameterize_gas_pbt_k, [151](#)
 - parameterize_pbt_k, [154](#)
 - parameterize_schmitt, [157](#)
 - parameterize_steadystate, [159](#)
 - predict_partitioning_schmitt, [165](#)
- * **Retrieval**
 - get_cheminfo, [98](#)
 - get_lit_cheminfo, [103](#)
- * **Solve**
 - calc_analytic_css, [24](#)
 - calc_stats, [63](#)
 - calc_tkstats, [65](#)
 - honda.i.vive, [110](#)
 - solve_1comp, [175](#)
 - solve_3comp, [179](#)
 - solve_fetal_pbt_k, [183](#)
 - solve_gas_pbt_k, [186](#)
 - solve_model, [191](#)
 - solve_pbt_k, [194](#)
- * **Statistics**
 - calc_stats, [63](#)
 - calc_tkstats, [65](#)
- * **Steady-State**
 - calc_css, [32](#)
 - calc_mc_css, [52](#)
 - calc_mc_oral_equiv, [56](#)
- * **cheminformatics**
 - get_chem_id, [101](#)
- * **datasets**
 - EPA.ref, [90](#)
 - Tables.Rdata.stamp, [203](#)
- * **data**
 - age_dist_smooth, [9](#)

- armitage_input, 16
- aylward2014, 19
- bmiage, 21
- chem.in_vivo.PK.aggregate.data, 71
- chem.in_vivo.PK.data, 71
- chem.in_vivo.PK.summary.data, 74
- chem.lists, 77
- chem.physical_and_in_vitro.data, 78
- concentration_data_Linakis2020, 82
- dawson2021, 89
- fetalpcs, 95
- Frank2018in_vivo, 95
- howgate, 112
- johnson, 130
- kapraun2019, 131
- mcnally_dt, 138
- metabolism_data_Linakis2020, 139
- nhanes_mec_svy, 141
- Obach2008, 142
- onlyp, 143
- pc.data, 161
- pearce2017regression, 162
- pharma, 162
- physiology.data, 163
- pksim.pcs, 164
- pradeep2020, 164
- pregnonpregaucs, 167
- sipes2017, 172
- spline_heightweight, 200
- spline_hematocrit, 200
- spline_serumcreat, 201
- supptab1_Linakis2020, 202
- supptab2_Linakis2020, 202
- tissue.data, 203
- wambaugh2019, 206
- wambaugh2019.nhanes, 207
- wambaugh2019.raw, 208
- wambaugh2019.seem3, 210
- wambaugh2019.tox21, 210
- wang2018, 211
- well_param, 212
- Wetmore.data, 213
- Wetmore2012, 213
- wfl, 214
- * dynamic**
 - calc_mc_tk, 58
- * httk-pop**
 - age_dist_smooth, 9
 - age_draw_smooth, 10
 - blood_mass_correct, 20
 - blood_weight, 21
 - bmiage, 21
 - body_surface_area, 22
 - bone_mass_age, 23
 - brain_mass, 24
 - ckd_epi_eq, 81
 - convert_httkpop_1comp, 83
 - estimate_gfr, 91
 - estimate_gfr_ped, 91
 - estimate_hematocrit, 92
 - gen_age_height_weight, 96
 - gen_height_weight, 97
 - gen_serum_creatinine, 98
 - get_gfr_category, 102
 - get_weight_class, 109
 - hematocrit_infants, 110
 - httkpop, 112
 - httkpop_biotophys_default, 117
 - httkpop_direct_resample, 117
 - httkpop_direct_resample_inner, 119
 - httkpop_generate, 120
 - httkpop_mc, 122
 - httkpop_virtual_indiv, 123
 - is_in_inclusive, 130
 - kidney_mass_children, 132
 - liver_mass_children, 132
 - lung_mass_children, 138
 - mcnally_dt, 138
 - nhanes_mec_svy, 141
 - pancreas_mass_children, 143
 - rfun, 170
 - skeletal_muscle_mass, 173
 - skeletal_muscle_mass_children, 174
 - skin_mass_bosgra, 174
 - spleen_mass_children, 199
 - spline_heightweight, 200
 - spline_hematocrit, 200
 - spline_serumcreat, 201
 - tissue_masses_flows, 204
 - tissue_scale, 205
 - wfl, 214
- * in-vitro**
 - calc_hep_fu, 47
 - invitro_mc, 126
- * monte-carlo**
 - httkpop_biotophys_default, 117
 - httkpop_direct_resample, 117
 - httkpop_direct_resample_inner, 119
 - httkpop_generate, 120
 - httkpop_mc, 122
 - httkpop_virtual_indiv, 123
 - invitro_mc, 126
 - propagate_invitrouv_1comp, 167
 - propagate_invitrouv_3comp, 168

- propagate_invitrouv_pbt, 168
- * **package**
 - httk-package, 6
- * **pbt**
 - calc_analytic_css_pbt, 31
 - parameterize_pbt, 154
 - propagate_invitrouv_pbt, 168
 - solve_pbt, 194
- * **physiology**
 - calc_hep_bioavailability, 44
- * **schmitt**
 - parameterize_schmitt, 157
- * **simulation**
 - calc_mc_tk, 58
- add_chemtable, 7, 17
- age_dist_smooth, 9
- age_draw_smooth, 10
- armitage_estimate_sarea, 11
- armitage_eval, 12
- armitage_input, 16
- augment.table, 17
- available_rblood2plasma, 18
- Aylward2014 (aylward2014), 19
- aylward2014, 19
- blood_mass_correct, 20
- blood_weight, 20, 21
- bmiage, 21
- body_surface_area, 22
- bone_mass_age, 23
- brain_mass, 24
- calc_analytic_css, 24, 54
- calc_analytic_css_1comp, 27
- calc_analytic_css_3comp, 28
- calc_analytic_css_3compss, 29
- calc_analytic_css_pbt, 31
- calc_css, 32
- calc_elimination_rate, 34, 167
- calc_fetal_phys, 36
- calc_half_life, 41
- calc_hep_bioavailability, 44
- calc_hep_clearance, 43, 45, 168, 169
- calc_hep_fu, 47
- calc_hepatic_clearance, 43
- calc_ionization, 48
- calc_krbc2pu, 50
- calc_maternal_bw, 51
- calc_mc_css, 52, 56, 57
- calc_mc_oral_equiv, 56
- calc_mc_tk, 58
- calc_rblood2plasma, 62
- calc_stats, 63
- calc_tkstats, 63, 65
- calc_total_clearance, 67
- calc_vdist, 68
- CAS.checksum, 70
- chem.invivo.PK.aggregate.data, 71
- chem.invivo.PK.data, 71
- chem.invivo.PK.summary.data, 74
- chem.lists, 77
- chem.physical_and_invitro.data, 78, 99
- ckd_epi_eq, 81
- concentration_data_Linakis2020, 82
- convert_httkpop_1comp, 83
- convert_solve_x, 83
- convert_units, 84, 85, 85
- create_mc_samples, 83, 87
- Dawson2021 (dawson2021), 89
- dawson2021, 89
- EPA.ref, 90
- estimate_gfr, 91
- estimate_gfr_ped, 91
- estimate_hematocrit, 92
- export_pbt_jarnac, 93
- export_pbt_sbml, 94
- fetalPCs (fetalpcs), 95
- fetalpcs, 95
- Frank2018invivo, 95
- gen_age_height_weight, 96
- gen_height_weight, 97
- gen_serum_creatinine, 98
- get_chem_id, 101
- get_cheminfo, 98
- get_gfr_category, 102
- get_invitroPK_param, 103
- get_lit_cheminfo, 103
- get_lit_css, 104
- get_lit_oral_equiv, 106
- get_physchem_param, 107
- get_rblood2plasma, 108
- get_weight_class, 109
- hematocrit_infants, 110
- honda.ivive, 110
- howgate, 112
- httk (httk-package), 6
- httk-package, 6
- httkpop, 112
- httkpop-package (httkpop), 112
- httkpop_biotophys_default, 117

- httkpop_direct_resample, 117
- httkpop_direct_resample_inner, 119
- httkpop_generate, 54, 60, 83, 88, 89, 114, 120, 122
- httkpop_mc, 114, 122
- httkpop_virtual_indiv, 123
- in.list, 125, 129
- invitro_mc, 53, 60, 89, 126
- is.expocast (in.list), 125
- is.httk, 126, 128
- is.nhanes (in.list), 125
- is.pharma (in.list), 125
- is.tox21 (in.list), 125
- is.toxcast (in.list), 125
- is_in_inclusive, 130
- johnson, 130
- Kapraun2019 (kapraun2019), 131
- kapraun2019, 131
- kidney_mass_children, 132
- liver_mass_children, 132
- load_dawson2021, 79, 133
- load_pradeep2020, 79, 134
- load_sipes2017, 79, 135
- lump_tissues, 136
- lung_mass_children, 138
- mcnally_dt, 138
- metabolism_data_Linakis2020, 139
- monte_carlo, 140
- nhanes_mec_svy, 141
- Obach2008, 142
- onlyp, 143
- pancreas_mass_children, 143
- parameterize_1comp, 144
- parameterize_3comp, 146
- parameterize_fetal_pbt, 148
- parameterize_gas_pbt, 151
- parameterize_pbt, 154
- parameterize_schmitt, 62, 157, 166
- parameterize_steadystate, 159
- pc.data, 161
- Pearce2017Regression (pearce2017regression), 162
- pearce2017regression, 162
- pharma, 162
- physiology.data, 163
- pksim.pcs, 164
- Pradeep2020 (pradeep2020), 164
- pradeep2020, 164
- predict_partitioning_schmitt, 62, 165
- pregnonpregaucs, 167
- propagate_invitrouv_1comp, 83, 167
- propagate_invitrouv_3comp, 168
- propagate_invitrouv_pbt, 168
- r_left_censored_norm, 170
- reset_httk, 169
- rfun, 170
- scale_dosing, 86, 171
- set_httk_precision, 172
- Sipes2017 (sipes2017), 172
- sipes2017, 172
- skeletal_muscle_mass, 173
- skeletal_muscle_mass_children, 173, 174, 174
- skin_mass_bosgra, 174
- solve_1comp, 175
- solve_3comp, 179
- solve_fetal_pbt, 183
- solve_gas_pbt, 186
- solve_model, 60, 191
- solve_pbt, 33, 194
- spleen_mass_children, 199
- spline_heightweight, 200
- spline_hematocrit, 200
- spline_serumcreat, 201
- supptab1_Linakis2020, 202
- supptab2_Linakis2020, 202
- Tables.Rdata.stamp, 203
- tissue.data, 203
- tissue_masses_flows, 204
- tissue_scale, 205
- wambaugh2019, 206
- wambaugh2019.nhanes, 207
- wambaugh2019.raw, 208
- wambaugh2019.seem3, 210
- wambaugh2019.tox21, 210
- Wang2018 (wang2018), 211
- wang2018, 211
- well_param, 212
- Wetmore.data, 213
- Wetmore2012, 213
- wfl, 214